

LIST OF FIGURES

2.1	Typical XAFS spectrum	32
2.2	Physics of X-ray Absorption	33
2.3(a)	(a) X-ray absorption by a free atom	33
2.3(b)	X-ray absorption in the presence of neighboring atoms	33
2.4	Dependence of (a) scattering amplitude $F(k)$ and (b) phase shift $\delta(k)$ on scatterer type	39
2.5(a)	Single Scattering path for photo electron	42
2.5(b)	Double scattering path for photo electron	42
2.6	Typical XANES spectrum. XANES can be used to qualitatively detect (a) oxidation state, (b) site symmetry.	45
3.1	Synchrotron radiation from Bending Magnet source	49
3.2	Generations of synchrotron sources	51
3.3	Time dependence of voltage of RF cavity	55
3.4	Electron bunches moving in the storage ring produce radiation peaks having the same bunch length (ps) and separation (ns)	55
3.5	Radiation pattern for electron in circular orbit when (a) $v \ll c$ and (b) $v \sim c$	57
3.6	Spectral flux vs (a) wavelength and (b) photon energy of synchrotron.	57
3.7	Schematic of insertion devices	59
3.8	Comparison of spectra from Bending Magnet, Undulator and Wiggler.	60
3.9(a)	Schematic of XAFS experiment using monochromator	64
3.9(b)	Schematic of XAFS experiment using polychromator	65
3.10	Absorption spectrum of Ga foil at Ga K edge (10.368 keV) obtained with the Si(111) monochromator (a) set within one third the energy region of Ga K-edge. This is clearly due to third harmonic contamination, (b) true absorption spectrum.	66
3.11	Detuning of monochromator to eliminate higher energy harmonics	67

3.12	Reflectivity of Rh as function of angle	68
3.13	Experimental geometry for (a) Transmission mode and (b) Fluorescence mode XAFS	69
3.14	Efficiency of an ionization chamber as a function of energy for different gases at normal pressure.	71
3.15	Concept of usage of Lytle detectors. $Z - 1$ filters preferentially absorb elastic scatter above the filter's absorption edge. The slits transmit the sample fluorescence, but block most of the filter re-fluorescence.	73
3.16	(a) Aluminium sample holder for powder pellets/tapes; (b) Liquid sample holder; (c) Schematic of moisture proof sample holder for measurements under low temperature	78
3.17	Example of noise in XAFS data	80
4.1	Schematic of XAFS data analysis	82
4.2	Data Analysis Flowchart	83
4.3	Contour map of χ^2 as a function of two variables x and y	95
5.1	Schematic of beamline operating in (a) energy dispersive mode and (b) energy scanning mode.	98
5.2	Optical layout of B1-08	100
5.3	Comparison (k -space) linearly calibrated Indus-2 Ni foil data with data from NSLS	102
5.4	Comparison of standard NSLS data with non-linear calibrated Indus-2 data	105
5.5	Plot of (a) α vs k ; (b) amplitude ratios (for Indus-2 data w.r.t. NSLS data) vs k .	106
5.6	As K edge XANES data on $\text{PrOFe}_{0.9}\text{Co}_{0.1}\text{As}$ as function of pressure	110
5.7	(a) Schematic of Diamond Anvil Cell, (b) Plot of diamond thickness vs transmitted x-ray intensity through diamond.	111
5.8	Modified optical layout of BL-08 after inclusion of bendable elliptical post-mirror M_1	113
5.9	Post-mirror design	115
5.10	Transmitted intensity through the sample without DAC (black curve) and with DAC (red curve).	116

5.11	(a) Space available between CC and S ₁ , (b) Plot of ΔE and k_{\max} vs E for $(q_H)_{\min}$	118
5.12	Horizontal and vertical focusing	119
5.13	Photograph of the beamline with the post mirror in place	120
5.14	(a) Post mirror parameters, (b) Footprint of beam on the post mirror	120
5.15	Tilting the mirror	123
5.16	Schematic diagram of elliptically bent mirror	123
5.17	Number of steps required for motors M _A and M _B , to obtain focused spot	124
5.18	XAFS spectrum of Cu foil	125
5.19	Plot of (a) q_H vs horizontal spot size σ_H , and (b) M1 demagnification vs q_H	125
5.20	Focal spot photograph	128
5.21	Schematic diagram of low temperature setup	132
5.22	Schematic diagram of low temperature setup. Green arrows depict He being supplied to the expander for cooling. Red arrows depict return cycle of He.	133
5.23	Schematic diagram of BL-09	134
5.24	Photograph of (a) BL-09 experimental station with the cryostat in place, (b) Cu sample holder	135
5.25	Comparison of Au foil XAFS data recorded outside and inside the cryostat at room temperature in (a) k-space, (b) R-space	136
5.26	Initial attempt at low temperature data collection	137
5.27	Temperature dependent XAFS data on Au foil recorded at BL-09 in (a) k-space, (b) R-space	138
5.28	Comparison of RT Au foil data (Indus-2) (blue line) with standard Au foil (RT) data from APS (USA) (green line). Phase mismatch between the two data could be corrected with small energy correction $\Delta E_0=3\text{eV}$ (red line).	139
5.29	Comparison between data and fit for Au foil data at RT and at 50K.	140
5.30	(a). Evolution of DWF with temperature. Strategies (i) and (ii)	141

involve fitting the data without using Debye Model. In (i), datasets for different temperatures were fit individually while in (ii), they were fit simultaneously. Strategy (iii) involved simultaneous fitting of the datasets using Debye Model. [Inset shows the derivative of the theoretical curves for different Θ_D (160K, 165K, 170K). Θ_D (marked by solid square) represents the Temperature beyond which the rate of change of derivative remains constant. (b) Plot of temperature of foil (T') vs temperature readout of the sensor (T_{set})

6.1	Schematic of the deposited multilayer	146
6.2	XTEM micrographs of (a) pristine and (b) irradiated (ion fluence = 2×10^{15} ions/cm ²) samples.	148
6.3	Illustration of formation of standing waves of X-rays in Pt/Ni/C Multilayer. As the angle of incidence increases through the diffraction peak region (top), antinodes move from the low electron-density medium (C layers) to the high electron-density medium (Pt layers) (bottom).	148
6.4	(A) X-ray Reflectivity of pristine and irradiated multilayers. (B) (a) Reflectivity under first order Bragg peak and integrated field intensities in 1-Pt layer, 2-Ni layer and 3-C layer. Reflectivity data and fluorescence yield for (b) pristine and (c) irradiated samples.	149
6.5.	(a) First order Bragg peak; the positions of antinodes and nodes of the X-ray standing wave (XSW) formed within the first few layers (7 consecutive layers from surface) of our graded Pt/Ni/C multi-trilayer in (b) Pristine ML and (c) Irradiated ML. The black curve corresponds to the angle chosen in left (lower angle) side of the Bragg peak (BP) while the blue curve corresponds to the angle chosen at the right (high angle) side of the BP.	152
6.6	a. Comparison of data in k -space before and after irradiation for (a) Ni/C interface and (b) Ni/Pt interface	154
	b. Comparison of data with fit	154
6.7	Structural model for the multilayer before and after irradiation.	158
6.8	XANES at (a) Ni/C interface and (b) Ni/Pt interface	158
6.9	(a) Various cluster models considered, (b) final model for embedded clusters in C layers	159
6.10	Fourier Transform for both the MLs at Ni/Pt interface	161
7.1	Schematic of SHI induced modification	168
7.2	Ag/Pt phase diagram	169

7.3	Structural characterization of pristine system: (a) TEM, (b) XRD pattern, (c) Absorption spectrum, (d) Selective area diffraction pattern	173
7.4	Pt L3 edge XAFS data for pristine Ag/Pt system	175
7.5	Plot of (a) N, (b) σ^2 and (c) R vs. irradiation fluence for pristine Ag/Pt system	175
7.6	XANES spectra at (a) Pt L3 edge and (b) Ag K edge for the pristine Ag/Pt system	176
7.7	Ag K edge XAFS data for pristine Ag/Pt system	176
7.8	Simulations for fcc structure around Ag with different Ag:Pt ratios	178
7.9	Possible models for the pristine system: (a) Ag and Pt exist as separate clusters, (b) Ag@Pt core-shell. Note that the shell like feature around Ag represents disordered higher shell features of Ag.	178
7.10	XAFS data for pristine Au/Ag system (a) Ag K edge, (b) Au L3 edge	179
7.11	XAFS fit results for Au/Ag system. Plot of (a) N, (b) σ^2 and (c) R as function of SHI fluence.	180
7.12	Structural characterization of SHII Ag/Pt system: (a) TEM, (b) XRD pattern, (c) Absorption spectrum, (d) Selective area diffraction pattern	181
7.13	XAFS data for the SHII Ag/Pt samples at (a) Pt L3 edge, (b) Ag K edge	182
7.14	Example of fit quality for (a) Pt edge, (b) Ag edge	183
7.15	XANES spectra for the SHII samples at (a) Pt edge and (b) Ag edge	183
7.16	Possible models for the SHII Ag/Pt systems	184
7.17	XAFS data for the SHII Au/Ag samples at (a) Ag K edge, (b) Au L3 edge	185
8.1	Pre-XAFS characterization of <i>Rasasindura</i> in comparison with Laboratory synthesized Red <i>HgS</i> using : (a) XRD, (b) XRF, (c) Raman and (d) SERS.	193
8.2	Comparison of <i>Hg L3</i> edge XAFS data on <i>Rasasindura</i> and Red (α)- <i>HgS</i> with simulated XAFS data for α - and β - <i>HgS</i> . It is clear that the data for <i>Rasasindura</i> resembles α - <i>HgS</i> (<u>not</u> β - <i>HgS</i>).	195
8.3	Comparison between (a) derivatives of XANES data on α - <i>HgS</i> , Hg^0 and <i>Rasasindura</i> . <i>Rasasindura</i> closely resembles α - <i>HgS</i> . Clearly in	197

	<i>Rasasindura</i> , (i) edge position is shifted wrt Hg^0 ($E_{shift} = 5eV$) and (ii) pre-edge features are present which are absent in $Hg(0)$. (b) Simulated derivative spectra for different fractions (x_{Hg^0}) of Hg^0	
8.4	XAFS fit results for <i>Rasasindura</i> and Red (α)- HgS (lab). <i>Rasasindura</i> is more ordered than Red (α)- HgS (lab).	198
8.5	Simulations for different values of σ_{Hg-Hg}^2 : (a) XAFS simulations (b) XRD simulations. XRD spectrum is insensitive to σ_{Hg-Hg}^2 variation up to $\sigma_{Hg-Hg}^2 = 0.035\text{\AA}^2$. From XAFS simulations, $Hg-Hg$ features are suppressed for $\sigma_{Hg-Hg}^2 \geq 0.025\text{\AA}^2$	199
8.6	(a) Structure of α - HgS comprises of parallel $-S-Hg-S-Hg-S-$ chains along c-axis. (b) Compression of one of the chains (defect) affects $Hg-Hg$ (green arrows) substantially.	199
8.7	Model of <i>Rasasindura</i> nano-crystal with 24 nm HgS core.	202

LIST OF TABLES

3.1	Comparison of Indus-2 Source parameters with popular sources across the world	58
3.2	Choice of experimental geometry for XAFS	69
3.3	Summary of Detectors	74
5.1	Optical Elements of BL-08	101
5.2	Structural parameters obtained from XAFS data fitting	103
5.3	k'' values generated for the first segment	107
5.4	Characteristics of diamonds used for HP-XAFS	112
5.5	Spot size at q _H : $H \times V = \sigma_H \times \sigma_V$	113
5.6	Post Mirror Specifications	115
5.7	BL-08 parameters at E ₀ =10keV	118
5.8	Parameters for post mirror M1	121
5.9	Summary of alignment procedure for M1	126
5.10	Post mirror focusing parameters	127
5.11	Specifications of XAFS compatible cryostat	129
5.12	XAFS Fit results for Au foil	142
6.1	XAFS coordination analysis steps for Ni/C interface	155
6.2	XAFS fit results for Pt/Ni/C multilayer	157
7.1	Structural characterization of Pristine System	173
7.2	XAFS fit results for Ag/Pt system	177
7.3	Structural Characterization of SHII systems	182
8.1	Characterization of <i>Rasasindura</i> and Red <i>HgS</i>	193
8.2	Comparison of bond lengths (<i>R</i>)	198

