

# LIST OF FIGURES

Figure		Page No.
<b>Chapter 1</b>		
<b>Figure 1.1</b>	Outline of general introduction of IPMC	08
<b>Figure 1.2</b>	SEM image showing surface morphology of a nafion based IPMC membrane (a) and actual view of fabricated nafion based IPMC membrane actuator (b)	10
<b>Figure 1.3</b>	Chemical structure of nafion (perfluorinated sulfonic acid ionic polymer)	11
<b>Figure 1.4</b>	Graphical representation of bending mechanism of IPMC membrane actuator	13
<b>Figure 1.5</b>	Scanning electron micrograph shows the three layers in an electroless plated IPMC membrane	16
<b>Figure 1.6</b>	Fabrication of IPMC by stacking and hot press techniques	26
<b>Figure 1.7</b>	Effects of various cations on the actuation of the IPMC muscle	32
<b>Figure 1.8</b>	Applications of IPMCs in different areas	33
<b>Chapter 2</b>		
<b>Figure 2.1</b>	Graphical representation of bending mechanism for IPMC membrane	66
<b>Figure 2.2</b>	Water uptake of kraton and nafion based IPMCs membranes at room temperature (R.T.), 45 and 65 °C for a time period of 4, 6, 8, 10, 20 and 24 h	68
<b>Figure 2.3</b>	SEM micrographs of kraton and nafion polymer membrane based IPMCs actuator before actuation (a) kraton, (b) nafion and after actuation (c) kraton (d) nafion, respectively	71
<b>Figure 2.4</b>	Cross-sectional SEM micrographs of kraton membrane (a) and nafion membrane (b) based IPMCs actuator showing deposition of Pt metal electrode layer	72
<b>Figure 2.5</b>	Water loss from nafion and kraton based IPMC actuator at	73

3 V electrical potential for different time period of 5, 8 and 10 min

<b>Figure 2.6</b>	Cyclic voltammetric curves of kraton and nafion polymer IPMC membranes at $\pm 3$ V triangle triangle voltage with a scan rate of $100 \text{ mV s}^{-1}$	75
<b>Figure 2.7</b>	LSV curves of kraton and nafion polymer membranes based IPMC actuator at 3 V with a scan rate of $100 \text{ mV s}^{-1}$	76
<b>Figure 2.8</b>	Displacement images of kraton and nafion IPMC membranes at varying times under 3 V dc	77

---

### Chapter 3

---

<b>Figure 3.1</b>	Graphical representation for the fabrication and bending of an IPMC membrane	86
<b>Figure 3.2</b>	% Water uptake of SPVA-Py ionic polymer membrane at room temperature (R.T.) and $45^\circ\text{C}$	89
<b>Figure 3.3</b>	SEM micrographs of SPVA-Py-Pt membrane (a, c) before actuation (b, d) after actuation and (e) cross sectional image showing Pt plating	93
<b>Figure 3.4</b>	FTIR spectrum of SPVA-Py-Pt IPMC membrane	94
<b>Figure 3.5</b>	% Water loss of SPVA-Py-Pt IPMC membrane	95
<b>Figure 3.6</b>	Microstructure behaviour of SPVA-Py-Pt IPMC membranes	96
<b>Figure 3.7</b>	Current-voltage (I-V) hysteresis curve of SPVA-Py-Pt IPMC membrane at $\pm 6$ V with a scan rate of $100 \text{ mV sec}^{-1}$	97
<b>Figure 3.8</b>	Electrical circuit for improving the I-V performance	98
<b>Figure 3.9</b>	Linear sweep voltammetry (LSV) of SPVA-Py-Pt membrane at 3 V with a scan rate of $100 \text{ mV sec}^{-1}$	99
<b>Figure 3.10</b>	Schematic diagram for analyzing the bending behaviour of IPMC actuator	101
<b>Figure 3.11</b>	Actual test setup for measuring bending behaviour of the IPMC actuator	102
<b>Figure 3.12</b>	Bending behaviour of IPMC actuator	103
<b>Figure 3.13</b>	Bending behaviour of the SPVA-Py-Pt membrane based	106

	IPMC actuator	
<b>Figure 3.14</b>	Testing setup for tip force response of an SPVA-Py-Pt based ionic actuator	107
<b>Figure 3.15</b>	Normal distribution function for the SPVA-Py-Pt based ionic actuator	109
<b>Figure 3.16</b>	CAD model of an SPVA-Py-Pt based IPMC actuator based micro-gripping system	112
<b>Figure 3.17</b>	Detailed dimensions of IPMC based micro-gripper	113

---

#### Chapter 4

---

<b>Figure 4.1</b>	Schematic diagram for PAN-KR-GR-Pt IPMC based dexterous handling system (a) and PAN-KR-GR-Pt based micro-gripper (b)	126
<b>Figure 4.2</b>	% Water uptake of PAN-KR-GR based membrane at room temperature (R.T.) and 45°C for different time intervals	128
<b>Figure 4.3</b>	% Water loss of PAN-KR-GR-Pt-based IPMC membrane at 3, 4, 5, and 6 V for different time interval	131
<b>Figure 4.4</b>	Scanning electron microscopic images of PAN-KR-GR-Pt-based IPMC membrane at different magnifications showing surface morphology (a and c) before actuation, (b and d) after actuation, and (e) cross-sectional image	133
<b>Figure 4.5</b>	FTIR spectrum of PAN-KR-GR polymer composite membrane	134
<b>Figure 4.6</b>	XRD spectrum of PAN-KR-GR composite polymer membrane	135
<b>Figure 4.7</b>	TGA spectra showing thermal stability of PAN-KR-GR polymer membrane and PAN-KR-GR-Pt-based IPMC membrane	136
<b>Figure 4.8</b>	Cyclic voltammetry curve of PAN-KR-GR-Pt-based IPMC membrane at $\pm 3$ V	137
<b>Figure 4.9</b>	Linear sweep voltammetry curve of PAN-KR-GR-Pt based IPMC membrane at 3 V	138
<b>Figure 4.10</b>	Schematic diagram for bending behavior of PAN-KR-GR-	139

	Pt-based ionic actuator	
<b>Figure 4.11</b>	Actual test setup for bending behavior of PAN-KR-GR-Pt-based ionic actuator	141
<b>Figure 4.12</b>	Bending behaviour of PAN-KR-GR-Pt-based ionic actuator	142
<b>Figure 4.13</b>	Forward and reverse bending behaviors of PAN-KR-GR-Pt-based ionic actuator	144
<b>Figure 4.14</b>	Measurement test setup for tip force response of PAN-KR-GR-Pt-based actuator (a) schematic diagram of test setup for the tip load of IPMC and (b) actual test setup	146
<b>Figure 4.15</b>	Normal distribution function for PAN-KR-GR-Pt based IPMC actuator	148
<b>Figure 4.16</b>	Dexterous handling device using PAN-KR-GR-Pt IPMC membrane	149

---

### Chapter 5

---

<b>Figure 5.1</b>	Schematic diagram for analyzing the bending behaviour of KR-Ag-Pw IPMC actuator	157
<b>Figure 5.2</b>	Actual test setup for bending behaviour of KR-Ag-Pw IPMC actuator	158
<b>Figure 5.3</b>	Water uptake of KR-Ag-Pw ionic polymer actuator membrane at room temperature (R.T.), 45 °C and 65 °C for different interval of time	160
<b>Figure 5.4</b>	Water loss of KR-Ag-Pw ionic polymer membrane at 3, 4, 5 and 6 V for 3, 6 and 9 min. of time interval	161
<b>Figure 5.5</b>	Scanning electron microscopic images of kraton membrane (a) KR-AgPw ionic polymer membrane (b,d) before and (c,e) after applied electric potential	163
<b>Figure 5.6</b>	FTIR spectra of KR and KR-Ag-Pw polymer membranes	164
<b>Figure 5.7</b>	TGA curves of KR and KR-AgPw polymer membranes	165
<b>Figure 5.8</b>	X-ray diffraction pattern of KR and KR-Ag-Pw ionomeric polymer membrane	167
<b>Figure 5.9</b>	Cyclic voltammetric curve of KR-Ag-Pw ionic polymer	168

membrane actuator at triangle voltage input of 3.5 V with a step of 50 mV s<sup>-1</sup>

<b>Figure 5.10</b>	Linear sweep voltammetric curve of KR-Ag-Pw ionic polymer actuator membrane at 3.5 V with a step of 50 mV s <sup>-1</sup>	169
<b>Figure 5.11</b>	Bending behaviour of KR-AgPw IPMC actuator	170
<b>Figure 5.12</b>	Bending behavior of KR-Ag-Pw based ionic actuator	172
<b>Figure 5.13</b>	Mean force value of KR-Ag-Pw based ionic polymer	175
<b>Figure 5.14</b>	Normal distribution function for KR-Ag-Pw based ionic actuator	176
<b>Figure 5.15</b>	Strain behavior of KR-Ag-Pw ionic polymer	177
<b>Figure 5.16</b>	Multi fingers based micro-gripping system using KR-Ag-Pw based ionic actuator	179

---

## Chapter 6

---

<b>Figure 6.1</b>	% Water uptake of KR-GR and SPEEK polymer membrane at room temperature and 45 °C	189
<b>Figure 6.2</b>	% Water loss of KR-GR-Pt and SPEEK-Pt IPMC membranes actuators	191
<b>Figure 6.3</b>	XRD spectrum of KR-GR and SPEEK polymer membrane	193
<b>Figure 6.4</b>	Scanning electron microscopic images of KR-GR-Pt and SPEEK-Pt IPMC membranes before actuation (a, c) and after actuation (b, d) and cross sectional images (e, f)	195
<b>Figure 6.5</b>	EDX graphs of KR-GR-Pt (a, b) and SPEEK-Pt (c, d) shows the elemental composition of IPMC membrane actuators	196
<b>Figure 6.6</b>	XRD spectrum of KR-GR and SPEEK polymer membrane	197
<b>Figure 6.7</b>	TGA spectra showing thermal stability of KR-GR-Pt and SPEEK-Pt membrane actuator	198
<b>Figure 6.8</b>	CV curves of KR-GR-Pt and SPEEK-Pt IPMC membranes recorded under a ±3.5 V voltage with 50 mV s <sup>-1</sup> scan rate	199
<b>Figure 6.9</b>	LSV curves of KR-GR-Pt and SPEEK-Pt IPMC membranes recorded under a 3.5 V voltage with 50 mV s <sup>-1</sup> scan rate	200

<b>Figure 6.10</b>	Layout for analysing the bending of KR-GR-Pt based IPMC actuator	<b>201</b>
<b>Figure 6.11</b>	Experimental testing setup for actuating the KR-GR-Pt composite polymer	<b>203</b>
<b>Figure 6.12</b>	Different bending position of KR-GR-Pt based IPMC actuator	<b>204</b>
<b>Figure 6.13</b>	Deflection characteristics of KR-GR-Pt composite polymer	<b>206</b>
<b>Figure 6.14</b>	Experimental testing load setup for KR-GR-Pt based IPMC actuator	<b>207</b>
<b>Figure 6.15</b>	Normal distribution curve for KR-GR-Pt ionic actuator	<b>210</b>
<b>Figure 6.16</b>	A prototype of multi KR-GR-Pt ionic fingers based gripping system	<b>211</b>