

LIST OF TABLES

Table No.	Title	Page No.
3.1	Fibre Testing Instruments	36
3.2	Yarn Testing Instruments	36
3.3	Fabric Testing Instruments	37
3.4	Blending of fibres	40
3.5	Specifications of machines used for yarn development	41
3.6	Technical parameters for spinning:	42
3.7	Spinning Parameters	42
4.1	Diameter of fibres	67
4.2	Length of fibres	69
4.3	Strength of fibres	71
4.4	Crimp of Fibres	73
4.5	Moisture regain and moisture content of fibres	74
4.6	Amount of twist in yarns	76
4.7	Count of yarns	78
4.8	Strength characteristics of yarns	79
4.9	Unevenness in yarns	82
4.10	Fabric count	84
4.11	Weight of fabrics	86
4.12	Thickness of the fabric	88
4.13	Cover Factor of woven fabric	90
4.14	Tightness factor of knitted fabrics	91
4.15	Stitch length of knitted fabric	92
4.16	Tearing strength of fabrics	94
4.17	Bursting strength of the knitted fabrics	97
4.18	Tensile strength of fabrics	98
4.19	Abrasion resistance of fabrics	99

Table No.	Title	Page No.
4.20	Pilling grade of fabric	101
4.21	Air-permeability of fabrics	103
4.22	Thermal insulation of fabrics	105
4.23	Wicking time of fabric	107
4.24	Bending length of fabrics	109
4.25	Percent drape coefficient of the fabric	112
4.26	Weighted mean score of hand of fabrics	114
4.27	Crease recovery of fabrics	115
4.28	Co-efficient of friction of fabrics	118
4.29	Thickness and surface thickness of fabric	119
4.30	Bending rigidity and shear rigidity	121
4.31	Extensibility of fabrics	123
4.32	Dimensional Stability and Formability of Woven and Knitted Fabrics	125
4.33	Felting shrinkage in woven fabrics	128
4.34	Felting shrinkage in knitted fabrics	128
4.35	Percent dye exhaustion	130
4.36	Percent dye exhaustion for vegetable dye (madder)	131
4.37	Colour fastness to light	132
4.38	Colour fastness to dry-cleaning	133
4.39	Colour fastness to washing	133
4.40	Colour fastness to perspiration	134
4.41	Colour fastness to rubbing	134
4.42	Colour Fastness to Ironing	135
4.43	Raw material cost	135
4.44	Manufacturing cost of yarn	136
4.45	Cost of Fabric	136
4.46	Cost of Individual Garments	137
4.47	Acceptability of developed prototypes	138