

LIST OF TABLES

| TABLE NO. | TITLE | PAGE NO. |
|------------------|---|-----------------|
| 4.1 | Fuzzy If-Then rules of ANFIS | 61 |
| 7.1 | Frequency band of detailed components of DWT | 87 |
| 8.1 | Specifications of DWT-Artificial Neural Network | 97 |
| 8.2 | Training pattern of DWT- ANN method | 98 |
| 8.3 | Identification rates of DWT-ANN approach | 101 |
| 8.4 | Specifications of FFT-ANFIS network | 104 |
| 8.5 | FFT-ANFIS network output pattern for switch fault | 105 |
| 8.6 | Identification rates of FFT-ANFIS network | 108 |
| 8.7 | Specifications of DWT-ANFIS Network | 110 |
| 8.8 | DWT-ANFIS Network Output Training Pattern for Fault Cases | 111 |
| 8.9 | DWT-ANFIS Fault Identification rate (%) at different Membership Function | 115 |
| 8.10 | Table 9 Fault Identification rate (%) at different approaches | 116 |

LIST OF FIGURES

| FIGURE NO. | TITLE | PAGE NO. |
|------------|--|----------|
| 1.1 | Block diagram of adjustable ac drive system connected with an inverter | 2 |
| 1.2 | Schematic of 3 ϕ IGBT Inverter module connected with motor | 3 |
| 1.3 | Classic multilevel converter topologies. (a) 3L- NPC featuring IGCTs. (b) Three-level FC featuring MV-IGBTs. (c) Five-level CHB featuring LV-IGBTs. | 6 |
| 1.4 | Schematic diagram of single phase cascaded H- bridge multilevel inverter | 8 |
| 1.5 | Conventional fault diagnosis and protection system of voltage source inverter drive | 13 |
| 3.1 | Discretely sampled data of sine wave signal | 44 |
| 3.2 | Frequency spectrum of sine wave signal | 44 |
| 3.3 | Schematic implementation of MRSD | 49 |
| 3.4 | Overview of signal decomposition using DWT | 50 |
| 3.5 | Block diagram representation of wavelet coefficients | 50 |
| 3.6 | Daubechies 4 wavelet function | 52 |
| 4.1 | Model of a neuron | 55 |
| 4.2 | Schematic of artificial neural network. | 56 |
| 4.3 | Processing of output of each neuron from sigmoid function | 57 |

| FIGURE NO. | TITLE | PAGE NO. |
|-------------------|---|-----------------|
| 4.4 | Schematic of ANFIS for Sugeno-type fuzzy inference system | 59 |
| 5.1 | Schematic of a typical 3 ϕ cascaded H-Bridge multilevel inverter with induction motor load. | 64 |
| 5.2 | Schematic diagram of single phase cascaded H-Bridge five level inverter with Z_L load. | 65 |
| 5.3 | Schematic diagram of 1 ϕ cascaded H-Bridge five level inverter connected with induction motor load. | 66 |
| 5.4 | Triangular carrier signals and sinusoidal reference signal used in the pulse width modulation. $m=0.85$. $f_c=3$ kHz. | 67 |
| 5.5 | Sinusoidal pulse width modulated switching pulses of cell A generated with carrier frequency 3 kHz and modulation index 0.85. | 67 |
| 5.6 | Laboratory experimental setup | 68 |
| 5.7 | Data acquisition system interfaced with LabVIEW software in PC | 69 |
| 5.8 | National Instruments USB-6251 hardware for collecting output voltage signals | 69 |
| 6.1 | Output voltage and load current waveform before and after S1A open circuit fault initiation with induction motor load | 72 |
| 6.2 | Output voltage and load current waveform after S2A open circuit fault with induction motor load | 72 |

| FIGURE NO. | TITLE | PAGE NO. |
|-------------------|--|-----------------|
| 6.3 | Output voltage and load current waveform of multilevel inverter and its magnified view before and after the initiation of S1A short circuit fault with induction motor load. $m=0.85$. Fault initiated at 1 sec. | 74 |
| 6.4 | Magnified view of output voltage and load current waveform after S1B short circuit fault with induction motor load. $m=0.85$. | 75 |
| 6.5 | Output voltage and load current waveform of multilevel inverter at no fault condition with static R-L load. $m=0.85$. | 75 |
| 6.6 | Output voltage and load current waveform at S1A short circuit fault condition with static R-L load. $m=0.85$. | 76 |
| 6.7 | Output voltage and load current waveform at S1B short circuit fault condition with static R-L load. $m=0.85$. | 76 |
| 7.1 | Schematic diagram of fault diagnostic system using FFT features. | 78 |
| 7.2 | Output voltage waveforms at normal condition and after open switch fault of Cell A and B. | 79 |
| 7.3 | Output voltage waveforms at normal condition and after short switch fault of Cell A and B. | 80 |
| 7.4 | FFT result of output voltage at normal condition | 81 |
| 7.5 | Features of output voltage waveform obtained from FFT technique (i) THD (ii) 3 rd harmonic ratio (iii) 5 th harmonic ratio at different fault cases | 82 |

| FIGURE NO. | TITLE | PAGE NO. |
|-------------------|---|-----------------|
| 7.6 | RMS value of voltage obtained at different open-switch fault of cell A&B at $m=0.85$. | 84 |
| 7.7 | Schematic of the fault diagnostic system from the features of DWT-MRA technique | 85 |
| 7.8 | DWT MRA detailed components of output voltage waveform under no fault condition obtained up to nine level of decomposition. ($m=0.85$. $fc=3$ kHz). | 86 |
| 7.9 | DWT MRA energy content of output voltage waveform under no fault condition obtained upto nine level of decomposition at different modulation index. | 88 |
| 7.10 | corresponding DWT MRA energy content of output voltage waveforms at different open circuit switch fault conditions of H-Bridge A. ($m=0.85$. $fc=3$ kHz). | 89 |
| 7.11 | DWT MRA energy content of output voltage waveforms at different open circuit switch fault conditions of H-Bridge B. ($m=0.9$. $fc=3$ kHz). | 90 |
| 7.12 | DWT MRA energy content of output voltage waveforms at different short circuit switch fault conditions of H-Bridge A. ($m=0.9$. $fc=3$ kHz). | 91 |
| 7.13 | DWT MRA energy content of output voltage waveforms at different short circuit switch fault conditions of H-Bridge B. ($m=0.85$. $fc=3$ kHz). | 91 |
| 7.14 | Typical output voltage waveform obtained at different open circuit and short circuit switch fault conditions of H-Bridge A during the experimental studies ($m=0.85$) | 92 |

| FIGURE NO. | TITLE | PAGE NO. |
|-------------------|---|-----------------|
| 7.15 | Typical DWT MRA energy content of output voltage waveform at different fault conditions obtained during experimental studies. ($m=0.85$). | 93 |
| 7.16 | V _{rms} /V _{dc} ratio of output voltage waveforms obtained at different (i) open circuit (ii) short circuit fault conditions of H-Bridge A&B. ($m=0.85$) | 95 |
| 7.17 | V _{rms} /V _{av} ratio of output voltage waveforms obtained at different (i) open circuit (ii) short circuit fault conditions of H-Bridge A&B. ($m=0.85$) | 96 |
| 8.1 | Evaluation of the mean square error of the neural network at different no. of hidden layer neurons. | 99 |
| 8.2 | Variations in the MSE of the ANN during training with respect to increase in no. of iterations | 100 |
| 8.3 | Output of neurons in the output layer of the neural network (a) no fault (b) S1B fault (c) S3A fault (d) S4B fault. | 102 |
| 8.4 | Degree of membership of fuzzy gbell membership function for different inputs to FFT-ANFIS network. | 104 |
| 8.5 | Convergence of root mean square error of FFT-ANFIS network during training process with gbellMF. | 106 |

| FIGURE NO. | TITLE | PAGE NO. |
|-------------------|---|-----------------|
| 8.6 | Output of FFT-ANFIS network for (i) training and (ii) testing data at different open switch fault case. | 107 |
| 8.7 | Variations in root mean square error value of FFT-ANFIS network at different open switch fault case for both testing and training sets. | 109 |
| 8.8 | Degree of membership of fuzzy gbell membership function for different inputs to DWT-ANFIS network. | 112 |
| 8.9 | Convergence of root mean square error of DWT-ANFIS network during training process with gbell MF. | 112 |
| 8.10 | Output of DWT-ANFIS network for (i) training and (ii) testing data at different switch fault case. | 113 |
| 8.11 | Variations in root mean square error value of DWT-ANFIS network at different switch fault case for both testing and training sets. | 115 |
| 8.12 | Comparison of performance of various approaches in identifying the faulty switch of multilevel inverter | 116 |