

## List of Figures

Figure 2-1 FSW process stages, (a) plunge, (b) dwell and (c) weld and termination .....	8
Figure 2-2 Dissimilar Cu-Al FSW process and terminologies.....	9
Figure 2-3 Binary phase diagram of Cu-Al dissimilar system (Akinlabi, 2011) .....	35
Figure 2-4 Friction stir welding defects, (b) (c) (d) voids(Firouzdor and Kou, 2012, Xue et al., 2011a, Esmaeili et al., 2011a), (e) surface cracks(Xue et al., 2011a), (f) (g) micro cracks(Esmaeili et al., 2011a), (h) ( i) fragmental defects(Esmaeili et al., 2011b) .....	42
Figure 3-1 (a) FSW machine, (b) and (c) fixture.....	50
Figure 3-2 Workpiece material positioning.....	50
Figure 3-3 Hybrid Cu-Al FSW, (a) TIG assisted FSW and (b) external cooling enhanced FSW .....	55
Figure 3-4 Mini tensile specimen preparation (a) as per ASTM E8 standards, (b) prepared through transverse section .....	56
Figure 4-1 Photograph of Tool 1 .....	59
Figure 4-2 Surface morphologies of welds produced by Tool 1, under different tool pin offsets: (a) 1 mm, (b) 2 mm and (c) 3 mm [Arrows indicate surface lines] .....	61
Figure 4-3 Macrographs of welds produced by Tool 1, under different tool pin offsets: (a) 1 mm, (b) 2 mm and (c) 3 mm.....	62
Figure 4-4 Dispersion of Cu particles produced by taper tool pin design for butt joint dissimilar FSW .....	62
Figure 4-5 Photograph of Tool 2 .....	63
Figure 4-6 Surface morphologies of welds produced by Tool 2, under different welding speeds: (a) 40 mm/min, (b) 55 mm/min, (c) 70 mm/min and (d) 95 mm/min .....	64
Figure 4-7 Macrographs of welds produced by Tool 2, under different welding speeds: (a) 40 mm/min, (b) 55 mm/min, (c) 70 mm/min and (d) 95 mm/min .....	65
Figure 4-8 Photograph of Tool 2, Tool 3 and Tool 4 .....	67
Figure 4-9 Concept of tool pin offset for different tool pin diameters .....	68
Figure 4-10 Surface morphologies of welds produced by (a) Tool 3 (pin diameter 6 mm), (b) Tool 2 (pin diameter 8 mm) and (c) Tool 4 (pin diameter 10 mm).....	68
Figure 4-11 Macrographs of welds produced by (a) Tool 3 and (b) Tool 2.....	70
Figure 4-12 Microstructural examination at different stir zones of weld produced by Tool 3	71
Figure 4-13 Microstructural examination at different stir zones of weld produced by Tool 2	72

Figure 4-14 SEM images (a, c) stir zone-Cu interface of weld made by Tool 3, (b) stir zone-Cu interface of weld made by Tool 2, (d) stir zone of weld made by Tool 2; EDX images at (e) S1: Cu-71.27% and Al-28.73%, (f) S2: Cu-45.86% and Al-54.14%, (g) S3: Cu-87.78% and Al-12.22%, (h) S4: Cu-83.96% and Al-16.04% .....	73
Figure 4-15 Tensile strength and fracture to elongation for welds made by Tool 3 and Tool 2 .....	74
Figure 4-16 (a) SEM image of Cu-stir zone interface for weld made by Tool 2 and (b) Microstructure of Cu-stir zone interface .....	75
Figure 4-17 Hardness profile of welds under different tool pin diameters .....	76
Figure 4-18 Surface morphologies of welds produced by polygonal pins having constant static cross sectional area (a) Tool 5 (triangular profile), (b) Tool 6 (square profile) and (c) Tool 7 (hexagonal profile) .....	79
Figure 4-19 Macrographs of welds produced by (a) Tool 5, (b) Tool 6 and (c) Tool 7 [circles indicate defects] .....	80
Figure 4-20 Microstructural examination at different stir zones of weld produced by Tool 5	81
Figure 4-21 Microstructural examination at different stir zones of weld produced by Tool 6	82
Figure 4-22 Microstructural examination at different stir zones of weld produced by Tool 7	83
Figure 4-23 Tensile strength and fracture to elongation for welds made by Tool 5, Tool 6 and Tool 7 .....	84
Figure 4-24 Hardness profile of welds under different polygonal pin profile (for Tool 5, Tool 6 and Tool 7) .....	86
Figure 4-25 Surface morphologies of welds produced by polygonal pins having constant swept cross sectional area (a) Tool 8 (triangular profile), (b) Tool 9 (square profile) and (c) Tool 10 (hexagonal profile) .....	87
Figure 4-26 Macrographs of welds produced by (a) Tool 8, (b) Tool 9 and (c) Tool 10 [circles indicate defects] .....	88
Figure 4-27 Microstructural examination at different stir zones of weld produced by Tool 8	89
Figure 4-28 Microstructural examination at different stir zones of weld produced by Tool 9	90
Figure 4-29 Microstructural examination at different stir zones of weld produced by Tool 10 .....	91
Figure 4-30 Tensile strength and fracture to elongation for welds made by Tool 8, Tool 9 and Tool 10 .....	92

Figure 4-31 SEM images (a) stir zone made by Tool 8, (b) stir zone made by Tool 9, (c) EDX at S1: Cu-52.88 % and Al-47.12 %, (d) EDX at S2: Cu-86.16 % and Al-13.84 % (e) stir zone made by Tool 10, (f) EDX at S3: Cu-84.06 % and Al-15.94 %.....	93
Figure 4-32 Hardness profile of welds under different polygonal pin profile (for Tool 8, Tool 9 and Tool 10) .....	94
Figure 4-33 Surface morphologies of welds produced by different tool tilt angles (a) 0°, (b) 1°, (c) 2°, (d) 3° and (e) 4° .....	96
Figure 4-34 Tensile strength for different tool tilt angles .....	98
Figure 4-35 Fracture to the elongation for different tool tilt angles.....	98
Figure 4-36 Microstructure at tilt angle 2° (a) weld metal at top, (b) Al-weld interface, (c) Cu-weld interface and (d) weld metal at root.....	99
Figure 4-37 Microstructure at tilt angle 4° (a) Cu-weld interface, (b) weld metal at top, (c) weld metal at root and (d) Al-weld interface.....	100
Figure 4-38 Hardness profiles of welds made under different tilt angles .....	102
Figure 4-39 SEM and EDX analysis at stir zone for tilt angle 0°; (a) dark area: Al - 63.11 atom % & Cu - 36.89 atom %, (b) light area: Al - 42.57 atom % & Cu – 57.43 atom %.....	103
Figure 4-40 SEM and EDX analysis at stir zone for tilt angle 2°; (a) dark area: Al – 11.96 atom % & Cu – 88.04 atom %, (b) light area: Al – 13.47 atom % & Cu – 86.43 atom %.....	104
Figure 4-41 Surface morphologies of joints produced under (a) Normal FSW, (b) HFSW40, (c) HFSW80, (d) HFSW120, (e) CFSWair and (f) CFSWwater [surface oxides pointed out by arrow sign].....	106
Figure 4-42 Macro observations of joints produced under (a) Normal FSW, (b) HFSW40, (c) HFSW80, (d) HFSW120, (e) CFSWair and (f) CFSWwater [the defects indicated by circles]. .....	107
Figure 4-43 IMCs layer of the stir zone under (a) NFSW, (b) HFSW40, (c, d) HFSW80, (e, f) HFSW120, (g) CFSWair and (h) CFSWwater [indicated by arrows].....	112
Figure 4-44 X-ray diffraction patterns acquired under normal and assisted FSW.....	113
Figure 4-45 Tensile strength and fracture to elongation under normal, CFSW and HFSW technologies. ....	115
Figure 4-46 Hardness variations under different modes of FSW.....	118
Figure 4-47 Indentation variations in the stir zone for NFSW .....	118