

## LIST OF TABLES

<b>Table No.</b>	<b>Description</b>	<b>Page no.</b>
Table 1.1	Specifications of most of the resolvers	7
Table 3.1	Simulation parameters of MATLAB <sup>®</sup> SIMULINK <sup>®</sup>	90
Table 3.2	Rotor angular position error for different speeds	98
Table 5.1	Rotor angular position error for different speeds	144
Table 6.1	Terminal assignment of RTD1B14Y1 resolver	150
Table 6.2	Technical specifications of RTD1B14Y1 resolver	151
Table 6.3	Technical specifications of MAXON 273759 DC motor	152
Table 6.4	Wiring connection of AD7366 with ARM7 LPC2148FBD64	156
Table 6.5	Wiring connection of AD5024 with ARM7 LPC2148FBD64	157
Table 6.6	Voltage required for MAXON 273759 DC motor for wide range of speed	164
Table 7.1	Angular performance of Arctangent and modified ATO techniques using MATLAB <sup>®</sup> SIMULINK <sup>®</sup>	184
Table 7.2	Angular performance of modified ATO technique using simulation and experimental	186

## LIST OF FIGURES

<b>Figure No.</b>	<b>Description</b>	<b>Page no.</b>
Figure 1.1	Modern schematic diagram of a synchro	4
Figure 1.2	Resolving an angle into its components	6
Figure 1.3	Frequency response of a resolver	6
Figure 1.4 (a)	Cross section of brushless resolver	7
Figure 1.4 (b)	Schematic diagram of brushless resolver control Transmitter	8
Figure 1.5	Schematic of brushless resolver control transformer	9
Figure 1.6	Electromechanical Servo mechanism	10
Figure 1.7	Schematic of a Stationary transformer	10
Figure 1.8	Schematic of a Resolver	11
Figure 1.9	Internal view of a resolver	12
Figure 1.10 (a)	Equivalent cross sectional view	12
Figure 1.10 (b)	Resolver excitation and output signals	12
Figure 1.11	Amplitude spectrum of resolver signals $V_{s1}$ , $V_{s2}$	14
Figure 1.12	Digital data transmission of a resolver system	15
Figure 1.13	Angle extraction using Arctangent Method	17
Figure 1.14	Resolver to digital converter based on ATO Technique	19
Figure 3.1	Angle extraction using Inverse tangent algorithm	82
Figure 3.2	Arctangent algorithm based RDC	82
Figure 3.3	Synchronous demodulator	84
Figure 3.4	Sample and hold circuit	86
Figure 3.5	MATLAB <sup>®</sup> SIMULINK <sup>®</sup> model of RDC using Arctangent algorithm	87

Figure 3.6	Frequency response of low pass filter	89
Figure 3.7	Square wave excitation signal, SIN and COS outputs of the Resolver	90
Figure 3.8	SIN output, demodulated SIN, COS output and demodulated COS signals	91
Figure 3.9	Sampled SIN and COS outputs and measured rotor shaft angle	91
Figure 3.10	Actual rotor angle (blue) and measured rotor angle (green)	92
Figure 3.11	Measured rotor angle and rotor angle error	92
Figure 3.12	Square wave excitation signal, SIN and COS outputs of the Resolver	93
Figure 3.13	SIN output, demodulated SIN, COS output and demodulated COS signals	93
Figure 3.14	Sampled SIN and COS outputs and measured rotor shaft angle	94
Figure 3.15	Actual rotor angle (blue) and measured rotor angle (green)	94
Figure 3.16	Measured rotor angle and rotor angle error	95
Figure 3.17	Square wave excitation signal, SIN and COS outputs of the Resolver	95
Figure 3.18	SIN output, demodulated SIN, COS output and demodulated COS signals	96
Figure 3.19	Sampled SIN and COS outputs and measured rotor shaft angle	96
Figure 3.20	Actual rotor angle (blue) and measured rotor angle (green)	97
Figure 3.21	Measured rotor angle and rotor angle error	97
Figure 3.22	Graph between rotor angular position error and rotor speed	99
Figure 4.1	Angle extraction using angle tracking observer	104
Figure 4.2	Structure of ATO based Resolver to Digital Converter	105
Figure 4.3	MATLAB <sup>®</sup> SIMULINK <sup>®</sup> model of RDC using ATO algorithm	109
Figure 4.4	Magnitude and phase response of Low pass filter	110
Figure 4.5	Square wave excitation signal, SIN and COS outputs of the resolver	111

Figure 4.6	SIN output, demodulated SIN, COS output and demodulated COS signals	112
Figure 4.7	SIN, COS modulated signals of resolver and measured rotor shaft angle	112
Figure 4.8	Square wave excitation signal, SIN and COS outputs of the resolver	113
Figure 4.9	SIN output, demodulated SIN, COS output and demodulated COS signals	113
Figure 4.10	SIN, COS modulated signals of resolver and measured rotor shaft angle	114
Figure 4.11	Square wave excitation signal, SIN and COS outputs of the resolver	114
Figure 4.12	SIN output, demodulated SIN, COS output and demodulated COS signals	115
Figure 4.13	SIN, COS modulated signals of resolver and measured rotor shaft angle	115
Figure 5.1	Block diagram of modified Angle Tracking Observer based RDC	120
Figure 5.2	Block diagram of synchronous demodulator	122
Figure 5.3	Sample and hold circuit	123
Figure 5.4	Amplitude variations of SIN (blue) and COS (red) signals	126
Figure 5.5	MATLAB <sup>®</sup> SIMULINK <sup>®</sup> model of RDC using modified ATO Algorithm	129
Figure 5.6	Square wave excitation signal, SIN and COS outputs of the resolver	130
Figure 5.7	SIN output, demodulated SIN, COS output and demodulated COS signals	131
Figure 5.8	Sampled SIN and COS outputs and measured rotor shaft angle	131
Figure 5.9	Actual rotor angle (blue) and measured rotor angle (green)	132
Figure 5.10	Measured rotor angle and rotor angle error	132
Figure 5.11	Square wave excitation signal, SIN and COS outputs of the resolver	133

Figure 5.12	SIN output, demodulated SIN, COS output and demodulated COS signals	133
Figure 5.13	Sampled SIN and COS outputs and measured rotor shaft angle	134
Figure 5.14	Actual rotor angle (blue) and measured rotor angle (green)	134
Figure 5.15	Measured rotor angle and rotor angle error	134
Figure 5.16	Square wave excitation signal, SIN and COS outputs of the Resolver	135
Figure 5.17	Sampled SIN and COS outputs and measured rotor shaft angle	135
Figure 5.18	Actual rotor angle (blue) and measured rotor angle (green)	136
Figure 5.19	Measured rotor angle and rotor angle error	136
Figure 5.20	Square wave excitation signal, SIN and COS outputs of the Resolver	137
Figure 5.21	Sampled SIN and COS outputs and measured rotor shaft angle	137
Figure 5.22	Actual rotor angle (blue) and measured rotor angle (green)	137
Figure 5.23	Measured rotor angle and rotor angle error	138
Figure 5.24	Square wave excitation signal, SIN and COS outputs of the Resolver	138
Figure 5.25	Sampled SIN and COS outputs and measured rotor shaft angle	139
Figure 5.26	Actual rotor angle (blue) and measured rotor angle (green)	139
Figure 5.27	Measured rotor angle and rotor angle error	139
Figure 5.28	Square wave excitation signal, SIN and COS outputs of the Resolver	140
Figure 5.29	Sampled SIN and COS outputs and measured rotor shaft angle	140
Figure 5.30	Actual rotor angle (blue) and measured rotor angle (green)	141
Figure 5.31	Measured rotor angle and rotor angle error	141
Figure 5.32	Square wave excitation signal, SIN and COS outputs of the Resolver	142
Figure 5.33	Sampled SIN and COS outputs and measured rotor shaft angle	142

Figure 5.34	Actual rotor angle (blue) and measured rotor angle (green)	142
Figure 5.35	Measured rotor angle and rotor angle error	143
Figure 5.36	Graph between rotor angular position error and rotor speed	144
Figure 6.1	Experimental setup of the proposed RDC system using Modified ATO algorithm	148
Figure 6.2	Resolver RTD1B14Y1 with Synchro flange	149
Figure 6.3	Schematic of RTD1B14Y1 resolver	149
Figure 6.4	Cross sectional view of 12 pin D2SR12 of RTD1B14Y1 resolver	150
Figure 6.5	MAXON 273759 DC Motor	152
Figure 6.6	Schematic of TL082CM	153
Figure 6.7	ADC-DAC board	154
Figure 6.8	Pin diagram of AD7366	155
Figure 6.9	Wiring of each pin of AD7366 with ARM7 LPC2148FBD64	155
Figure 6.10	Pin diagram of AD5024	156
Figure 6.11	Wiring of each pin of AD5024 with ARM7 LPC2148FBD64	157
Figure 6.12	ARM7 LPC2148FBD64 Application specific board	158
Figure 6.13	Architecture of ARM7 LPC2148FBD64 embedded processor	159
Figure 6.14	Pin configuration of LPC2148FBD64MCU	160
Figure 6.15	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	167
Figure 6.16	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	167
Figure 6.17	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	168
Figure 6.18	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	169
Figure 6.19	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	169

Figure 6.20	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	170
Figure 6.21	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	171
Figure 6.22	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	171
Figure 6.23	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	172
Figure 6.24	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	172
Figure 6.25	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	173
Figure 6.26	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	173
Figure 6.27	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	174
Figure 6.28	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	174
Figure 6.29	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	175
Figure 6.30	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	175
Figure 6.31	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	176
Figure 6.32	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	176
Figure 6.33	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	177
Figure 6.34	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	177
Figure 6.35	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	178
Figure 6.36	Resolver excitation (purple), modulated SIN (yellow) and modulated COS (green) signals	178

Figure 6.37	Sampled resolver output signals, SIN (yellow), COS (purple) signals and measured angle (green)	179
Figure 6.38	Measured motor shaft angle (yellow) and angular error between measured angle and estimated angle (purple)	179
Figure 7.1	Angular performance of Arctangent and modified ATO Techniques	185
Figure 7.2	Angular performance of modified ATO technique using simulation and experimental results	186



## LIST OF APPENDICES

<b>Appendix-A;</b> Schematic of developed RDC system using modified ATO Technique	189
--------------------------------------------------------------------------------------	-----