

LIST OF FIGURES AND PLATES

Plate	Plate caption	page
2.1	Photograph of the experimental set-up with accessories.....	30
Figure	Figure caption	page
1.1	Shallow enclosures.....	3
1.2	Tall enclosures.....	3
1.3(a)	Closed ended vertical annulus.....	4
1.3(b)	Open ended vertical annulus.....	4
1.4(a)	Closed loop thermo-siphon.....	5
1.4(b)	Cooling circuit of the transformer cabinet.....	5
1.5	View of a real transformer.....	5
2.1	Schematic View of an Internally Heated Vertical Annular Closed Loop Thermo-siphonic System with Accessories.....	30
2.2	Electronic Circuit for Current and Voltage signals to DAC system.....	38
2.3	Thermocouple locations in the annular test section.....	40
2.4	Thermocouple-Probe Assembly.....	42
3.1(a)	Schematic view of the thermo-siphon.....	46
3.1(b)	Plan of the thermo-siphon.....	46
3.1(c)	Computational geometry.....	46
3.2	Dimensional boundary conditions for numerical solution of the problem [Heated: $z=z_1$ to z_2 and Unheated: $z=0$ to z_1 & $z=z_2$ to L] ...	52
3.3	Non-Dimensional boundary conditions for numerical solution of the problem [Heated: $z=z_1$ to z_2 and Unheated: $z=0$ to z_1 & $z=z_2$ to L].....	55
3.4	Representative Numerical grid of 100×2500	59
3.5	Algorithm for a generic iterative solver.....	67
3.6	Structure of the matrix for a five point computational molecule.....	67
3.7	Computational molecule at point P.....	68
3.8	Simplified GMRES algorithm.....	72
3.9	1D 'slab' decomposition of a 2D domain.....	74

3.10	Comparison of steady state (a) W-velocity (b) θ -temperature (c) U-velocity (d) P-pressure for different choice of grid at mid height of annulus at $Ra = 4.4 \times 10^4$ and $RR = 1.184$	75
3.11	Benchmark configuration with boundary conditions.....	76
3.12	Fluid flow and temperature field. (a) Streamlines (b) Horizontal component of the velocity (c) Vertical component of the velocity, (d) Temperature field.....	78
4.1	Variation in the measured wall surface temperatures $\{T_3, T_6, T_9$ and T_{12} (see Table 2.1)] with time for different values of heat flux during free flow of the test liquid (through by pass line).....	90
4.2	Variation in the measured wall surface temperatures $[T_3, T_6, T_9$ and T_{12} (see Table 2.1)] with time for different values of heat flux with flow restriction (through the flow meters).....	91
4.3	Variation in the measured wall surface temperatures along the axial length of the annulus at different times until steady state, during free flow of the test liquid (through the bypass line).....	92
4.4	Variation in the measured wall surface temperatures along the axial length of the annulus at different times until steady state, during flow restriction (through the flow meters).....	93
4.5	Variation in the measured wall surface temperatures along axial length of the annulus at different values of the heat flux for free flow of the test liquid during the steady state condition.....	94
4.6	Variation in the measured wall surface temperatures along axial length of the annulus at different values of the heat flux with flow restriction during the steady state condition.....	95
4.7	Variation in the test liquid temperatures at inlet (T_{15}) and outlet (T_{16}) of the annulus with time for different values of heat flux during free flow of the test liquid (through by pass line).....	96
4.8	Variation in the test liquid temperatures at inlet (T_{15}) and outlet (T_{16}) of the annulus with time for different values of heat flux during flow restriction (through the flow meters).....	97

4.9	Variation in the measured wall and liquid temperatures along axial length of the annulus at different values of the heat flux for free flow of the liquid during the steady state condition.....	98
4.10	Variation in the measured wall and liquid temperatures along axial length of the annulus at different values of the heat flux with flow restriction during the steady state condition.....	99
4.11	Variation of local Heat transfer coefficient along the axial length at steady state for different heat flux.....	102
4.12	Variation of local Nusselt number along the axial length at steady state for different heat flux.....	103
4.13	Variation of average heat transfer coefficient and Nusselt number for different heat flux during restricted and free flows of the fluid.....	103
4.14	Variation in pressure drop in test liquid in the annulus during free flow through the by-pass line.....	104
4.15	Variation in pressure drop in test liquid in the annulus during restricted flow through the flow meters.....	104
4.16	Changes in the liquid head of the down flow pipe, read by the gauge pressure during the operation of the system with time.....	105
4.17	Variation in the liquid water head in the separator due to mass accumulation during the flow restriction.....	107
4.18	Variation in circulation rate of the test liquid measured by the flow meter (restricted flow).....	108
4.19	Variation in circulation rate of the test liquid measured by the flow meter during restricted flow, total flow rate (flow meter reading plus mass accumulated in the separator) and that estimated at steady state with heat balance.....	109
4.20	Variation in circulation rate of the test liquid measured by the flow meters during restricted flow, total flow rate (flow meters plus mass accumulated in the separator) and that estimated at steady state by heat balance.....	110
4.21	Variation of the liquid circulation rate and Reynolds number for different heat flux during the free flow condition.....	111

5.1	Variation of Temperature a) along the radial direction at mid height with time b) along the radial direction at different axial length ($Ra = 4.4 \times 10^4$).....	113
5.2	Variation of Temperature along the axial length with time for fully heated inner wall a) wall temperature b) liquid bulk temperature ($Ra = 4.4 \times 10^4$).....	114
5.3	Temperature contours at the inlet of the annulus with time for fully heated case	115
5.4	Temperature contours at the inlet of the annulus with time for fully heated case.....	116
5.5	Comparison of thermal boundary layer along the axial length for full heated annulus at different Rayleigh numbers at steady state.....	117
5.6	Comparison of thermal entrance length full heated annulus at different Rayleigh numbers at steady state.....	118
5.7	Variation of Temperature along the radial direction a) at mid height with time b) at different axial length ($Ra = 4.4 \times 10^4$).....	120
5.8	Variation of Temperature along the axial length with time for partial heated inner wall (a) wall temperature (b) liquid bulk temperature ($Ra = 4.4 \times 10^4$).....	121
5.9	Contours of temperature profile at a) the beginning and b) end of the heating of inner wall of the annulus.....	122
5.10	Contours of temperature profile at a) the beginning and b) end of the heating of the inner wall of the annulus.....	123
5.11	Contours of temperature profile at a) the beginning and b) end of the heating of inner wall of the annulus.....	124
5.12	Contours of temperature profile at a) the beginning and b) end of the heating of the inner wall of the annulus	125
5.13	Comparison of Temperature profile at a) the beginning b) end of the heated inner wall of the annulus at different Rayleigh numbers.....	127
5.14	Comparison of thermal boundary layer profile along the axial length for partial heated annulus at different Rayleigh numbers.....	128

5.15	Comparison of temperature variations along the radial length at mid-height for partial and full heated annulus for different Rayleigh numbers.....	128
5.16	Variation of radial velocity a) along the radial direction at mid height with time b) at mid height at different R with time c) average radial velocity along the axial direction with time d) along the radial direction at different axial length ($Ra = 4.4 \times 10^4$).....	130
5.17	Transient growth of radial velocity contours at the inlet of the annulus a) $Ra = 4.4 \times 10^3$ b) $Ra = 1.1 \times 10^4$	132
5.18	Transient growth of radial velocity at the inlet of the annulus a) $Ra = 1.1 \times 10^4$ b) $Ra = 4.4 \times 10^4$	133
5.19	Steady state contours of radial velocity at the inlet along the axial length for fully heated inner wall of the annulus at different Rayleigh numbers.....	134
5.20	Variation of radial velocity at different radial location with time a) at lower unheated zone b) mid height c) upper unheated zone. ($Ra = 4.4 \times 10^4$).....	136
5.21	Variation of average radial velocity along the axial direction with time. ($Ra = 4.4 \times 10^4$).....	137
5.22	Variation of radial velocity along the radial direction with time at the a) inlet b) outlet.....	137
5.23	Variation of radial velocity along the radial length a) beginning of heating b) mid height c) heating end and d) exit of the annulus. ($Ra = 4.4 \times 10^4$).....	138
5.24	Variation of radial velocity along the radial direction at different axial length for a) Non-heating lower zone b) Heating zone c) Non-heating upper zone. ($Ra = 4.4 \times 10^4$).....	139
5.25	Contours of radial velocity component for $Ra = 4.4 \times 10^3$ at a) the beginning and b) end of the heating.....	141
5.26	Contours of radial velocity component for $Ra = 2.2 \times 10^4$ at a) the beginning and b) end of the heating.....	142
5.27	Contours of radial velocity component for $Ra = 4.4 \times 10^4$ at a) the beginning and b) end of the heating.....	143

5.28	Contours of radial velocity component for $Ra = 6.61 \times 10^4$ at a) the beginning and b) end of the heating	144
5.29	Comparison of radial velocity at a) the beginning and b) end of the heating inner wall of the annulus at different Rayleigh numbers.....	146
5.30	Comparison of Radial velocity variations along the radial length at mid-height for partial and full heated annulus for different heat fluxes.	147
5.31	Variation of axial velocity a) along the radial direction at mid height with time b) at mid height for different radial length with time c) average radial velocity along the axial direction with time d) along the radial direction at different axial length ($Ra = 4.4 \times 10^4$).....	148
5.32	Contours of axial velocity component at the inlet with time a) $Ra = 4.4 \times 10^3$ b) $Ra = 2.2 \times 10^4$	149
5.33	Contours of axial velocity component at the inlet with time a) $Ra = 3.3 \times 10^3$ b) $Ra = 4.4 \times 10^4$	150
5.34	Comparison of axial velocity along the axial length for full heated annulus at different Rayleigh numbers.....	151
5.35	Variation of axial velocity along the radial length with time a) at mid height b) outlet of the annulus. ($Ra = 4.4 \times 10^4$).....	152
5.36	Variation of axial velocity a) at mid height for different radial length with time b) average radial velocity along the axial direction with time. ($Ra = 4.4 \times 10^4$).....	152
5.37	Variation of axial velocity along the radial length a) beginning of heating b) mid height c) heating end and d) exit of the annulus. ($Ra = 4.4 \times 10^4$).....	153
5.38	Variation of axial velocity along the radial length at different axial location a) heating zone b) non-heating upper. ($Ra = 4.4 \times 10^4$).....	153
5.39	Contours of axial velocity at a) the beginning and b) end of the heating inner wall of the annulus.....	154
5.40	Contours of axial velocity component at a) the beginning and b) end of the heating inner wall of the annulus.....	155
5.41	Contours of axial velocity component at a) the beginning and b) end of the heating inner wall of the annulus.....	156

5.42	Contours of axial velocity component at a) the beginning and b) end of the heating inner wall of the annulus.....	157
5.43	Comparison of axial velocity near the mid-height of the partially heated annulus at different Rayleigh numbers.....	158
5.44	Comparison of axial velocity variations along the radial length at mid-height for partial and full heated annulus for different Rayleigh numbers.....	159
5.45	Variation of pressure defect a) along the radial direction at different axial length b) along the axial direction at mid radial location ($Ra = 4.4 \times 10^4$).....	161
5.46	Variation of pressure defect along the axial length with time a) fully heated annulus b) partial heated annulus ($Ra = 4.4 \times 10^4$).....	161
5.47	Comparison of pressure defect variations along the radial length at mid-height for partial and full heated annulus for different Rayleigh numbers.....	162
5.48	Comparison of pressure defect variations along the axial length for partial and full heated annulus for different Rayleigh numbers.....	162
5.49	Variation of Local Nusselt along the axial length for different Raleigh number a) fully heated annulus b) partial heated annulus.....	164
5.50	Variation of Average Nusselt at different Raleigh number for fully and partially heated inner wall of the annulus.....	164
5.51	Variation of mass flow rate at different axial location with time a) fully heated annulus b) partial heated annulus ($Ra = 4.4 \times 10^4$).....	165
5.52	Variation of mass flow rate for different Rayleigh numbers with time a) Full heating b) partial heating.....	166
5.53	Variation of bulk axial velocity for different Rayleigh numbers.....	166
5.54	Comparison of mass flow rate for fully and partial hated annulus for different Rayleigh numbers.....	167
5.55	Wall and liquid bulk temperature along the axial length.....	167
5.56	Comparison of steady state Experimental and Numerical (dimensional and non-dimensional) wall temperatures along the axial length for different heat fluxes when the upper zone is adiabatic in the numerical solution.....	169

5.57	Comparison of steady state Experimental and Numerical (dimensional and non-dimensional) wall temperatures along the axial length for different heat fluxes when the upper zone is heated in the numerical solution.....	170
5.58	Comparison of steady state Experimental and Numerical (dimensional and non-dimensional) liquid temperatures along the axial length for different heat fluxes when the upper zone is adiabatic in the numerical solution.....	171
5.59	Comparison of steady state Experimental and Numerical (dimensional and non-dimensional) liquid temperatures along the axial length for different heat fluxes when the upper zone is heated in the numerical solution.....	172
5.60	Comparison of steady state Experimental and Numerical wall and liquid temperatures along the axial length for different heat fluxes when the upper zone is heated in the numerical solution.....	174
5.61	Comparison of steady state Experimental and Numerical local Nusselt number along the axial length of the heated zone for different heat flux.....	175
5.62	Comparison of the Experimental and Numerical liquid mass flow rates in the annulus with time for different heat flux.....	176
5.63	Comparison of the Experimental and Numerical pressure defect between inlet and outlet of the annulus with time.....	178