

LIST OF FIGURES:

Sl. No	Figure Caption	Page. No
Fig. 1.1	Unit cell of fluorite, yellow atoms represent A^{4+} cation and the red O^{-2}	5
Fig. 1.2	Unit cell of pyrochlore, blue sphere represent A^{3+} cation and the red O^{-2}	5
Fig. 1.3	Unit cell of pyrochlore structure	6
Fig. 1.4	Typical firing profile for LTCC components	6
Fig. 3.1	Synthesis flow chart of the ceramics synthesized using solid state reaction method	40
Fig. 3.2	Basic principle involved in diffraction of X-ray beam from assembly of lattice - atoms	41
Fig. 3.3	Schematic diagram of Scanning Electronic Microscopy	44
Fig.4.1(a)	XRD patterns of BMV and BCV ceramics sintered at 963K	54
Fig.4.1(b)	XRD patterns of $BM_{0.5}C_{0.5}V$ ceramics sintered at 963K	55
Fig.4.1(c)	XRD patterns of BMC_1V BMC_2V BMC_3V BMC_4V ceramics $\theta = 10^{\circ}$ to 80° sintered at 963K	56
Fig.4.1(d)	XRD patterns of BMC_1V BMC_2V BMC_3V BMC_4V ceramics $\theta = 28^{\circ}$ to 30° sintered at 963K	57
Fig.4.2(a)	SEM micrographs of BMV and BCV sintered at 963K for 4h	60
Fig.4.2(b)	SEM micrographs of BMC_1V and BMC_2V sintered at 963K for 4h	61
Fig.4.2(c)	SEM micrographs of $BM_{0.5}C_{0.5}V$, BMC_3V and BMC_4V sintered at 963K for 4h	62
Fig.4.3	EDS micrographs of $Bi_{1.5}Mg_{1-x}Cu_xV_{1.5}O_7$ sintered at 963K for 4h	63-65
Fig. 4.4	%Shrinkage Vs concentration (x) of $Bi_{1.5}Mg_{1-x}Cu_xV_{1.5}O_7$	66
Fig. 4.5	Frequency dependent Z behaviour of $Bi_{1.5}Mg_{1-x}Cu_xV_{1.5}O_7$ pyrochlore LTCC at (a) $50^{\circ}C$; (b) $100^{\circ}C$; (c) $200^{\circ}C$; (d) $300^{\circ}C$; (e) $400^{\circ}C$	70-72
Fig. 4.6	Frequency dependent Z' behaviour of $Bi_{1.5}Mg_{1-x}Cu_xV_{1.5}O_7$ pyrochlore LTCC (a) $50^{\circ}C$; (b) $100^{\circ}C$; (c) $200^{\circ}C$; (d) $300^{\circ}C$; (e) $400^{\circ}C$	72-74
Fig. 4.7	Frequency dependent Z'' behaviour of $Bi_{1.5}Mg_{1-x}Cu_xV_{1.5}O_7$ pyrochlore LTCC (a) $50^{\circ}C$; (b) $100^{\circ}C$; (c) $200^{\circ}C$; (d) $300^{\circ}C$; (e) $400^{\circ}C$	74-76
Fig. 4.8	A plot of (Z''/Z''_{max}) vs. $\log(\omega/\omega_{max})$ of $Bi_{1.5}Mg_{1-x}Cu_xV_{1.5}O_7$ pyrochlore LTCC (a) $50^{\circ}C$; (b) $100^{\circ}C$; (c) $200^{\circ}C$; (d) $300^{\circ}C$; (e) $400^{\circ}C$	77-78

Sl. No	Figure Caption	Page. No
Fig. 4.9	Frequency dependent ϵ' behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC at different temperature a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	80-83
Fig. 4.10	Frequency dependent ϵ'' behavior of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC at different temperature a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	84-87
Fig. 4.11	Frequency dependent $\tan(\delta)$ behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	89-92
Fig. 4.12	Frequency dependent σ_{ac} behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	94-97
Fig. 4.13(a)	Temperature dependent $ Z $, behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC at 1 KHz	99
Fig.4.13 (b)	Temperature dependent $ Z $, behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC at 10KHz	100
Fig.4.13 (c)	Temperature dependent $ Z $, behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC at 100 KHz	101
Fig.4.13 (d)	Temperature dependent $ Z $, behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC at 1 MHz	102
Fig.4.13 (e)	Temperature dependent $ Z $ behaviour of $\text{Bi}_{1.5}\text{Mg}_{0.5}\text{Cu}_{0.5}\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC	103
Fig.4.14	Temperature dependent ϵ' behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	106-109
Fig.4.15	Temperature dependent ϵ'' behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	110-113
Fig.4.16	Temperature dependent $\ln\sigma_{ac}$ behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ Pyrochlore LTCC a) $x = 0$, b) $x = 0.2$, c) $x = 0.4$, d) $x = 0.5$, e) $x = 0.6$, f) $x = 0.8$, g) $x = 1$	116-119
Fig. 4.17	Temperature dependent ρ_{dc} behaviour of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ pyrochlore LTCC	121

LIST OF TABLES:

Sl. No	Table caption	Page. No
Table. 1	Dielectric properties of commercial LTCC	7
Table. 4.1	The sintering of $\text{Bi}_{1.5}\text{Mg}_x\text{Cu}_{1-x}\text{V}_{1.5}\text{O}_7$ -pellets and their final appearance.	51
Table .4.2	Crystallographic data of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ ($x=0-1$) pyrochlore LTCC	57
Table. 4.3	Density data of $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ ($x=0-1$) pyrochlore LTCC	58
Table. 4.4	EDS data in Atomic % of elements in $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ ($x=0-1$)	60
Table. 4.5	Ac conductivity Vs temperature (E_a in eV) in $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ ($x=0-1$)	115
Table. 4.6	DC conductivity Vs temperature (E_a in eV) in $\text{Bi}_{1.5}\text{Mg}_{1-x}\text{Cu}_x\text{V}_{1.5}\text{O}_7$ ($x=0-1$)	121

ABBREVIATIONS:

BMV	:	$\text{Bi}_{1.5}\text{MgV}_{1.5}\text{O}_7$
BMC_1V	:	$\text{Bi}_{1.5}\text{Mg}_{0.8}\text{Cu}_{0.2}\text{V}_{1.5}\text{O}_7$
BMC_2V	:	$\text{Bi}_{1.5}\text{Mg}_{0.6}\text{Cu}_{0.4}\text{V}_{1.5}\text{O}_7$
BMC_3V	:	$\text{Bi}_{1.5}\text{Mg}_{0.4}\text{Cu}_{0.6}\text{V}_{1.5}\text{O}_7$
BMC_4V	:	$\text{Bi}_{1.5}\text{Mg}_{0.2}\text{Cu}_{0.8}\text{V}_{1.5}\text{O}_7$
BCV	:	$\text{Bi}_{1.5}\text{CuV}_{1.5}\text{O}_7$
$\text{BM}_{0.5}\text{C}_{0.5}\text{V}$:	$\text{Bi}_{1.5}\text{Mg}_{0.5}\text{Cu}_{0.5}\text{V}_{1.5}\text{O}_7$
Z	:	Impedance
Z'	:	Real part of impedance
Z''	:	Imaginary part of impedance
ϵ'	:	Real part of permittivity
ϵ''	:	Imaginary part of permittivity
σ_{ac}	:	AC Conductivity
ρ_{dc}	:	DC resistivity
ρ_T	:	Room temperature resistivity