

LIST OF THE FIGURES

Figure No.	Figure Title	Page No.
1.1	Ragone plot.	2
1.2	Diagram of symmetric supercapacitor.	3
1.3	Spinel structure of Co_3O_4 .	7
2.1	Types of supercapacitor.	27
2.2 (a)	Behavior of the electrolyte ion (positive charge) in the pore at the time of charging and discharging.	32
2.2 (b)	Helmholtz double layer.	33
2.3	Capacitor charged voltage distribution and equivalent circuit.	34
2.3.a)	Equivalent circuit of capacitor.	35
2.3.b)	Equivalent circuit of DLC with series resistance.	35
2.3.c)	Equivalent circuit of DLC and redox capacitor.	35
2.4. a)	Schematic charge separation of the pseudocapacitor.	37
2.4. b)	Ionic intercalation.	37
2.5	Equivalent circuit of pseudocapacitor.	38
2.6	Schematic diagram of composite electrode.	39
3.1	The schematic of electrodeposition.	47
3.2	Schematic of potentiodynamic electrodeposition set up.	51
3.3	X-ray diffractometer (schematic)	54
3.4	Determination of crystalline size	55
3.5	Scanning electron microscope (schematic)	57
3.6	Different forms of energies evolving after electron collision.	57
3.7	Schematic of field emission scanning electron microscopy	58
3.8	Wettability photograph of the sample.	60
3.9	Schematic diagram of operating principle of an AFM.	61
3.10	Schematic of operating principle of TEM.	62

Figure No.	Figure Title	Page No.
3.11 a)	Experimental setup with electrochemical analyzer.	64
3.11 b)	Pin connections 1) Green-working electrode, 2) White-reference electrode and 3) Red-counter electrodes.	64
3.12	Cyclic voltammogram where i_{pc} - peak cathodic current, i_{pa} - peak anodic current, E_{pc} - peak cathodic potential and E_{pa} - peak anodic potential.	65
3.13	Charge - discharge curve.	66
3.14	Nyquist plot.	67
3.15	Equivalent circuit.	67
4.1	Variation in film thickness for different 0.1 M ingredients.	75
4.2	XRD patterns of the samples deposited by using different ingredients.(A- cobalt chloride, B- cobalt Nitrate , C- cobalt acetate).	76
4.3	FE-SEM images of Co_3O_4 sample prepared on SS using different ingredients at various magnifications.	78
4.4	Cyclic voltammograms of the electrodes prepared using different ingredients scanned at 5 mV/s in 1M KOH	80
4.5	Variation of film thickness with concentration of cobalt chloride solution.	81
4.6	XRD patterns of the samples prepared using different molar concentrations of cobalt chloride solution (M_1 : 0.05 M, M_2 : 0.1M, M_4 : 0.2 M, M_6 : 0.3 M).	82
4.7	FE-SEM images of Co_3O_4 prepared using cobalt chloride as ingredient, sample M_2 , M_4 and M_6 at different magnification..	83
4.8	Cyclic voltammograms of the electrodes prepared by varying the molar concentrations of cobalt chloride solution carried in 1M	84

Figure No.	Figure Title	Page No.
	KOH.	
4.9	Variation of thickness with deposition time for the samples prepared using 0.1 M cobalt chloride solution.	85
4.10	XRD patterns of Co ₃ O ₄ samples prepared for different deposition times (D ₁ : 20 min., D ₂ : 30 min., D ₅ : 60 min.) using 0.1 M cobalt chloride solution.	86
4.11	FE-SEM images of typical D ₂ (30 min.) and D ₅ (60 min.) samples at different magnifications.	87
4.12	TEM images for the sample D ₂ .	88
4.13	2D and 3D AFM micrographs of sample D ₂ .	89
4.14	Wettability test for Co ₃ O ₄ samples prepared at different deposition times.	89
4.15	Cyclic voltammograms of D ₁ , D ₂ and D ₅ electrodes carried in 1M KOH.	91
4.16	Charge-discharge curves of typical D ₂ electrode carried at different current densities (mA/cm ²) in 1M KOH.	92
4.17	Stability curve of D ₂ electrode carried at 100 mV/s in 1M KOH.	93
4.18	Nyquist plot of D ₂ electrode.	94
4.19	Matched nyquist plot of D ₂ electrode	95
4.20	Variation of film thickness with annealing temperature (K) for sample D ₂ .	96
4.21	XRD patterns of D ₂ sample annealed at different temperatures.	97
4.22	FE-SEM images of AT ₁ , AT ₂ , AT ₃ , AT ₄ and AT ₅ samples at 25000 magnification.	99
4.23	Wettability images of sample D ₂ annealed at different temperatures.	100

Figure No.	Figure Title	Page No.
4.24	Cyclic voltammograms of D ₂ electrode annealed at different temperatures and carried in 1M KOH. (AT ₁ : 473 K, AT ₂ : 573 K, AT ₃ : 673 K, AT ₄ : 773 K and AT ₅ : 873 K).	101
4.25	XRD patterns of the samples deposited at different scan rates (DS ₁ : 20 mV/s, DS ₂ : 50 mV/s, DS ₃ : 80 mV/s) and annealed at 473 K.	102
4.26	FE-SEM images of typical DS ₃ sample.	103
4.27	a) TEM image of DS ₃ sample, b) SAED pattern of DS ₃ sample.	104
4.28	a) 2D AFM image of DS ₃ sample, b) 3D AFM image of DS ₃ sample.	105
4.29	Wettability study of sample AT ₁ and DS ₃ .	105
4.30	Cyclic voltammograms of electrode DS ₁ , DS ₂ and DS ₃ scanned in 1M KOH.	106
4.31	Cyclic voltammograms of electrode DS ₃ scanned at different scan rate in 1M KOH.	107
4.32	Cyclic voltammograms of electrode DS ₃ carried in different 1 M electrolytes at 2 mV/s scan rate.	108
4.33	Cyclic voltammograms of electrode DS ₃ in different KOH concentrations.	109
4.34	Stability curve of DS ₃ electrode scanned at 100 mV/s in 1M KOH.	110
4.35	Charge-discharge curves of DS ₃ electrode carried at different current densities.	111
4.36	Nyquist plot of DS ₃ electrode.	113
4.37	Matched nyquist plot of DS ₃ electrode.	114
5.1	Variation of thickness with Mn incorporation in cobalt oxide samples.	133

Figure No.	Figure Title	Page No.
5.2	XRD patterns of the samples deposited up to 1 % Mn incorporation.	135
5.3 a)	FE-SEM images of manganese incorporated cobalt oxide samples carried at X 10000 and X 50000 magnifications.	137
5.3 b)	FESEM image (at X 300K magnification) of CM ₁ sample.	137
5.4	Graphical EDX analysis of typical Mn incorporated cobalt oxide thin films	138
5.5	Wettability images of the Mn incorporated Co ₃ O ₄ samples (a) CM _{0.2} (b) CM _{0.4} (c) CM _{0.6}) CM _{0.8} (e) CM ₁ .	139
5.6 a)	CVs of C _p and CM ₁ electrodes.	140
5.6 b)	CVs of different Mn incorporated electrodes.	141
5.7	Variation in thickness with annealing temperatures for CM ₁ sample.	142
5.8	XRD patterns of the sample CM ₁ annealed at different temperatures.	143
5.9	FESEM images of MnO ₂ : Co ₃ O ₄ thin film (CM ₁) annealed at different temperatures.	144
5.10	TEM (a and b) and SAED (c) images for the sample MAT ₁ (MAT ₁ : 1% Mn incorporated Co ₃ O ₄ thin film).	145
5.11	2D AFM micrograph of MAT ₁ sample.	146
5.12	Wettability images for the MnO ₂ :Co ₃ O ₄ thin films annealed at different temperatures.	147
5.13	CVs of CM ₁ electrode annealed at different temperatures and scanned in 1M KOH (CM ₁ : 1% Mn incorporated cobalt oxide electrode, MAT ₁ to MAT ₅ : 473 K to 673 K with the interval of 50 K).	148

Figure No.	Figure Title	Page No.
5.14	CVs of MAT ₁ electrode observed at different scan rates in 1M KOH (MAT ₁ : 1% manganese doped Co ₃ O ₄ electrode annealed at 473 K).	149
5.15	CVs of MAT ₁ electrode in different electrolytes (MAT ₁ : 1% manganese doped Co ₃ O ₄ electrode annealed at 473 K).	150
5.16	CVs of MAT ₁ electrode observed in different concentrations of KOH.	151
5.17	Electrochemical stability of MAT ₁ electrode at 100 mV/s in 1 M KOH.	152
5.18	CD curves of MAT ₁ at different current densities in 1M KOH.	153
5.19	Nyquist plot for electrode MAT ₁ .	154
5.20	Equivalent Circuit for optimized MAT ₁ electrode.	154
6.1	Variation in film thickness with Ru (%) incorporation in cobalt oxide sample. (C _p : Pristine Co ₃ O ₄ , CR _{0.2} : 0.2 % Ru, CR _{0.4} : 0.4 % Ru, CR _{0.6} : 0.6 % Ru, CR _{0.8} : 0.8 % Ru, CR ₁ : 1 % Ru).	167
6.2 a)	XRD patterns of the samples deposited up to 1 % Ru incorporation.	168
6.2 b)	Observed shifting of XRD peaks to the lower 2θ values.	169
6.3	FE-SEM images [at 50 K magnification] of ruthenium incorporated cobalt oxide samples.	171
6.4	EDX images of Ruthenium incorporated cobalt oxide samples.	172
6.5	Wettability image of ruthenium incorporated cobalt oxide samples.	173
6.6	CVs of different Ru incorporated cobalt oxide electrodes in 1M KOH.	174
6.7	Variation in film thickness with annealing temperature for CR _{0.4} sample.	176

Figure No.	Figure Title	Page No.
6.8	XRD patterns of the optimized CR _{0.4} sample annealed at different temperatures (RAT ₁ : 473 K, RAT ₂ : 523 K, RAT ₃ : 573 K, RAT ₄ : 623 K, RAT ₅ : 673 K).	177
6.9	FESEM images [at 50K magnification] of ruthenium incorporated cobalt oxide samples annealed at different temperatures.	178
6.10	TEM images of sample C _p and RAT ₁ , inset of Fig. is SAED pattern for the sample RAT ₁ .	179
6.11	2D and 3D AFM micrographs of RAT ₁ sample.	180
6.12	Wettability photographs of the sample C _p and RAT ₁ .	181
6.13	CVs of CR _{0.4} electrode annealed at different temperatures and scanned at 2 mV/s in 1M KOH.	182
6.14	CVs of RAT ₁ electrode carried for different scan rates in 1M KOH.	183
6.15	CVs of RAT ₁ electrode scanned in different 1M electrolytes.	184
6.16	CVs of RAT ₁ electrode scanned in KOH electrolyte of different concentrations.	185
6.17	Stability study of the sample RAT ₁ at 100mV/s in 1M KOH.	186
6.18	Charge discharge curves of electrode RAT ₁ scanned at different current densities in 1M KOH.	187
6.19	Nyquist plot of RAT ₁ electrode.	188
6.20	Matched nyquist plot of RAT ₁ electrode and inset shows equivalent circuit.	189
7.1	CV curves of MnO ₂ : Co ₃ O ₄ symmetric device carried at different scan rates in 1M KOH.	200
7.2	Stability curve of MnCo ₃ O ₄ symmetric device carried in 1M KOH.	201
7.3	Charge - discharge curves of MnO ₂ - Co ₃ O ₄ symmetric device	202

Figure No.	Figure Title	Page No.
	observed at different current densities in 1M KOH.	
7.4	Nyquist plot of MnO ₂ - Co ₃ O ₄ : MnO ₂ - Co ₃ O ₄ symmetric device.	203
7.5	a) Matched nyquist plot of MnO ₂ - Co ₃ O ₄ : MnO ₂ - Co ₃ O ₄ symmetric device, b) Matched equivalent circuit.	204