

LIST OF TABLES

Table No.	Title	Page No.
Table 2.1	The values of parameters A, B and e used for calculations of 'c' in [Eq. (2)].	25
Table 3.1	Equilibrium lattice parameters (in Å) of semiconductors included in our study, calculated with LDA, PBE, WC and PBEsol along with Experimental values.	34
Table 3.2	Statistical quantities i.e. ME, MAE, MRE (%) and MARE (%) in the optimized lattice constants for different series of materials studied as produced by various functionals tested.	35
Table 3.3	Comparison of WC and PBEsol optimized lattice constants (Å) of III-N with hybrid and OPT functional results.	36
Table 3.4	Comparison of calculated lattice constants (in Å) of III-P in zinc blende structure using PBEsol, SCAN with those reported hybrid and optB88-vdW functionals for III-P.	37
Table 3.5	Calculated bulk modulus (in GPa) of all the III-V and II-VI binary semiconductors included in the study with different functionals used.	38
Table 3.6	Various error values in bulk modulus of the different series of the materials studied.	39
Table 4.1	The values of parameters A, B and e used for calculations of 'c' in [Eq. (2)].	47
Table 4.2	Calculated band gap (eV) with local, semilocal functional, original mBJLDA and improved mBJLDA (mBJSC) for III-N semiconductors at lattice constants with LDA(a_{lda}), PBE(a_{pbe}), WC(a_{wc}) and PBEsol (a_{pbesol}) optimized lattice constants.	49
Table 4.3	Comparison of band gap (eV) of III-N with other reported results.	50

Table 4.4	Calculated band gap (eV) with local, semilocal functional, original mBJLDA and improved mBJLDA (mBJLDASC) for III-P semiconductors.	59
Table 4.5	Comparison of band gap (eV) of III-P with other reported results.	64
Table 4.6	Calculated band gap (eV) with local, semilocal functional, original mBJLDA and improved mBJ (mBJSC), mBJ(new) for BeX (X=O, S, Se, Te) semiconductors.	65
Table 4.7	Calculated band gap (eV) with local, semilocal functional, original mBJLDA and improved mBJ (mBJSC), mBJ(new) for MgX(X=O, S, Se, Te) semiconductors.	74
Table 4.8	Calculated band gap (eV) with local, semilocal functional, original mBJLDA and improved mBJ (mBJSC), mBJ(new) for CdX(X=O, S, Se, Te) semiconductors.	75
Table 5.1	Static Dielectric function and refractive index for all the materials (III-N, III-P, BeX, MgX, CdX: X=O, S, Se, Te) studied	87
Table 5.2	Second order Susceptibility of CdS, CdSe, CdTe, BeS, BeSe, BeTe, GaN, AlN	88