

REFERENCES

- [1] Al Refeai, T. (1991). "Behaviour of granular soils reinforced with discrete randomly oriented inclusions", *Geotextiles and Geomembranes*, Vol.10, pp.319-333.
- [2] Al Wahab, R.M., and El-Kedrah, M.A. (1995). "Using fibers to reduce tension cracks and shrink/swell in a compacted clay", *Geoenvironmental 2000*, Geotechnical Special Publication No.46, pp.791-805.
- [3] Al-Khafaji, A.W., and Andersland, O.B. (1992). *Geotechnical engineering and soil testing*, Saunders College Publishing, New York, NY.
- [4] Allan, M.L., and Kukacka, L.E. (1995). "Permeability of microcracked fiber reinforced containment barriers", *Waste Management*, Vol.15, No.2, pp.171-177.
- [5] Anand J.Puppala, Balakrishna Katha and Laureano R.Hoyos (2004). "Volumetric shrinkage strain measurements in expansive soils using digital imaging technology", *Geotechnical Journal*, Vol.27, No.6, pp.1-10.
- [6] Andersland, O.B., and Khattak, A.S. (1970). "Shear strength of kaolinite fibre soil mixtures", *Proceedings of the first international conference on soil reinforcement*, Vol.1, Paris, pp.11-16.
- [7] Annadurai, S., and Shanmugalakshmi, R. (2007). *Fundamentals of digital image processing*, Dorling Kindersley (India) Pvt. Ltd.
- [8] Arvind Kumar, Baljit Singh Wakia and Jatender Mohan (2005). "Compressive strength of fibre reinforced highly compressible clay", *Journal of Construction and Building Materials*, Vol.20, pp.1063-1068.

- [9] Babu T.Jose, Solly George and Sridharan, A. (2002). "Suitability of Cochin marine clay as a liner material", *Proceedings of Indian geotechnical conference*, Allahabad.
- [10] Bagchi, A. (1994). *Design construction and monitoring of landfills*, John Wiley and Sons Inc., New York, USA.
- [11] Balaguru, P. (1994). "Contribution of fibres to crack reduction of cement composites during the initial and final setting", *ACI Materials Journal* (American Concrete Institute), Vol.91, No.3, pp.280-288.
- [12] Bill R.Elsbury, Gregory A., Sraders and David C.Anderson (1990). "Lessons learned from compacted clay liner", *Journal of Geotechnical Engineering*, Vol.116, No.11, pp.1641-1661.
- [13] Bosscher, P.J., and Connell, D.E. (1988). "Measurement and analysis of jointing properties in fine-grained soils", *Journal of Geotechnical Engineering*, ASCE, Vol.114, No.7, pp.826-843.
- [14] Boward, J.F., and Vallejo, L.E. (1996). "Clay liner crack propagation", Geotechnical Special Publication: Engineering Contaminated Soil and Interaction of Soil, *Geomembranes* (Proceedings of the 1996 ASCE).
- [15] Boynton, S.S., and Daniel, D.E. (1985). "Hydraulic conductivity tests on compacted clay", *Journal of Geotechnical Engineering*, ASCE, Vol.III, No.4, pp.465-477.
- [16] Brain A.Albrecht and Craig H.Benson (2001). "Effect of desiccation on compacted natural clays", *Journal of Geotechnical and Geo Environmental Engineering*, Vol.127, No.1, pp.67-75.
- [17] Carol, J. Miller, P.E., and Sami Rifai, P.E. (2004). "Fiber reinforcement for waste containment soil liners", *Journal of Environmental Engineering*, Vol.130, No.8, pp.891-895.
- [18] Chacko, A. (1998). *A study on the parameters affecting the compressibility characteristics of Cochin marine clays*, Ph.D. Thesis, Cochin University of Science and Technology, Cochin.

- [19] Chaosheng Tang, Bin Shi, Wei Gao, Fengjun Chen and Yi Cai (2007). “Strength and mechanical behaviour of short polypropylene fiber reinforced and cement stabilized clayey soil”, *Geotextiles and Geomembranes*, Vol.25, pp.194-202.
- [20] Chapuis, R.P. (1990). “Sand-bentonite liners predicting permeability from laboratory tests”, *Canadian Geotechnical Journal*, Vol.27.
- [21] Chertkov (2002). “Characteristic crack dimension of saturated drying soils”, *Journal of Scientific Research and Development*, Vol.IV, pp.1-9.
- [22] Craig H.Benson, David E.Daniel and Gordon P.Boutwell (1999). “Field performance of compacted clay liners”, *Journal of Geotechnical and Geoenvironmental Engineering*, Vol.125, No.5, pp.390-403.
- [23] Crockford, W.W., Grogan, W.P., and Chill, D.S. (1993). “Strength and life of stabilized pavement layers containing fibrillated polypropylene”, *Transportation Research Record*, No.1418, pp.60-66.
- [24] Daniel, D.E. (1993). *Geotechnical practice for waste disposal*, Chapman & Hall, London.
- [25] Daniel, D.E., and Benson, C.H. (1990). “Water content-density criterion for compacted soil liners”, *Journal of Geotechnical Engineering*, Vol.116, No.12, Dec., pp.1811-1830.
- [26] David E.Daniel and Yung-Kwang Wu (1993). “Compacted clay liners and covers for arid sites”, *Journal of Geotechnical Engineering*, Vol.119, No.2, pp.223-237.
- [27] DOE (1995). *Landfill design, construction and operational practice*, Waste management paper 26B, Department of Environment, HMSO, London.
- [28] Eigenbrod (2003). “Self-healing in fractured fine grained soils”, *Canadian Geotech Journal*, 40, pp.435-449.
- [29] Elsbury, B.R., Daniel, D.E., and Sraders, G.A. (1990). “Lessons learned from compacted clay liners”, *Journal of Geotechnical Engineering*, Vol.116, No.11, pp.....

- [30] El-Shoby, M.A., and Rabha, E.A. (1981). "Some factors affecting swelling of clayey soils", *Journal of South East Society of Soil Engineering*, **June 12**, pp.19-39.
- [31] EPA (1985). *Draft minimum technology guidance on double liner systems for landfills and surface impoundments*, EPA/530-SW-85-014.
- [32] Fang, Hsai-yang (1994). "Cracking and fracture behaviour of soil", *Geotechnical Special Publication Fracture Mechanics Proceedings of the ASCE National Convention*, No.43, pp.102-117.
- [33] Fatani, M.N., Bauer, G.E., and Al-Joulani, N. (1991). "Reinforcing soil with aligned and randomly oriented metallic fibres", *Geotechnical Testing Journal*, Vol.14, pp.78-87.
- [34] Fredlund, D.G., and Rahardjo, H. (1993). *Soil mechanics for unsaturated soils*, Wiley & Sons, New York, NY.
- [35] Fredlund, D.G., Xing, A., Fredlund, M.D., and Barbour, S.L. (1995). "The relationship of the unsaturated soil shear strength to the soil-water characteristic curve", *Canadian Geotechnical Journal*, Vol.32, No.3, pp.440-448.
- [36] Freeze, R.A., and Cherry, J. (1979). *Groundwater*, Prentice-Hall, Englewood Cliffs, NJ.
- [37] Freitag, D.R. (1986). "Soil randomly reinforced with fibres", *Journal of Geotechnical Engineering*, Vol.112, pp.823-826.
- [38] Gopal Ranjan, Vasan, R.M., and Charan, H.D. (1994). "Behaviour of plastic fibre reinforced sand", *Geotextiles and Geomembranes*, Vol.13, pp.555-565.
- [39] Gray, D.H., and Al-Refai, T.F. (1986). "Behaviour of fabric versus fibre reinforced sand", *Journal of Geotechnical Engineering*, ASCE, Vol.112, pp.804-820.
- [40] Gray, D.H., and Ohashi, H. (1983). "Mechanics of fiber-reinforcement in sand", *Journal of Geotechnical Engineering*, Vol.109, pp.335-353.

- [41] Gregory, G.H. (1999). “Theoretical shear-strength model of fiber-soil composite”, *Paper presented and published at the ASCE Texas Section Spring Meeting*, Longview, Texas, pp.1-10.
- [42] Head, K.H. (1981). *Manual of soil laboratory testing*, Vol.I, Pentech Press, London.
- [43] Head, K.H. (1981). *Manual of soil laboratory testing*, Vol.II, Pentech Press, London.
- [44] Hewitt, P.J., and Philip L.K. (1999). “Problems of clay desiccation in composite lining systems”, *Engineering Geology*, Vol.53, pp.107-113.
- [45] Hoare, D.J. (1979). “Laboratory study of granular soils reinforced with randomly oriented discrete fibre”, *Proceedings of the international conference on use of fabrics in geotech*, Vol.1, Paris, pp.47-52.
- [46] Holtz, W.G., and Gibbs, H.J. (1956). “Engineering properties of expansive clays”, *ASCE Transaction*, Paper No.2814, Vol.121.
- [47] IS 2720 (Part 2): (1973). *Methods of test for soils: Determination of water content* (second revision), Bureau of Indian Standards, New Delhi.
- [48] IS 2720 (Part 3): (1980). *Methods of test for soils: Determination of specific gravity, Sec.1 Fine grained soils* (first revision), Bureau of Indian Standards, New Delhi.
- [49] IS 2720 (Part 4): (1985). *Methods of test for soils: Part 4—Grain size analysis* (second revision), Bureau of Indian Standards, New Delhi
- [50] IS 2720 (Part 5): (1985). *Methods of test for soils: Determination of liquid limit and plastic limit* (second revision), Bureau of Indian Standards, New Delhi
- [51] IS 2720 (Part 6): (1985). *Methods of test for soils: Determination of shrinkage factors* (first revision), Bureau of Indian Standards, New Delhi
- [52] IS 2720 (Part 7): (1985). *Methods of test for soils: Determination of water content—Dry density relation using light compaction* (second revision), Bureau of Indian Standards, New Delhi

- [53] IS 2720 (Part xx): (1979). *Methods of tests for soils: Determination of linear shrinkage* (second revision), Bureau of Indian Standards, New Delhi
- [54] Jose, B.T. (1989). *A study of physical and engineering behaviour of Cochin marine clays*, Ph.D. Thesis, Cochin University of Science and Technology.
- [55] Juca, J.F.T. (1993). "Flow properties of unsaturated soils under controlled suction", in *Unsaturated soils* by Sandra, L.H., and Wray, W.K. (Eds.), Geotechnical Special Publication No.39, ASCE, New York, pp.151-162.
- [56] Katti, R.K., and Katti, A.R. (1994). *Behaviour of saturated expansive soil and control methods*, Oxford and IBH Publishing Co., New Delhi, pp.886-979.
- [57] Katti, R.K., Hunaad, S., Dewaikar, D.M., Kulkarni, S.K., Kadilakar, B.S., Chandrasekharan, V., and Sundaram, P.N. (1977). "Characteristics of Bombay marine clay in twin city area", *Proceedings of international symposium on soft clay*, A.I.T, Bangkok, Thailand, pp.23-27.
- [58] Kenney, T.C., Chalal, R., Chieu, E. Ofoegbu, G.I., Orange, G.Nand Ume, C.A. (1985). "Controlling construction sizes of granular filters", *Canadian Geotechnical Journal*, 22.1, pp.32-43.
- [59] Kleppe, J.H., and Olson, R.E. (1985). "Desiccation cracking of soil barriers", hydraulic barriers in soil and rock", *American Society for Testing and Materials*, Special Technical Publication, STP 874, pp.263-278.
- [60] Kodikara, J.K., Nahlawi, H., and Bouazza, A. (2004). Modelling of curling in desiccating clay", *Canadian Geotech. Journal*, Vol.41, pp.560-566.
- [61] Koerner, R.M. (1984). *Construction and geotechnical methods in foundation engineering*, Mc-Graw Hill Book Company, New York.
- [62] Koerner, R.M. (1994). *Designing with geosynthetic*, Prentice Hall, New Jersey, NJ.

- [63] Konrad, J.M., and Ayad, R. (1997). "An idealized framework for the analysis of cohesive soils undergoing desiccation", *Journal of Geotechnical Engineering*, Vol.34, pp.477-488.
- [64] Koonnamas Panthutaecha, Anand J.Puppala, Sai K.Vanapalli and Hilary Inyang (2006). "Volume change behaviours of expansive soils stabilized with recycled ashes and fibers", *Journal of Materials in Civil Engineering*, Vol.18, No.2, pp.295-306.
- [65] Leung, M., and Vipulanandan, C. (1995). "Treating contaminated, cracked and permeable field clay with grouts", Geotechnical Special Publication *Proceedings of the speciality conference on geotechnical practice in waste disposal*, part 1, No.46, ASCE New York, NY, USA, pp.829-843.
- [66] Liang Bo Hu, Herve Peron, Tomasz Hueckel and Lyesse Laloui (2006). "Numerical and phenomenological study of desiccation of soil", *Proceedings of the fourth international conference on unsaturated soils*, UNSAT 2006, pp.166-173.
- [67] Maher, M.H., and Gray, D.H. (1990). "Static response of sands reinforced with randomly distributed fibres", *Journal of Geotechnical Engineering*, ASCE, Vol.116, pp.1661-1677.
- [68] Maher, M.H., and Ho, Y.C. (1994). "Mechanical properties of kaolinite/fiber soil composite", *Journal of Geotechnical Engineering*, ASCE, Vol.120, pp.1381-1393.
- [69] McGown, A., Andrews, K.Z., Hyritis, N., and Mercer, F.B. (1985). "Soil strengthening using randomly distributed mesh elements", *Proceedings of the eleventh international conference on soil mechanics and foundation engineering*, Vol.5, San Francisco, pp.1735-1738.
- [70] Mi, H. (1995). *Kinematic wave formulation for flow through macroporous soil*, Ph.D. Dissertation, Dept. of Civil and Environmental Engineering, Wayne State University, Detroit, MI.

- [71] Michlowski, R.K., and Cermak, J. (2003), "Triaxial compression of sand reinforced with fibres", *Journal of Geotechnical and Geoenvironmental Engineering*, ASCE, Vol.120(2), pp.125-1236.
- [72] Miller, C.J. (1988). "Field investigation of clay liner movement", *Hazardous Waste and Hazardous Materials*, Vol.5, No.3, pp.231-238.
- [73] Miller, C.J., and Mishra, M. (1989). "Modeling of leakage through cracked clay liners-I: State of the art", *Water Resources Bulletin*, American Water Resources Association, Vol.25, No.3, pp.551-555.
- [74] Miller, C.J., Hong, M., and Yesiller, N. (1998). "Experimental analysis of desiccation crack propagation in clay liners", *Journal of American Water Resources Association*, Vol.34, No.3, pp.677-684.
- [75] Miller, C.J., Yesiller, N., Demond, A., Merayyan, S. and Yaldo, K. (1998). "Variability in the unsaturated behaviour of clay landfill liners and resulting performance implications", *Proceedings of the fourth international symposium on environmental geotechnology and global sustainable development*, Boston, Massachusetts.
- [76] Morris, P.H., Graham, J. and Williams, D.J. (1992). "Cracking in drying soils", *Canadian Geotechnical Journal*, Vol.29, pp.263-277.
- [77] Murray, R.S., and Quirk, J.P. (1990). "Intrinsic failure and cracking of clay", *Soil Science Society of American Journal*, Vol.54, pp.1179-1184.
- [78] Nahlawi, H., and Kodikara, J.K. (2006). "Laboratory experiments on desiccation cracking of thin soil layers", *Geotechnical and Geological Engineering*, Vol.24, pp.1641-1664.
- [79] Naser Abu-Hejleh, A., and Dobroslav Znidarcic (1995). "Desiccation theory for soft cohesive soils", *Journal of Geotechnical Engineering*, Vol.121, No.6, pp.493-502.
- [80] Nataraj, M.S., and McManis, K.L. (1997). "Strength and deformation properties of soil reinforced with fibrillated fibers", *Geosynthetics International*, Vol.4, No.1, pp.65-79.

- [81] Omid, G.H., Prasad, T.V., Thomas, J.C., and Brown, K.W. (1996). “The influence of amendments on the volumetric shrinkage and integrity of compacted clay soils used in landfill liners”, *Water, Air and Soil Pollution*, Vol.86, pp.263-274.
- [82] Omid, G.H., Prasad, T.V., Thomas, J.C. and Brown, K.W. (1996). “Effect of desiccation cracking on the hydraulic conductivity of a compacted clay liner”, *Water, Air and Soil Pollution*, Vol.89, pp.91- 103.
- [83] Onweremadu, E.U., Akamigbo, F.O.R., and Igwe, C.A. (2007). “Physical shrinkage relationship in soils of dissimilar lithologies in central Southeastern Nigeria”, *Journal of Applied Sciences*, Vol.7(17), pp.2495-2599.
- [84] Peron, H., Laloui, L., Hueckel, T., Hu, L. (2006). “Experimental study of desiccation of soil”, Proceedings of the *Fourth international conference on unsaturated soils*, UNSAT 2006, pp.1073-1084.
- [85] Peter H. Morris, Graham, J., and David J. Williams (1992). “Cracking in drying soils”, *Canadian Geotechnical Journal*, Vol.29, pp.263-277.
- [86] Prabhakar, J. and Sridhar, R.S. (2002), “Effect of random inclusion of sisal fibre on strength behaviour of soil”, *Journal of Construction and Building Materials*, Vol.16, pp.123-131.
- [87] Rafael C. Gonzalez and Richard E. Woods (2005). *Digital image processing*, Dorling Kindersley (India) Pvt. Ltd.
- [88] Rayhani, M.H.T., Yanful, E.K., and Fakher, A. (2007). “Desiccation-induced cracking and its effects on the hydraulic conductivity of clayey soils from Iran”, *Canadian Geotechnical Journal*, Vol.44, pp.276-283.
- [89] Rayhani, M.H.T., Yanful, E.K., and Fakher, A. (2008). “Physical modeling of desiccation cracking in plastic soils”, *Engineering Geology*, Vol.97, pp.25-31.
- [90] Rhys Lewis (1990). *Practical digital image processing*, Ellis Horwood Ltd., England.

- [91] S.Du, Y.J. and Suetsugui. D (2007), An evaluation of Fibre Admixtures on be Desiccation Crack Behaviour of the Compacted Akaboku Soil Potentially Used as a Landfill Cover Barrier Material. Proc. 60th Canadian Geotechnical Conference and 8th Joint CGS/IAH Groundwater Conference. Vol.1. 1377-1382.
- [92] Sami M.Rifai (2000). *Impact of polypropylene fibers on desiccation cracking and hydraulic conductivity of compacted clay soils*, Ph.D. Dissertation, Graduate School of Wayne State University, Detroit, Michigan.
- [93] Shenbaga, Kaniraj, R., and Gayathri, V. (2002). “Geotechnical behaviour of fly ash mixed with randomly oriented fibre inclusions”, *Geotextiles and Geomembranes*, Vol.21, pp.123-149.
- [94] Solly George (2004). *Performance of marine clay as liner material in comparison with bentonite clay*, Ph.D. Thesis, Cochin University of Science and Technology, Cochin.
- [95] Solly George and Babu T.Jose (2002). “Heavy metal adsorption by liner materials to impound industrial waste”, *Proceedings of international conference on advances in civil engineering*, Kharagpur.
- [96] Solly George, Babu T.Jose and Benny Mathews Abraham (2001). “Interaction of clay liners with waste having heavy metals”, *Proceedings of Indian geotechnical conference*, Indore.
- [97] Solly George, Babu T.Jose and Benny Mathews Abraham (2003). “Selection of a suitable liner system for landfills”, *Proceedings of national symposium on strategies for sustainable planning and management of industrial ecology*, Coimbatore.
- [98] Solly George, Babu T.Jose and Benny Mathews Abraham (2003). “Significance of diffuse double layer on permeability of clay liners”, *Proceedings of Indian geotechnical conference*, Roorkee.
- [99] Sridharan, A., and Prakash, K. (2007). *Geotechnical engineering characterization of coal ashes*, CBS Publishers, New Delhi.

- [100] Stacy Ziegler, Dov Leshchinsky, Hoe.I.Ling, and Edward B.Perry (1998). “Effect of short polymeric fibres on crack development in clays”, *Soils and Foundations, Japanese Geotechnical Society*, Vol.38, No.1, pp.247-253.
- [101] Tay, Y.Y., Stewart, D.I., and Cousens, T.W. (2001). “Shrinkage and desiccation cracking in bentonite-sand landfill liners”, *Engineering Geology*, Vol.60, pp.263-274.
- [102] Towner, G.D. (1987). “The mechanics of cracking of drying clay”, *Journal of Agri. Engg. Res.*, Vol.36, pp.115-124.
- [103] Towner, G.D. (1987). “The tensile stress generated in clay through drying”, *Journal of Agri. Engg. Res.*, Vol.37, pp.279-289.
- [104] Vogel, H.J., Hoffmann, H., and Leopold, A., and Roth, K. (2005). “Studies of crack dynamics in clay soil II—A physically based model for crack formation”, *Geoderma*, Vol.125, pp.213-223.
- [105] Vogel, H.J., Hoffmann, H., and Roth, K. (2005). “Studies of crack dynamics in clay soil I—Experimental methods, results, and morphological quantification”, *Geoderma*, Vol.125, pp.203-211.
- [106] Yesiller, N., Miller, C.J., Inci, G., and Yaldo, K. (2000). “Desiccation and cracking behaviour of three compacted landfill liner soils”, *Engineering Geology*, Vol.57, pp.105-121.
- [107] Zeynep, H., Ozkul and Gokhan Baykal (2007). “Shear behaviour of compacted rubber fiber-clay composite in drained and undrained loading”, *Journal of Geotechnical and Geoenvironmental Engineering*, Vol.131, pp.767-781.
- [108] Ziegler Stacy, Dov Leshchinsky, Hoe I.Ling and Edward B.Perry (1998). “Effect of short polymeric fibers on crack development in clays”, *Soil and Foundations*, Vol.38, No.1, pp.247-253.