

---

**List of Tables**

---

Table 3.1	Properties of soils used	37
Table 3.2	Properties of Sand used	38
Table 3.3	Properties of fibres used in the study	39
Table 4.1	Properties of BES and BSMC used for the study	55
Table 4.2	Variations in properties of marine clay on drying	56
Table 4.3	Compaction characteristics of liner soil used in the Study	58
Table 4.4	Desiccation crack details of BES for various cycles	63
Table 4.5	Desiccation crack details of sun dried marine clay	65
Table 4.5(a)	Desiccation crack details of BSMC and Kaolinite soil	65
Table 4.6	Desiccation crack details of the liner soils for cycle 2	66
Table 4.7	Details of Desiccation cracks of BES and SMC	70
Table 4.8	Crack intensity factor for BES and SMC	71
Table 5.1	Aspect Ratio of the Fibres used	74
Table 5.2	Compaction characteristics of BES with nylon fibres	74
Table 5.3	Hydraulic conductivity for BES amended with nylon fibres	80
Table 5.4	Hydraulic conductivity for BES amendedwith polypropylene monofilament fibre	81
Table 5.5	Hydraulic conductivity of BES amended with polypropylene fibre mesh	81
Table 5.6	Hydraulic conductivity of SMC amended with nylon and polypropylene fibres	82
Table 5.7	Hydraulic conductivity test results of SMC amended with polypropylene fibre mesh	83
Table 5.8	Shrinkage limit of BES mixture amended with fibres of 25 mm length.	84
Table 5.9	Shrinkage limit of BES mixture amended with polypropylene fibre mesh	84
Table 5.10	Shrinkage limit of SMC amended with fibres of length 25 mm	85

Table 5.11	Shrinkage characteristics of SMC amended with polypropylene fibre mesh	85
Table 5.12	Variation of unconfined compressive strength of nylon amended BES with fibre content	87
Table 5.13	Variation of unconfined compressive strength of polypropylene monofilament fibre amended BES	87
Table 5.14	Variation of unconfined compressive strength with fibre content for polypropylene fibre mesh amended BES.	89
Table 5.15	Comparison of unconfined compressive strength of fibre amended BES for a fibre content of 0.8%	90
Table 5.16	Unconfined compressive strength for BES amended with nylon fibre of length 10 mm and 25 mm.	91
Table 5.17	Unconfined compressive strength for BES amended with polypropylene monofilament fibre of length 10 mm and 25 mm.	91
Table 5.18	Effect of aspect ratio on nylon amended BES.	92
Table 5.19.	Variation of unconfined compressive strength of nylon amended SMC	94
Table 5.20	Variation of unconfined compressive strength of SMC with polypropylene monofilament.	95
Table 5.21.	Variation of unconfined compressive strength of Polypropylene fibre mesh amended SMC	96
Table 5.22.	Comparison of Unconfined Compressive Strength of Fibre amended SMC at a Fibre content of 0.8%	97
Table 5.23	Comparison of the Unconfined Compressive Strength of BES and SMC for different Fibres	97
Table 5.24	Tension test results of BES amended with nylon fibres	100
Table 5.25	Tension test results of BES amended with polypropylene monofilament fibres	101
Table 5.26	Tension test results of BES amended with polypropylene fibre mesh	102

Table 5.27	Tension test results of SMC amended with nylon fibres	104
Table 5.28	Tension test results of SMC amended with polypropylene monofilament fibres	105
Table 5.29	Variation of tensile strength and residual tensile strength for fibre amended SMC.	108
Table 5.30	Tensile strength of BES and SMC	110
Table 5.31	Crack Intensity factor for SMC amended with Nylon Fibre	114
Table 5.32	CIF of SMC Amended with different Fibre for Cycle 1	115

---

## *List of Figures*

---

Fig: 3.1	Photographs of the Fibres Used	41
Fig 3.2	Drier	43
Fig 3.3	Hood System for Drying Of Soils	44
Fig 3.4	Arrangement for Falling Head Permeability Test in Oedometer Consolidation Cell	52
Fig: 3.5	Tension test fixture installed in the direct shear device	52
Fig 4.1	Compaction curves of the liner soils used for the study	58
Fig: 4.2	Desiccation cracks in BES sample	60
Fig: 4.3	Sequence of analysis carried out to find crack intensity factor	61
Fig: 4.4	Determination of length of crack	62
Fig: 4.5	Desiccated Samples of BES	63
Fig: 4.6	Desiccated Sample of Sundried Marine Clay (Cycle 1)	64
Fig: 4.7	Desiccated samples of SMC (Cycle 2 & Cycle 3)	65
Fig: 4.8	Desiccated samples of liner soils for Cycle 1	66
Fig: 4.9	Desiccated samples of liner soils Cycle 2	67
Fig: 4.10	Variation Of Crack Intensity Factor For Different Soils	68
Fig: 4.11	Comparisons of Desiccated Samples (Cycle 1)	69
Fig: 4.12	Comparisons of designated samples of BES and SMC	70
Fig 4.13	Variation of CIF for desiccated samples of BES and SMC for different cycle	71
FIG.5.1	Compaction characteristics of sun dried marine clay amended with nylon fibre.	75
Fig 5.2	Correlation of maximum dry unit weight and optimum Moisture Content of the amended and unamended soil used in the study	77
Fig 5.3	Variation of hydraulic conductivity $i^{\text{th}}$ consolidation pressure for different fibres	78
Fig 5.4	Hydraulic Conductivity of BES amended with Nylon fibres at different consolidation pressure	79

Fig 5.5	Variation of Hydraulic conductivity BES amended with polypropylene monofilament fibre for different consolidation pressure	80
Fig: 5.6	Stress Strain Characteristics of nylon fibre amended Bentonite enhanced sand mixture	86
Fig 5.7	Stress strain characteristics of BES amended with polypropylene monofilament fiber	88
Fig: 5.8	Stress strain characteristics of BES amended with Fibrillated Polypropylene Fiber Mesh	88
Fig: 5.9	Variation of Unconfined Compressive Strength of BES amended with different fibers	89
Fig: 5.10	Stress Strain Characteristics of Bentonite Sand mixture amended with Nylon fibre of different lengths	90
Fig: 5.11	Stress Strain Curves for fibre amended BES at an aspect ratio of 20	92
Fig 5.12	Stress Strain Characteristics of Sun dried clay amended with nylon fibres of length 25mm	93
Fig: 5.13	Stress Strain Characteristics of Sun dried Marine clay amended with polypropylene Monofilament fibre	93
Fig 5.14	Stress Strain Curves for Sun dried Marine clay amended with polypropylene Fiber Mesh	95
Fig 14(a)	Variation of UCC strength of SMC amended with different fibres	96
Fig 5.15	Stress Strain Curves for BES and SMC amended with polypropylene Fibre Mesh	98
Fig: 5.16	Tension Test result for BES amended with Nylon fibres	99
Fig: 5.17	Tension Test Results for BES amended with polypropylene Monofilament fibers	99
Fig: 5.18	Results of tension tests in BES amended with polypropylene fibrillated Fibre Mesh	102
Fig 5.19	Variation of peak Tensile stress with fibre content for BES mixture amended with fibres	103

Fig: 5.20	Variation of Residual Tensile Stress with fibre content for BES amended with fibers	103
Fig: 5.21	Tension test results of Nylon amended Sun dried Marine Clay	105
Fig: 5.22	Tension test result on SMC amended with polypropylene Monofilament fibre	106
Fig: 5.23	Tension test results for SMC amended with polypropylene Fibre Mesh	106
Fig: 5.24	Variation of peak stress with fibre content for SMC amended with different types of fibre	107
Fig: 5.25	Variation of the residual tensile stress with fiber content for Sun dried Marine Clay amended with fibers	108
Fig: 5.26	Tension test results for BES and SMC with 0.6% Nylon fibre	110
Fig: 27	Tension test for BES and SMC amended with polypropylene Monofilament	110
Fig: 5.28	Tensile test results for BES and SMC amended with polypropylene Fiber Mesh	111
Fig: 5.29	Photographs of desiccated samples of SMC (Cycle 1)	113
Fig: 5.30	Photographs of desiccated samples of fiber amended SMC (Cycle 1)	114
Fig: 5.31	Photographs of desiccated samples for SMC amended with fibre (Cycle 2)	116