

# List of Figures

1.1	An illustrative picture of a biaxial molecules and biaxial nematic phase. . . .	4
1.2	A visualization of the basis vector of order parameter (courtesy [9]) . . . .	9
1.3	Schematic representation of the different temperature regions and the available phases. . . . .	14
1.4	The free energy density plots for different temperatures with the change in order parameter [11] . . . . .	15
2.1	An illustrative plot for Boltzmann sampling . . . . .	47
2.2	The different parameters computed for a $25 \times 25 \times 25$ cubic LL system with the variation in temperature: (a) average energy (b) specific heat (c) The order parameter (d) the nematic susceptibility (fluctuations in S) ( $\chi$ ) . . . . .	54
3.1	The different ways a hybrid nature can be induced in to a liquid crystal system	61
3.2	Director's tilt angle with respect to the z-direction in a h = 10-layer hybrid cell as a function of MC temperature [25]. . . . .	64
3.3	Schematic representation of three possible ordered configurations in a hybrid film: (a) the bent-director structure, (b) biaxial structure with director exchange, and (c) uniform director structure . . . . .	65
3.4	A model of planar hybrid film. . . . .	67
3.5	The density of states and histogram for a $15 \times 15 \times 10$ system with energy . . . . .	69
3.6	The variation of (a) system order parameter (b) layer-wise order parameter (c) system biaxiality parameter (d) layer-wise biaxiality parameter for a $15 \times 15 \times 10$ system with the variation in temperature. . . . .	71
3.7	The variation of the director tilt angle ( $\phi$ ) with the z-axis for $15 \times 15 \times 10$ system and specific heat with temperature . . . . .	72
3.8	The density of states and histogram of $15 \times 15 \times 6$ system with variation in energy ( $\xi_1 = \xi_{nz} = 1.00$ ) . . . . .	74

3.9	The variation of the director tilt angle ( $\phi$ ) with the z-axis for $15 \times 15 \times 6$ system and system biaxiality with temperature ( $\xi_1 = \xi_{nz} = 1.00$ ) . . . . .	75
3.10	(a) Variation of system and layer-wise order parameter with temperature for a $15 \times 15 \times 6$ system with anchoring $\xi_1 = \xi_{nz} = 1.00$ , (b)Variation of system and layer-wise biaxiality parameter with temperature for a $15 \times 15 \times 6$ system with anchoring $\xi_1 = \xi_{nz} = 0.75$ , (c) Variation of specific heat and director tilt angle with temperature for a $15 \times 15 \times 6$ system with anchoring $\xi_1 = \xi_{nz} = 0.5$ , (d) Variation of biaxiality parameter and director tilt angle with temperature for a $15 \times 15 \times 6$ system with anchoring $\xi_1 = \xi_{nz} = 0.25$ , . . . . .	76
3.11	(a)The variation of the director tilt angle ( $\phi$ ) with the z-axis and specific heat $C_V$ with temperature for $15 \times 15 \times 6$ system with anchoring strength $\xi_1 = \xi_{nz} = 0.25$ (b) Fluctuations in the director tilt angle with temperature when $\xi_1 = \xi_{nz} = 0.25$ for system $15 \times 15 \times 6$ . . . . .	77
3.12	Variation of energy, fluctuations in energy, order parameter and biaxiality parameter with temperature for a $15 \times 15 \times 5$ system. ( $\xi_1 = \xi_{nz}$ ) . . . . .	78
3.13	(a) Variation of system and layer-wise biaxiality parameter with temperature for a $15 \times 15 \times 5$ system with anchoring $\xi_1 = \xi_{nz} = 1.00$ , (b)Variation of specific heat and director tilt angle with temperature for a $15 \times 15 \times 5$ system with anchoring $\xi_1 = \xi_{nz} = 0.75$ , (c)Variation of system and layer-wise order parameter with temperature for a $15 \times 15 \times 5$ system with anchoring $\xi_1 = \xi_{nz} = 0.5$ , (d) Variation of the fluctuations of director tilt angle with temperature for a $15 \times 15 \times 5$ system with anchoring $\xi_1 = \xi_{nz} = 0.25$ , . . . . .	79
3.14	(a) Variation of system and layer-wise order parameter with temperature for a $15 \times 15 \times 4$ system with anchoring $\xi_1 = \xi_{nz} = 1.00$ , (b)Variation of specific heat and director tilt angle with temperature for a $15 \times 15 \times 4$ system with anchoring $\xi_1 = \xi_{nz} = 0.75$ , (c) Variation of system and layer-wise biaxiality parameter with temperature for a $15 \times 15 \times 4$ system with anchoring $\xi_1 = \xi_{nz} = 0.5$ , (d) Variation of layer-wise order parameter susceptibility with temperature for a $15 \times 15 \times 4$ system with anchoring $\xi_1 = \xi_{nz} = 0.25$ , . . . . .	80
3.15	Angle director variation with temperature for $15 \times 15 \times 5$ system ( $\xi_1 = \xi_{nz} = 1.00$ ) . . . . .	81

3.16	Fluctuations of the director angle with temperature for $15 \times 15 \times 5$ system ( $\xi_1 = \xi_{nz} = 1.00$ ) . . . . .	82
3.17	The director angle with temperature for $15 \times 15 \times 4$ system ( $\xi_1 = \xi_{nz} = 0.5$ )	82
3.18	The variation of different parameters with temperature for ( $\xi_1 = \xi_{nz}$ ) changing from 0.25 to 1.00 . . . . .	83
3.19	The variation of biaxiality with temperature for the different anchoring strength at the lower temperatures. . . . .	84
3.20	The variation of biaxiality with anchoring strength $\xi$ . . . . .	85
3.21	Variation of $T_{C1}$ with the thickness of the liquid crystal film $d$ . . . . .	86
3.22	Deviation of bent -director angle with change in the anchoring strength of the substrates . . . . .	86
3.23	A cartoon depicting how a cylindrical hybrid film is modeled (the blue indicating the ghost molecules). . . . .	88
3.24	(a) Order parameter of the bulk film b) Layer-wise order parameter c) Layer-wise radial order parameter d) Layer-wise order parameter along z-axis e) Layer-wise biaxiality of system layer-wise and f) Specific Heat ( $C_V$ ) [ $r_1 = 2, r_2 = 8; \epsilon_1 = 0.5$ with axial boundary conditions and $\epsilon_2 = 1.0$ with radial boundary conditions] . . . . .	96
3.25	(a) Average energy b) specific heat c) system order parameters - S and P d)system radial and axial order parameters e) layer-wise axial order param- eter f) Layer-wise radial order parameter g) layer-wise biaxiality parameter h) layer-wise order parameter S [ $r_1 = 2, r_2 = 8; \epsilon_1 = 0.48$ with axial bound- ary conditions and $\epsilon_2 = 1.0$ with radial boundary conditions] . . . . .	98
3.26	(a) Biaxial order parameter (b) System order parameter (c) Radial order pa- rameter (d) Axial order parameter against temperature for different values of $\epsilon_1$ with axial ordering keeping $\epsilon_2 = 1.00$ with radial anchoring. . . . .	101
3.27	Variation of specific heat with temperature for all the systems in table 3.3 .	102
3.28	Variation of layer-wise biaxiality with temperature with the specific heat for the system [ 2, 8 ; A1, R2 ; 0.48, 1.0 ] . . . . .	102
4.1	Admissible values for the dimensionless parameter $\gamma$ and $\lambda$ in equation 4.1.2. The phase diagram with change in $\lambda$ with $\gamma = 0$ (Ref [39] figure 2, figure 4) . . . . .	116

4.2	The phase diagram proposed with the parameter $\gamma = 0$ and varying $\lambda$ (reference [43] figure 6) . . . . .	117
4.3	Contour map of the ratio $\rho := T_{N_B - N_U} / T(N_U - I)$ between the biaxial- uniaxial temperature and isotropic-uniaxial temperature as a function of the parameters $(\gamma, \lambda)$ restricted to the triangle.(reference [44] figure 3(a)) . .	117
4.4	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.0$ and $\Lambda = 0.1$ . . . . .	122
4.5	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.0$ and $\Lambda = 0.8$ . . . . .	122
4.6	The specific heat with temperature at different $\Lambda$ values. . . . .	124
4.7	The phase diagram for $\Gamma=0.00$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	124
4.8	$R_{00}^2$ and $R_{22}^2$ with variation in temperature for different values of $\Lambda$ keeping $\Gamma = 0.1$ . . . . .	125
4.9	$R_{20}^2$ and $R_{20}^2$ with variation in temperature for different values of $\Lambda$ keeping $\Gamma = 0.1$ . . . . .	125
4.10	The specific heat with temperature at different $\Lambda$ values. . . . .	126
4.11	The phase diagram for $\Gamma=0.10$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	126
4.12	The specific heat with temperature for different $\Lambda$ values. . . . .	128
4.13	The phase diagram for $\Gamma=0.2$ , considering the transition temperature from the specific heat for every system by changing the $\Lambda$ value. . . . .	128
4.14	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.2$ and $\Lambda = 0.22$ . . . . .	129

4.15	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.2$ and $\Lambda = 0.23$ . . . . .	129
4.16	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.3$ and $\Lambda = 0.00$ . . . . .	130
4.17	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.3$ and $\Lambda = 0.1$ . . . . .	130
4.18	The specific heat with temperature at different $\Lambda$ values. . . . .	132
4.19	The phase diagram for $\Gamma=0.3$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	132
4.20	The specific heat with temperature at different $\Lambda$ values. . . . .	133
4.21	The phase diagram for $\Gamma=0.4$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	133
4.22	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.4$ and $\Lambda = 0.2$ . . . . .	134
4.23	The specific heat with temperature at different $\Lambda$ values. . . . .	135
4.24	The phase diagram for $\Gamma=0.5$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	135
4.25	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.5$ and $\Lambda = 0.9$ . . . . .	136
4.26	The specific heat with temperature at different $\Lambda$ values. . . . .	137

4.27	The phase diagram for $\Gamma=0.6$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	137
4.28	$R_{00}^2$ and $R_{22}^2$ with variation in temperature for different values of $\Lambda$ keeping $\Gamma = 0.6$ . . . . .	138
4.29	$R_{20}^2$ and $R_{20}^2$ with variation in temperature for different values of $\Lambda$ keeping $\Gamma = 0.6$ . . . . .	138
4.30	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.7$ and $\Lambda = 0.0$ . . . . .	139
4.31	The specific heat with temperature at different $\Lambda$ values. . . . .	140
4.32	The phase diagram for $\Gamma=0.7$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	140
4.33	The specific heat with temperature at different $\Lambda$ values. . . . .	141
4.34	The phase diagram for $\Gamma=0.8$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	141
4.35	$R_{00}^2$ and $R_{22}^2$ with variation in temperature for different values of $\Lambda$ keeping $\Gamma = 0.8$ . . . . .	143
4.36	$R_{20}^2$ and $R_{20}^2$ with variation in temperature for different values of $\Lambda$ keeping $\Gamma = 0.8$ . . . . .	143
4.37	The specific heat with temperature at different $\Lambda$ values. . . . .	144
4.38	The phase diagram for $\Gamma=0.9$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	144
4.39	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 0.9$ and $\Lambda = 0.6$ . . . . .	145

4.40	Variation of (a) order parameter, (b) biaxiality parameter, (c) specific heat ( $C_V$ ), (d)Energy, (e) $R_{02}^2$ , (f) $R_{20}^2$ with temperature for a system with the parameter $\Gamma = 1.00$ and $\Lambda = 0.3$ . . . . .	146
4.41	The specific heat with temperature at different $\Lambda$ values. . . . .	147
4.42	The phase diagram for $\Gamma=1.00$ , taking the transition temperature from the peak position(s) of the specific heat data for every system by changing the $\Lambda$ value ( $T1$ – transition temperature from state $N_U$ to $N_B$ and $T2$ – transition temperature from $N_U$ to isotropic phase). . . . .	147
5.1	The system for biaxial hybrid film. . . . .	160
5.2	Phase diagram proposed for the hamiltonian 5.3 [28] . . . . .	161
5.3	(a) $R_{22}^2$ , (b) $R_{20}^2$ , (c) $R_{02}^2$ , (d) $R_{00}^2$ with the variation in temperature. (The plots in red indicate the respective fluctuations) . . . . .	163
5.4	The variation of (a) $R_{22}^2$ , (b) $R_{00}^2$ , (c) $R_{20}^2$ , (d) $R_{02}^2$ with temperature. . . . .	165
5.5	The variation of the z-angle $\phi$ with temperature overlapped by the specific heat plot to represent the different phases formed.) . . . . .	166
5.6	Variation of the angle made by the molecular z axis with the laboratory Z axis and the $R_{00}^2$ fluctuations with temperature. . . . .	167
5.7	Variation of (a) $R_{00}^2$ , (b) $R_{02}^2$ , (c) $R_{20}^2$ , (d) $R_{22}^2$ with temperature for a system with $\varepsilon_1 = 1.00$ and $\varepsilon_{nz} = 0.00$ . . . . .	170
5.8	Variation of the z tilt angle $\varphi_z$ and the specific heat $C_V$ with temperature for a system with $\varepsilon_1 = 1.00$ and $\varepsilon_{nz} = 0.00$ . . . . .	171
5.9	Variation of layer – wise (a) $R_{00}^2$ , (b) $R_{02}^2$ , (c) $R_{20}^2$ , (d) $R_{22}^2$ with temperature for a system with $\varepsilon_1 = 1.00$ and $\varepsilon_{nz} = 0.00$ . . . . .	173
5.10	Variation of system and layer – wise (a) $R_{00}^2$ , (b) $R_{02}^2$ , (c) $R_{20}^2$ , (d) $R_{22}^2$ and the system order fluctuations with temperature for a system with $\varepsilon_1 = 1.00$ and $\varepsilon_{nz} = 0.2$ (orange – system order parameter; scatter black – system order fluctuations; lines – layer – wise order parameters) . . . . .	174
5.11	Variation of the z tilt angle $\varphi_z$ and the specific heat $C_V$ with temperature for a system with $\varepsilon_1 = 1.00$ and $\varepsilon_{nz} = 0.2$ . . . . .	175
5.12	Variation of (a) $R_{00}^2$ , (b) $R_{02}^2$ , (c) $R_{20}^2$ , (d) $R_{22}^2$ and their fluctuations with temperature for a system with $\varepsilon_1 = 1.00$ and $\varepsilon_{nz} = 0.4$ (black – order parameter; red – susceptibilities ) . . . . .	176

5.13 (a) Variation of z – tilt angle $\varphi_z$ and $R_{00}^2$ susceptibility with temperature	
(b) Variation of y – tilt angle $\varphi_y$ and specific heat ( $C_V$ ). . . . .	178
5.14 Variation of layer – wise (a) $R_{22}^2$ , (b) $R_{00}^2$ , (c) $R_{20}^2$ , (d) $R_{02}^2$ temperature for a system with $\epsilon_1 = 1.00$ and $\epsilon_{nz} = 0.4$ . . . . .	179
5.15 Variation of system and layer – wise (a) $R_{00}^2$ , (b) $R_{02}^2$ , (c) $R_{20}^2$ , (d) $R_{22}^2$ temperature for a system with $\epsilon_1 = 1.00$ and $\epsilon_{nz} = 0.8$ . . . . .	180
5.16 Variation of z – tilt angle $\varphi_z$ and $R_{00}^2$ susceptibility with temperature. . . . .	181
5.17 The transition temperatures of the two peaks for all the $\epsilon_{nz}$ anchoring strengths between 0 to 1 in steps of 0.1 . . . . .	183
5.18 For every anchoring strength ( $\epsilon_{nz}, \epsilon_1 = 1.00$ ) the system order parameter $R_{00}^2$ and its fluctuations . . . . .	184
5.19 Variation in $R_{02}^2$ and its fluctuations with temperature for all the systems (Table 5.1) . . . . .	185
5.20 Change in phase biaxiality $R_{20}^2$ and its fluctuations for different anchoring strength $\epsilon_{nz}$ keeping $\epsilon_1 = 1.00$ . . . . .	186
5.21 The biaxiality parameter $R_{22}^2$ and its fluctuations for every system in table 5.1 with variations in temperature. . . . .	187
5.22 The angles for every layer plotted with the anchoring strength variation at temperature 0.25 . . . . .	188
5.23 The order parameters with anchoring strength at temperature 0.25. . . . .	189
5.24 The fanning angle $\varphi$ with anchoring strength variation. . . . .	190
6.1 An illustrative picture of PDLC . . . . .	195
6.2 Variation of radial and axial order with anchoring strength for scale factor 1.00 . . . . .	204
6.3 Variation of radial order with layers for the scale factor 1.00 for different anchoring strengths (the different plots correspond to different anchoring strengths $\epsilon_S$ , as indexed) . . . . .	205
6.4 Variation of axial order with layers for the scale factor 1.00 for different anchoring strength (the different plots correspond to different anchoring strengths $\epsilon_S$ , as indexed) . . . . .	205
6.5 Variation of RMS value of order fluctuations with layer number for different anchoring strengths (the different plots correspond to different anchoring strengths $\epsilon_S$ , as indexed) . . . . .	206



6.6	Simulated NMR spectrum for different resonant frequencies for the scale factor 1.00 (inner plot representing axial order). . . . .	207
6.7	Variation of the order parameters with anchoring strength for different scale factors as indexed. . . . .	208
6.8	Radial order for every layer for the scale factor 0.1 for different anchoring strengths (the different plots correspond to different anchoring strengths $\epsilon_S$ , as indexed). . . . .	209
6.9	Axial order for different anchoring strength for every layer at scale factor 0.1 (the different plots correspond to different anchoring strengths $\epsilon_S$ , as indexed) . . . . .	210
6.10	Variation of axial order for different K1 with the layer number. . . . .	210
6.11	Radius of the inner axial order core with the scale factor . . . . .	211
6.12	Variation of threshold anchoring strength with scale factor . . . . .	211
6.13	Simulated NMR spectra for various values of scale factors . . . . .	212
6.14	The hysteresis curve for cell dimension ( $\Lambda$ ) 700 Å . . . . .	213
6.15	Variation of Orientational order with anchoring strength for different cell dimensions . . . . .	214