

## List of Tables

Table 1.1	Comparison of three Different type of Filter	2
Table 2.1	Comparison between various OTA Topologies	51
Table 3.1	Comparison of OPAMP Vs OTA	76
Table 3.2	Comparison between Single and Multistage OTA	83
Table 3.3	Summary of Current Mirrors	99
Table 3.4	Specifications for Designed Practical Folded Cascode OTA	102
Table 3.5	Calculated Design Parameter for Folded Cascode OTA	102
Table 3.6	Sizing of Transistor for Folded Cascode OTA	102
Table 3.7	Input-Output Noise per device of Wilson Current Mirror base Folded Cascode OTA	112
Table 3.8	Summary of Simulated Result of Wilson Current Mirror base Folded Cascode OTA	113
Table 3.9	Pre and Post Layout Simulated Result Comparison of Wilson Mirror base Folded cascode OTA	126
Table 3.10	Input and Output Swing Comparison of Wilson Current Mirror and Cascode Current Mirror	134
Table 4.1	Comparison of Filter Topologies	158
Table 4.2	Gm-C First Order Filter Transfer Function	166
Table 4.3	Gm-C Second Order Filter (Fixed Q) Transfer Function	169
Table 4.4	Gm-C Second Order 2 OTAs Implementation Filter Parameter	170
Table 4.5	Gm-C Second Order 3 OTAs Implementation Filter Parameter	174
Table 4.6	Dual Band Filter Specifications	179
Table 4.7	Design equation for Proposed Biquad filter	185
Table 4.8	Capacitor Value for GSM and FM IF	185
Table 4.9	Pre and Post layout simulated Result comparison for 70MHz IF second order CMOS Gm-C IF Filter	194
Table 4.10	Temperature variations on 70MHz IF CMOS Gm-C Band	199

	Pass Filter	
Table 4.11	Supply Voltage variations on 70MHz IF CMOS Gm-C Band Pass Filter	199
Table 4.12	Pre and Post layout simulated Result comparison for 10.6MHz IF second order CMOS Gm-C IF Filter	209
Table 4.13	Temperature variations on 10.6MHz IF CMOS Gm-C Band Pass Filter	214
Table 4.14	Supply Voltage variations on 10.6MHz IF CMOS Gm-C Band Pass Filter	214
Table 4.15	Dual Band Filter measurement results	228
Table 4.16	Comparison with Previously Reported Work	239