

REFERENCES

1. Agrawal J.P., Venugopalan S., Athar J., Sabane J.V. and Muralidharan M. (1998), 'Polysiloxane-based inhibition system for double-base rocket propellants', *J. Appl. Polym. Sci.*, Vol. 69, pp. 7-12.
2. Akutsu F., Inoki M., Daicho N., Kasashima Y., Shiraishi N. and Marushima K. (1998), 'Curing behaviour and properties of epoxy resin cured with the diamine having the quinoxaline or triazine structure', *J. Appl. Polym. Sci.*, Vol. 69, pp. 1737-1741.
3. Alagar M., Thanikai Velan T.V. and Ashok Kumar A. (2000) 'Mechanical properties of E-glass fibre reinforced siliconized epoxy composites', *Polym. Comp.*, Vol. 21, pp. 739-744.
4. Anderson C.C. (1968), 'Adhesives', *Ind. Engg. Chem.*, Vol. 60, pp. 80-87.
5. Apicella A. and Nicholais L. (1985), 'Effect of processing on the durability of epoxy composites in humid environments', *Comp. Sci. Tech.*, Vol.24, pp. 101-121.
6. Ashcroft W.R. (1993), 'Chemistry and Technology of Epoxy resins', Ed. Ellis B, Academic Professional, London.
7. Bartlet P., Pascault J.P. and Sautereau H. (1985), 'Relationships between structure and mechanical properties of rubber-modified epoxy networks cured with dicyanodiamide hardener', *J. Appl. Polym. Sci.*, Vol. 30, pp. 2955-2966.
8. Barton J.M. and Wright W.W. (1985), 'A study of cure characteristics of an epoxy resin system by differential scanning calorimetry and torsional braid analysis', *Thermo. Chem. Acta.*, Vol. 85, pp. 411-414.
9. Bascom W.D., Cottington R.L., Jones R.L. and Peyser P.J. (1975), 'The fracture of epoxy and elastomer modified epoxy polymer in bulk and as adhesives', *J. Appl. Polym. Sci.*, Vol. 19, pp. 2545-2562.

10. Bhatnagar M.S. (1993), 'Epoxy resin from 1980 to date. Part 1', *Polym.-Plast. Technol. Eng.*, Vol. 32, pp. 53-113.
11. Belot V., Corriu R.J.P., Leclercq D., Mutin P.H. and Vioux A. (1992), 'Thermal redistribution reaction in crosslinked polysiloxane', *J. Polym. Sci. Polym. Chem.*, Vol. 30, pp. 613-623.
12. Blacketter D.M., Upadhyaya D. and King T.R. (1993), 'Micromechanics prediction of the transverse tensile strength of carbon fibre/epoxy composites: The influence of the matrix and interface', *Polym. Comp.*, Vol. 14, pp. 437-446.
13. Blacketter D.M., Upadhyaya D., King T.R. and King J.A. (1993a), 'Evaluation of fibre surface treatment and sizing on the shear and transverse tensile strengths of carbon fibre-reinforced thermoset and thermoplastic matrix composites', *Polym. Comp.*, Vol. 14, pp. 430-436.
14. Breitigam V. W., Bauer R.S. and May C. (1993), 'Novel processing and cure of epoxy resin systems' *Polymer*, Vol. 34, pp.767-771.
15. Brown J., Hamerton I. and Howlin B.J. (2000), 'Preparation, characterization and thermal properties of controllable Metal-Imidazole complex curing agents for epoxy resins', *J. Appl. Polym. Sci.*, Vol. 75, pp. 201-217.
16. Bruins P.F. (1968), 'Epoxy Resins Technology', Inter-science Publishers, NewYork.
17. Castan P. (1944), US Patent 2,324,483.
18. Cazacu M., Marcu M., Vlad A., Caraiman D. and Racles C. (1999), 'Synthesis of functional telechelic polydimethylsiloxane by ion-exchangers catalysis', *Eur. Polym. J.* Vol. 35, pp. 1629-1635.
19. Chantarasiri N., Tuntulani T., Tongraung P., Magee S.R. and Wannarong W. (2000), 'New metal-containing epoxy polymers from diglycidyl ether of bisphenol A and tetradentate schiff base metal complexes', *Eur. Polym. J.*, Vol. 36, pp. 695-702.

20. Chern Y.C., Hsieh K.H. and Hsu J.S. (1997), 'Interpenetrating polymer networks of polyurethane cross-linked epoxy and polyurethanes', *J. Mater. Sci.*, Vol. 32, pp. 3503-3509.
21. Crivello J.V. (1976), 'Polyimidothioethers' *J. Polym. Sci. Polym. Chem. Eds.*, Vol. 214, pp. 159-182.
22. Culler S.R., Ishida H. and Koenig J.L. (1986), 'The silane interface of composites: Effects of process conditions on γ -aminopropyltriethoxysilane', *Polym. Comp.*, Vol.7, pp.231-238.
23. d'Almeida J.R.M. (1991), 'Effects of distilled water and saline solution on the interlaminar shear strength of an aramid/epoxy composite', *Composites*, Vol. 22, pp. 448-450.
24. Dasgupta S. and Mital P.K. (1964), 'Dielectric properties of an epoxy resin', *J. Polym. Sci.*, Vol. 8, pp. 2299-2304.
25. Dehoff R.L. (1961), 'Effect of various curing agents on the chemical stability of epoxy resins', *Corrosion*, Vol. 17, pp. 83-87.
26. Denq B.L., Hu Y.S., Chen L.W., Chiu W.Y. and Wu T.R. (1999), 'The curing reaction and physical properties of DGEBA/DETA epoxy resin blended with propyl ester phosphazene', *J. Appl. Polym. Sci.*, Vol. 74, pp. 229-237.
27. Ellis B. (1993), 'Chemistry and Technology of Epoxy resins', Academic Press., London.
28. Enns and Gillham J.K. (1983), *Adv. Chem. Series 203*, Am. Chem. Soc., Washington, D.C.
29. Freddy Y.C., Song X.L., Yue C.Y. and Zhao Q. (2000), 'Modelling the curing kinetics for a modified bismaleimide resin', *J. Polym. Sci.: Part A: Polym. Chem.*, Vol. 38, pp. 907-913.
30. Gasson J. and Bledzki A.K. (1997), 'Effect of moisture content on the properties of siliconized jute-epoxy composites', *Polym. Comp.*, Vol.18, pp.179-184.

31. Glover D.J., Duffy J.V. and Hartmann B. (1988), 'Steric hindrance in the amine epoxide reaction', *J. Polym. Sci., Poly. Chem. Ed.*, Vol. 26, pp. 79-83.
32. Gonis J., Simon G.P. and Cook W.D. (1999), 'Cure properties of epoxies with varying chain length as studied by DSC', *J. Appl. Polym. Sci.*, Vol. 72, pp. 1479-1488.
33. Goodman S.H. (1986), 'Handbook of thermoset plastics', Noyes Publications, New Jersey.
34. Gouri C., Nair C.P.R. and Ramaswamy R. (1999), 'Adhesive and thermal characteristics of maleimide-functional novolac resins', *J. Appl. Polym. Sci.*, Vol. 73, pp. 695-705.
35. Greenlee S.O. (1948), US Patent 2,456,408.
36. Gupta N. and Varma I.K. (1998), 'Effect of structure of epoxy network on interfacial shear strength in glass epoxy composites-II', *J. Appl. Polym. Sci.*, Vol. 68, pp. 1767-1771.
37. Gutman I., Hartings R., Matsuoka R. and Kondo K. (1997), 'Experience with IEC 1109 1000 hour salt for ageing test for composite insulators', *IEEE Elect. Insulation Magazine*, Vol. 13, pp. 36-39.
38. Hamada H., Ikuta N., Nishida N. and Maekawa Z. (1994), 'Effect of interfacial silane network structure on interfacial strength in glass fibre composites', *Composites*, Vol. 25, pp. 512-515.
39. Han H.L. and Li K.Y. (1998), 'Interpenetrating polymer networks of bismaleimide and polyether polyurethane-crosslinked epoxy', *J. Appl. Polym. Sci.*, Vol. 70, pp. 2635-2645.
40. Han H.L., Chern Y.C., Li K.Y. and Hsieh K.H. (1998a), 'Interpenetrating polymer networks of bismaleimide and polyurethane-crosslinked epoxy', *J. Appl. Polym. Sci.*, Vol. 70, pp. 529-536.
41. Hao J., Wang W., Jiang B. and Jiang L. (1999), 'Synthesis of silicone containing polybismaleimide oligomers with different molecular weight and the toughness of their cured resins', *Eur. Polym. J.*, Vol. 35, pp. 1847-1854.

42. Harding P.H. and Berg J.C. (1998), 'The adhesion promotion mechanism of organofunctional silanes', *J. Appl. Polym. Sci.*, Vol. 67, pp. 1025-1033.
43. Hofflin P. (2000), 'Toughening of epoxy resins modified with polyetherester block copolymers: The influence of modifier molecular architecture on mechanical properties' *J. Appl. Polym. Sci.*, Vol. 76, pp. 623-634.
44. Hoh K.P., Ishida H. and Koenig J.L. (1988), 'Spectroscopic studies of the gradient in the silane coupling agent / matrix interface in fibre glass - reinforced epoxy', *Polym. Comp.*, Vol. 9, pp. 151-157.
45. Inez M.G., Miranda D. and Samios D. (1997), 'Analysis and comparison of the barrett, free-man-carrol and the time-temperature-trans-formation (TTT) superposition methods: the case of a high Tg diamine/epoxy system', *Eur. Polym. J.*, Vol. 38, pp. 325-329.
46. Jang B.Z., Lieu Y.K., Chang Y.S. and Hwang L.R. (1987), 'Cryogenic failure mechanisms of fibre-epoxy composites for energy applications', *Polym. Comp.*, Vol. 8, pp. 188-198.
47. Jenneskens L.W., Schuurs H.E.C., Simons D.J. and Willems L. (1994), 'Molecular mechanisms of adhesion promotion by silane coupling agents in glass bead reinforced polyamide-6 model composites', *Composites*, Vol. 25, pp. 504-511.
48. Kaji M., Kazuhiko K and Endo T. (1999), 'Synthesis of a bifunctional epoxy monomer containing bisphenyl moiety and properties of its cured polymer with phenol novolac', *J. Appl. Polym. Sci.*, Vol. 74, pp. 690-698.
49. Kim D. S., Han J.M. and Lee J.R. (1995), 'Cure behaviour and properties of an epoxy resin modified with a bismaleimide resin', *Polym. Engg. Sci.*, Vol. 35, pp. 1353-1358.
50. Klute C.H. and Viehmann W. (1961), 'Heat of polymerization of phenyl glycidyl ether and of an epoxy resin', *J. Polym. Sci.*, Vol. 5, pp. 86-95.
51. Koenig and Emadipour H. (1985), 'Mechanical characterisation of the interfacial strength of glass reinforced composites', *Polym. Comp.*, Vol. 6, pp.142-150.

52. Kossmehl G., Nagel H. I. and Pahl A. (1995), 'Cross-linking reactions on polyamides by bis- and tris(maleimides)', *Angew. Makromol. Chemie.*, Vol. 22, pp. 139-157.
53. Lee H. and Neville K. (1967), 'Handbook of epoxy resins', Mc-Graw Hill Co., New York.
54. Lee N.J. and Jang J. (1997), 'The use of a mixed coupling agent system to improve the performance of polypropylene-based composite reinforced with short-glass-fibre mat', *Comp. Sci. Tech.*, Vol.57, pp.1559-1569.
55. Lee S.S and Kim S.C. (1998), 'Physical aging of polydimethylsiloxane-modified epoxy resin', *J. Appl. Polym. Sci.*, Vol. 69, pp. 1291-1300.
56. Li S.D., Chen Y., Zhou J., Li P.S., Zhu C.S. and Lin M.L. (1998), 'Study on the thermal degradation of epoxidized natural rubber', *J. Appl. Polym. Sci.*, Vol. 67, pp. 2207-2211.
57. Li Y., Shen S., Liu Y. and Gao J. (1999), 'Kinetics of 4,4'-diaminodiphenylmethane curing of bisphenol-S epoxy resin', *J. Appl. Polym. Sci.*, Vol. 73, pp. 1799-1803.
58. Liang G. and Cu A. (1997), 'Synthesis and characterization of two novel maleimides containing an epoxy backbone', *Polym. Comp.*, Vol. 18, pp. 237-241.
59. Liang G. and Fan J. (1999), 'Novel modified bismaleimide resins with improved ablativity', *J. Appl. Polym. Sci.*, Vol. 73, pp. 1623-1631.
60. Liao D.C. and Hsieh K.H. (1994), 'Synthesis and characterization of bismaleimides derived from polyurethanes', *J. Polym. Sci. Part A: Polym. Chem.*, Vol. 32, pp. 1665-1672.
61. Liao Y.T. (1989), 'A study of glass-fibre-epoxy composite Interfaces', *Polym. Comp.*, Vol. 10, pp. 424-428.
62. Lin M.S., Liu C.C. and Lee C.T. (1999), 'Toughened interpenetrating polymer network materials based on unsaturated polyester and epoxy', *J. Appl. Polym. Sci.*, Vol. 72, pp. 585-592.

63. Lin S.T. and Hung S.K. (1996), 'Preparation and structural determination of siloxane-modified sulfone-containing epoxy resins' *J. Polym. Sci. Polym. Chem.*, Vol. 34, pp. 869-884.
64. Lin S.T. and Hung S.K. (1997), 'Thermal degradation study of siloxane-DGEBA epoxy copolymers', *Eur. Polym. J.*, Vol. 33, pp. 365-373.
65. Liu F.J., Munukutu S., Levon K. and Tesoro G. (1990), 'Synthesis and characterization of some imide end-capped amide-imides', *J. Polym. Sci. Part A: Polym. Chem.* Vol. 30, pp. 157-162.
66. Liu Y., Zhao M., Shen S. and Gao J. (1998), 'Curing kinetics, thermal property, and stability of tetrabromo-bisphenol-A epoxy resin with 4,4'-diaminodiphenyl ether', *J. Appl. Polym. Sci.*, Vol. 69, pp. 1991-2000.
67. Mahy J., Jenneskens L.W. and Grabandt O. (1994), 'The fibre/matrix interphase and the adhesion mechanism of surface-treated Twaron^R aramid fibre', *Composites*, Vol. 25, pp. 653-660.
68. Mandell J.F., McGarry F.J., Hsieh J.Y. and Li C.G. (1985), 'Tensile fatigue of glass fibres and composites with conventional and surface compressed fibres', *Polym. Comp.*, Vol. 6, pp. 168-174.
69. Mangion M.B.M. and Johari G.P. (1990), 'Relaxation of thermosets-III: Sub T_g dielectric relaxation of bisphenol-A based epoxide cured with different curing agents', *Macromolecules*, Vol. 23, pp. 3287-3695.
70. Mangion M.B.M. and Johari G.P. (1990a), 'Relaxation of thermosets-IV: A dielectric study of crosslinking of diglycidyl ether of bisphenol-A two curing agents', *J. Polym. Sci., Part B: Polym. Phys.*, Vol. 28, pp. 1621-1639.
71. Marsden and Ziemianski L.P. (1979), 'Organofunctional silanes - functions, applications and advantages', *British Polym. J.*, Vol. 11, pp. 1-7.
72. Melissaris P.A and Mikroyannidis A.J. (1988), 'Bismaleimides chain-extended by imidized benzophenone tetracarboxylic dianhydride and their polymerization to high temperature matrix resins', *J. Polym. Sci. Part A, Polym. Chem.*, Vol. 26, pp. 1165-1178.

73. Mika T.F. (1973), 'Epoxy resins, Chemistry and Technology', Marcel Dekker Inc., New York.
74. Mikroyannidis J.A. and Kourtides D.A. (1984), ' Study on curing of epoxy resins with 1-[Di(2-chloroethoxyphosphinyl)methyl]-2,4- and -2,6-diaminobenzene' J. Appl. Polym. Sci., Vol. 29, pp. 197-209.
75. Moloney A.C.R., Cantwell W.J. and Kausch H.H. (1987), 'Parameters determining the strength and toughness of particulate-filled epoxy resins', Polym. Comp., Vol. 8, pp. 314-323.
76. Morgan R J., Jurek R.J., Yen A. and Donnellan T. (1993), 'Toughening procedures, processing and performance of bismaleimide (BMI)-carbon fibre composites', Polymer, Vol. 34, pp. 835-842.
77. Musto P., Mariuscelli E., Ragosta G., Russo P. and Scarinzi G. (1998), 'An interpenetrated system based on a tetrafunctional epoxy resin and a thermosetting bismaleimide: structure-properties correlation', J. Appl. Polym. Sci., Vol. 69, pp. 1029-1042.
78. Mutsukawa K., Hasegawa K., Inoue H., Fukuda A. and Arita A. (1992), 'Preparation and curing behaviour of siloxane-containing epoxy resins', J. Polym. Sci., Part A: Polym. Chem., Vol. 30, pp. 2045-2048.
79. Nagai A., Takahashi A., Suzuki M., Katagiri K.J. and Mukoh A. (1990), 'Thermal behaviour and cured products of mixtures of two different bismaleimides', J. Appl. Polym. Sci., Vol. 41, pp. 2241-2250.
80. Natarajan.K. and Rao.R.M.V.G.K (1994), 'Toughening studies on ABS/PC blend-modified epoxy resin system', High Perform. Polym., Vol. 6, pp. 241-248.
81. Newaz G.M. (1986), 'Evaluation of fibre-matrix interfacial toughness in unidirectional composites', Polym. Comp., Vol. 7, pp. 421-425.
82. Nir Z., Gilwee W.J., Kourtides D.A. and Parker J.A. (1985), 'Polyfunctional epoxies: Part-II. Non-rubber versus rubber toughened brominated formulations for graphite composites', Polym. Comp., Vol. 6, pp. 72-81.

83. Ooi S.K., Cook W.D., Simon G.P. and Such C.H. (2000), 'DSC studies of the curing mechanisms and kinetics of DGEBA using imidazole curing agent', *Polymer*, Vol. 41, pp. 3639-3646.
84. Park J.O. and Jang S.H. (1992), 'Synthesis and characterization of bismaleimides from epoxy resins', *J. Polym. Sci., Part A: Polym. Chem.*, Vol. 30, pp. 723-729.
85. Park W.H. and Lee J.K. (1998), 'A study on isothermal cure behaviour of an epoxy-rich/anhydride system by differential scanning calorimetry', *J. Appl. Polym. Sci.*, Vol. 67, pp. 1101-1108.
86. Parthun M.G. and Johari G.P. (1992), 'Relaxation in thermosets-XVI: Dielectric studies of negative feedback during curing of an epoxide', *J. Polym. Sci., Part B: Polym. Phys.*, Vol. 30, pp. 655-667.
87. Parthun M.G. and Johari G.P. (1992a), 'Relaxation in thermosets-XXIII: Dielectric studies of curing kinetics of an epoxide with diamines of varying chain length', *Macromolecules*, Vol. 25, pp. 3254-3264.
88. Patel H.S. and Shah V.J. (1993), 'Epoxy-modified polyimides: Part I', *High perform. Polym.*, Vol. 5, pp. 145-153.
89. Patel H.S. and Shah V.J. (1995), 'Glass-reinforced composites based on a novel oligoimide-epoxy resin system', *Polym. Plast. Technol. Engg.*, Vol. 34, pp. 511-516.
90. Patel S. R. and Patel R.G. (1992), 'Glass fibre reinforced composites and thermal study of flame retardant epoxy resin systems using anhydride curing agents', *Polym. Plast. Technol. Engg.*, Vol. 31, pp. 756-771.
91. Pater R.H., Whitley K., Morgan C. and Chang A. (1991), 'Crosslinking-property relationships in PMR polyamide composites. Part I', *Polym. Comp.*, Vol. 12, pp. 126-132.
92. Penn L.S. and Chiao T.T. (1990), 'Handbook of Composites', Van Nostrand Reinhold Co., New York.
93. Petrovic Z. and Stojakovic N. (1988), 'Study of epoxy resin-filler interaction', *Polym. Comp.*, Vol. 9, pp. 42-50.

94. Plueddemann E.P. (1991), 'Silane coupling agents', 2nd Ed. Plenum Press, New York.
95. Potter W.G. (1970), 'Epoxide Resins', Iliffe Press, London.
96. Price and Jentung K.U. (1985), 'Effect of silane coupling agents on a phenolic cure reaction', *Ind. Eng. Chem. Prod. Res. Dev.*, Vol. 24, pp. 185-187.
97. Ramesh B.J., Zingde G.S. and Riffle J.S. (1993), 'Synthesis of α , ω -arylamine functionalized poly(dimethylsiloxane)s', *J. Polym. Sci., Part A: Polym. Chem.*, Vol. 31, pp. 1645-1651.
98. Rao B.S. (1988), 'Novel bismaleimides via epoxy-carboxy addition reaction: synthesis, characterization and thermal stability', *J. Polym. Sci: Part C: Lett. Ed.*, Vol. 26, pp. 3-10.
99. Rao B.S. (1989), 'Synthesis, characterization and thermal stability of bismaleimides derived from maleimido benzoic acid', *J. Polym. Sci: Part A: Polym. Chem.*, Vol. 27, pp. 2509-2518.
100. Rao R.M.V.G.K., Padma A. and Patel H. S. (1992), 'Kinetic studies on epoxy resin cured with a novel polyamine', *High Perform. Polym.*, Vol. 41-48.
101. Rhee H.W. and Bell J.P. (1991), 'Effects of reactive and non-reactive fibre coatings upon performance of graphite/epoxy composites', *Polym. Comp.*, Vol. 12, pp. 213-225.
102. Riccardi C.C., Adabbo H.E. and Williams R.J.J. (1984), 'Curing reactions of epoxy resins with diamines', *J. Appl. Polym. Sci.*, Vol. 29, pp. 2481-2492.
103. Rochette, A., Choplin L. and Tanguy P.A. (1988), 'Rheological study of micro-filled polypropylene as influenced by a coupling agent', *Polym. Comp.*, Vol. 9, pp. 419-425.
104. Schlack P. (1938), US Patent 2, 136,928.
105. Schrade P. (1968), German Patent, 1,176,122.

106. Serier A., Pascault J.P. and My L.T. (1991), 'Reaction in aminosilane-epoxy prepolymer systems-I: Kinetics of epoxy-Amine reactions', *J. Polym. Sci., Part A: Polym. Chem.*, Vol. 30, pp. 723-729.
107. Sheng S.H., Chung Y.P., Chan C.K. and Kuo P.L. (2000), 'Function and performance of silicone copolymer. Part IV. Curing behaviour with diglycidyl ether of bisphenol A', *Polymer*, Vol. 41, pp. 3263-3272.
108. Shih Y.C. and Chen C.M. (1998), 'Tetrafunctional aliphatic epoxy I. synthesis and characterization', *J. Appl. Polym. Sci.*, Vol. 69, pp. 51-58.
109. Simmons S., Shah M., Mackevich J. and Chang R.J. (1997), 'Polymer outdoor insulating materials-Part III: silicone elastomer considerations', *IEEE Elect. Insulation Magazine*, Vol. 13, pp. 25-31.
110. Sounik D.F. and Kenny M.E. (1985), 'New potential silane coupling agents', *Polym. Comp.*, Vol. 6, pp. 151-155.
111. Sridhar K, Siddhamalli and Kyu T. (2000), 'Toughening of thermoset/thermoplastic composites via reaction-induced phase separation: epoxy/phenoxy blends', *J. Appl. Polym. Sci.*, Vol. 77, pp. 1257-1268.
112. St.John N.A. and George G.A. (1994), 'The origin and applications of chemiluminescence from epoxy resins', *Prog. Polym. Sci.* Vol. 19, pp. 755-761.
113. Stanciu A., Airinei A., Timpu D., Ioanid A., Ioan C. and Bulacovschi V. (1999), 'Polyurethane/polydimethylsiloxane segmented copolymers', *Eur. Polym. J.*, Vol. 35, pp. 1959-1965.
114. Sung P. H. and Lin C. Y. (1997), 'Polysiloxane modified epoxy polymer networks-I: graft interpenetrating polymeric networks', *Eur. Polym. J.*, Vol. 33, pp. 903-906.
115. Tanaka Y., Okada A. and Tomizuka I. (1973), 'Epoxy resins chemistry and technology', Marcel Dekker Inc., NewYork.
116. Thangamathesvaran P.M. and Jain S.R. (1991), 'Synthesis and characterization of thiocarbonohydrazone based epoxy resins', *J. Polym. Sci., Part A: Polym. Chem.*, Vol. 29, pp. 261-267.

117. Visconti I.C. (1992), 'Overview of composites: Their uses and technology trends', *Polym. Plast. Technol. Eng.*, Vol. 31, pp. 1-59.
118. Wang C.S. and Lin C.H. (2000), 'Synthesis and properties of phosphorous containing advanced epoxy resins', *J. Appl. Polym. Sci.*, Vol. 75, pp. 429-436.
119. Wang C.S. (1999), 'Synthesis, characterization and properties of multifunctional naphthalene containing epoxy resins cured with cyanate ester', *J. Appl. Polym. Sci.*, Vol. 73, pp. 1611-1622.
120. Wang H.H. and Chen J.C. (1995), 'Modification and compatibility of epoxy resin with hydroxyl-terminated or amine-terminated polyurethanes', *Polym. Eng. Sci.*, Vol. 35, pp. 1468-1475.
121. Wang T.S., Parang J.K. and Shau M.D. (1999), 'The synthesis and properties of new epoxy resin containing phosphorus and nitrogen groups for flame retardancy', *J. Appl. Polym. Sci.*, Vol. 74, pp. 413-421.
122. Weatherhead R.G. (1980), 'FRP technology', Allied Sci. Pub. Ltd., London.
123. White J.E. (1986), 'Synthesis and properties of high-molecular-weight step-growth polymers from bismaleimides', *Ind. Eng. Chem. Prod. Res. Dev.*, Vol. 25, pp. 395-400.
124. Woo M., Chen L.B. and Seferis J.C. (1987), 'Characterization of epoxy-bismaleimide network matrices', *J. Mater. Sci.*, Vol. 22, pp. 3665-3671.
125. Wu H.F., Biresaw G. and Laemmle J.T. (1991), 'Effect of surfactant treatment on interfacial adhesion in single graphite/epoxy composites', *Polym. Comp.*, Vol. 12, pp. 281-288.
126. Wu S.L. and Tung I.C. (1995), 'Dielectric studies of mineral-filled epoxy', *Polym. Comp.*, Vol. 16, pp. 233-239.
127. Wu S.J., Lin T.K. and Shyu (2000), 'Cure behaviour, morphology and mechanical properties of the blends of epoxy with polyphenylene oxide', *J. Appl. Polym. Sci.*, Vol. 75, pp. 26-34.
128. Yee A. F. and Pearson R. A. (1986), 'Toughening mechanism in elastomer modified epoxies-Part I: mechanical studies', *J. Mater. Sci.*, Vol. 21, pp. 2462-2474.