

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
2.1	Schematic experimental set-up for the preparation of hydroxyl-terminated polydimethylsiloxane	50
2.2	Synthesis of bismaleimides	52
2.3	Preparation of siliconized epoxy resin	54
3.1	FTIR spectra of (a) unmodified epoxy, (b) γ -APS cured epoxy and (c) γ -APS	68
3.2	FTIR spectra of BMI-1	71
3.3	FTIR spectra of BMI-2	72
3.4	FTIR spectra of BMI-3	73
3.5	FTIR spectra of BMI-4	74
3.6	^1H -NMR spectra of BMI-1	76
3.7	^{13}C -NMR spectra of BMI-1	77
3.8	^1H -NMR spectra of BMI-2	78
3.9	Expanded ^1H -NMR spectra of BMI-2	79
3.10	^{13}C -NMR spectra of BMI-2	80
3.11	^1H -NMR spectra of BMI-3	81
3.12	Expanded ^1H -NMR spectra of BMI-3	82
3.13	^{13}C -NMR spectra of BMI-3	83
3.14	^1H -NMR spectra of BMI-4	84
3.15	Expanded ^1H -NMR spectra of BMI-4	85
3.16	^{13}C -NMR spectra of BMI-4	86

FIGURE NO.	TITLE	PAGE NO.
3.17	FTIR spectra of (a) pure BMI-1, (b) unmodified epoxy, (c) epoxy/BMI-1: 100/10, (d) epoxy/BMI-1: 100/50 and (e) epoxy/BMI-1: 100/50 after heating at 150°C for four hours	89
3.18	FTIR spectra of (a) pure BMI-2, (b) unmodified epoxy, (c) epoxy/BMI-2: 100/10, (d) epoxy/BMI-2: 100/50 and (e) epoxy/BMI-2: 100/50 after heating at 150°C for four hours	90
3.19	FTIR spectra of (a) pure BMI-3, (b) unmodified epoxy, (c) epoxy/BMI-3: 100/10, (d) epoxy/BMI-3: 100/50 and (e) epoxy/BMI-3: 100/50 after heating at 150°C for four hours	91
3.20	FTIR spectra of (a) pure BMI-4, (b) unmodified epoxy, (c) epoxy/BMI-4: 100/10, (d) epoxy/BMI-4: 100/50 and (e) epoxy/BMI-4: 100/50 after heating at 150°C for four hours	92
4.1	Effect of siloxane content on tensile strength of epoxy system	94
4.2	Effect of siloxane content on tensile modulus of epoxy system	94
4.3	Effect of BMI-1 content on tensile strength of epoxy and siliconized epoxy systems	98
4.4	Effect of BMI-1 content on tensile modulus of epoxy and siliconized epoxy systems	98
4.5	Effect of BMI-2 content on tensile strength of epoxy and siliconized epoxy systems	99

FIGURE NO.	TITLE	PAGE NO.
4.6	Effect of BMI-2 content on tensile modulus of epoxy and siliconized epoxy systems	99
4.7	Effect of BMI-3 content on tensile strength of epoxy and siliconized epoxy systems	100
4.8	Effect of BMI-3 content on tensile modulus of epoxy and siliconized epoxy systems	100
4.9	Effect of BMI-4 content on tensile strength of epoxy and siliconized epoxy systems	101
4.10	Effect of BMI-4 content on tensile modulus of epoxy and siliconized epoxy systems	101
4.11	Effect of siloxane content on flexural strength of epoxy system	102
4.12	Effect of siloxane content on flexural modulus of epoxy system	102
4.13	Effect of BMI-1 content on flexural strength of epoxy and siliconized epoxy systems	104
4.14	Effect of BMI-1 content on flexural modulus of epoxy and siliconized epoxy systems	104
4.15	Effect of BMI-2 content on flexural strength of epoxy and siliconized epoxy systems	105
4.16	Effect of BMI-2 content on flexural modulus of epoxy and siliconized epoxy systems	105
4.17	Effect of BMI-3 content on flexural strength of epoxy and siliconized epoxy systems	106
4.18	Effect of BMI-3 content on flexural modulus of epoxy and siliconized epoxy systems	106
4.19	Effect of BMI-4 content on flexural strength of epoxy and siliconized epoxy systems	107

FIGURE NO.	TITLE	PAGE NO.
4.20	Effect of BMI-4 content on flexural modulus of epoxy and siliconized epoxy systems	107
4.21	Effect of siloxane content on plain strain fracture toughness of epoxy system	109
4.22	Effect of BMI-1 content on plain strain fracture toughness of epoxy and siliconized epoxy systems	111
4.23	Effect of BMI-2 content on plain strain fracture toughness of epoxy and siliconized epoxy systems	111
4.24	Effect of BMI-3 content on plain strain fracture toughness of epoxy and siliconized epoxy systems	112
4.25	Effect of BMI-4 content on plain strain fracture toughness of epoxy and siliconized epoxy systems	112
6.1	DSC thermograms of epoxy- γ -APS mixture during cure	133
6.2	DSC thermograms of (a) epoxy-DDM and (b) mixture of epoxy-DDM- γ -APS mixture during cure	134
6.3	Reactions involved during the curing process of bismaleimides modified epoxy systems	135
6.4	DSC thermograms of epoxy-BMI-1 systems during cure (a) epoxy-DDM, (b) epoxy-DDM-5% BMI-1, (c) epoxy-DDM-10% BMI-1 and (d) epoxy-DDM-15% BMI-1	136

FIGURE NO.	TITLE	PAGE NO.
6.5	DSC thermograms of epoxy-BMI-2 systems during cure (a) epoxy-DDM, (b) epoxy-DDM-5% BMI-2, (c) epoxy-DDM-10% BMI-2 and (d) epoxy-DDM-15% BMI-2	137
6.6	DSC thermograms of epoxy-BMI-3 systems during cure (a) epoxy-DDM, (b) epoxy-DDM-5% BMI-3, (c) epoxy-DDM-10% BMI-3 and (d) epoxy-DDM-15% BMI-3	138
6.7	DSC thermograms of epoxy-BMI-4 systems during cure (a) epoxy-DDM, (b) epoxy-DDM-5% BMI-4, (c) epoxy-DDM-10% BMI-4 and (d) epoxy-DDM-15% BMI-4	139
6.8	DSC thermograms of BMI-1 during cure	140
6.9	DSC thermograms of BMI-2 during cure	141
6.10	DSC thermograms of BMI-3 during cure	142
6.11	DSC thermograms of BMI-4 during cure	143
6.12	DSC traces of epoxy and siliconized epoxy systems (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% siloxane modified epoxy systems	146
6.13	DSC traces of BMI-1 modified epoxy systems (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% BMI-1 modified epoxy systems	147
6.14	DSC traces of BMI-2 modified epoxy systems (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% BMI-2 modified epoxy systems	148

FIGURE NO.	TITLE	PAGE NO.
6.15	DSC traces of BMI-3 modified epoxy systems (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% BMI-3 modified epoxy systems	149
6.16	DSC traces of BMI-4 modified epoxy systems (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% BMI-4 modified epoxy systems	150
6.17	DSC traces of 10% siliconized epoxy/BMI-1 systems (a) 5%, (b) 10% and (c) 15% BMI-1 modified 10% siliconized epoxy systems	151
6.18	DSC traces of 10% siliconized epoxy/BMI-2 systems (a) 5%, (b) 10% and (c) 15% BMI-2 modified 10% siliconized epoxy systems	152
6.19	DSC traces of 10% siliconized epoxy/BMI-3 systems (a) 5%, (b) 10% and (c) 15% BMI-3 modified 10% siliconized epoxy systems	153
6.20	DSC traces of 10% siliconized epoxy/BMI-4 systems (a) 5%, (b) 10% and (c) 15% BMI-4 modified 10% siliconized epoxy systems	154
6.21	Effect of siloxane content on %wt loss of epoxy system	158
6.22	TGA curves of siliconized epoxy systems (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% siloxane modified epoxy systems	159

FIGURE NO.	TITLE	PAGE NO.
6.23	Effect of BMI-1 content on percentage weight loss of epoxy system	160
6.24	Effect of BMI-1 content on percentage weight loss of 10% siliconized epoxy system	160
6.25	Effect of BMI-2 content on percentage weight loss of epoxy system	161
6.26	Effect of BMI-2 content on percentage weight loss of 10% siliconized epoxy system	161
6.27	Effect of BMI-3 content on percentage weight loss of epoxy system	162
6.28	Effect of BMI-3 content on percentage weight loss of 10% siliconized epoxy system	162
6.29	Effect of BMI-4 content on percentage weight loss of epoxy system	163
6.30	Effect of BMI-4 content on percentage weight loss of 10% siliconized epoxy system	163
6.31	TGA curves of BMI-1 modified epoxy systems (a) 5%, (b) 10% and (c) 15% BMI-1 modified systems	164
6.32	TGA curves of BMI-2 modified epoxy systems (a) 5%, (b) 10% and (c) 15% BMI-2 modified systems	165
6.33	TGA curves of BMI-3 modified epoxy systems (a) 5%, (b) 10% and (c) 15% BMI-3 modified systems	166
6.34	TGA curves of BMI-4 modified epoxy systems (a) 5%, (b) 10% and (c) 15% BMI-4 modified systems	167

FIGURE NO.	TITLE	PAGE NO.
6.35	TGA curves of 10% siliconized/BMI-1 systems (a) 5%, (b) 10% and (c) 15% BMI-1 modified 10% siliconized epoxy systems	168
6.36	TGA curves of 10% siliconized/BMI-2 systems (a) 5%, (b) 10% and (c) 15% BMI-2 modified 10% siliconized epoxy systems	169
6.37	TGA curves of 10% siliconized/BMI-3 systems (a) 5%, (b) 10% and (c) 15% BMI-3 modified 10% siliconized epoxy systems	170
6.38	TGA curves of 10% siliconized/BMI-4 systems (a) 5%, (b) 10% and (c) 15% BMI-4 modified 10% siliconized epoxy systems	171
7.1	SEM micrographs of (a) unmodified epoxy, (b) 5%, (c) 10% and (d) 15% siliconized epoxy systems	179
7.2	SEM micrographs of (a) 10% BMI-1, (b) 10% BMI-2 (c) 10% BMI-3 and (d) 10% BMI-4 modified epoxy systems	180
7.3	SEM micrographs of (a) 10% BMI-1, (b) 10% BMI-2 (c) 10% BMI-3 and (d) 10% BMI-4 modified siliconized (10%) epoxy systems	181
7.4	Effect of siloxane content on water absorption of epoxy system	184
7.5	Effect of bismaleimides content (BMI-1, BMI-2, BMI-3 and BMI-4) on water absorption of epoxy system	184
7.6	Effect of bismaleimides content on water absorption of 10% siliconized epoxy system	185