

## **List of Figures**

Figure 1.1: Categories in Wireless Communication	2
Figure 1.2: Wireless Ad hoc Network	7
Figure 1.3: Wireless Sensor Network	9
Figure 1.4: Wireless Mesh Network	10
Figure 1.5: Cross Layering	13
Figure 3.1: Energy Consumption vs. Number of Sensor Nodes	40
Figure 3.2: Life Time vs. Number of nodes	41
Figure 3.3: Energy Consumption vs. Number of Sources nodes (Constraint Case)	41
Figure 3.4: Life Time vs. Number of Sources (Constraint Case)	42
Figure 4.1 Route Establishment in AODV Routing Protocol	49
Figure 4.2: Route Establishment in DSR Routing Protocol	51
Figure 4.3: Packet Confirmation for Neighboring Nodes	51
Figure 4.4: Directed Path in TORA	54
Figure 4.5: Performance of Routing Protocols in Normal Situation	55
Figure 4.6: Performance of Routing Protocols in Constraint Situation	56
Figure 4.7: Performance of AODV/DSDV with improved routing parameters	58
Figure 4.8: Ad hoc Network with congested/non-congested route	58
Figure 4.9: Packet Delivery Ratio Vs Packet Rate	63
Figure 4.10: Average End-to-End Delay Vs Packet Rate.	64
Figure 4.11: Normalized Routing Overhead Vs Packet Rate	64
Figure 4.12: Packet Delivery Ratio Vs Number of Connections	65
Figure 4.13: Average End-to-End Delay Vs Number of Connections	66
Figure 5.1: Cross Layering used in ECLAP	73

Figure 5.2: Duty scheduling scheme	75
Figure 5.3: Energy Consumption vs. number of nodes	79
Figure 5.4: Energy Consumption vs. Duty cycle	80
Figure 5.5: Lifetime vs. number of nodes	81
Figure 5.6: Lifetime vs. Duty cycle	81
Figure 5.7: Packet Delivery Ratio vs. Number of Nodes	82
Figure 5.8: Packet Delivery Ratio vs. Duty Cycle	83
Figure 6.1: Cross Layer Module for CL-TORA	89
Figure 6.2: Throughput vs. Number of Nodes	93
Figure 6.3: Average End to End Delay vs. Number of Nodes	93
Figure 6.4: Routing Overhead vs. Number of Nodes	94
Figure 7.1: Packet Delivery Ratio vs. Number of Nodes	104
Figure 7.2: Hop Delay vs. Number of Nodes	105
Figure 7.3: Routing Overhead vs. Number of nodes	106
Figure 8.1: Average end-to-end delay vs. Number of nodes (IEEE 802.11 rate 1 pps)	121
Figure 8.2: Average end-to-end delay vs. Number of nodes (TDMA 1 pps)	121
Figure 8.3: Average end-to-end delay vs. Number of nodes (IEEE 802.11 rate 5 pps)	122
Figure 8.4: Average end-to-end delay vs. Number of nodes (TDMA 5 pps)	122
Figure 8.5: Packet delivery fraction vs. Number of nodes (IEEE 802.11 rate 1 pps)	123
Figure 8.6: Packet delivery fraction vs. Number of nodes (TDMA 1 pps)	124
Figure 8.7: Packet delivery fraction vs. Number of nodes (IEEE 802.11 rate 5 pps)	124
Figure 8.8: Packet delivery fraction vs. Number of nodes (TDMA 5 pps)	124
Figure 8.9: Routing load vs. Number of nodes (IEEE 802.11 rate 1 pps)	125

Figure 8.10: Routing load vs. Number of nodes (TDMA 1 pps)	126
Figure 8.11: Routing load vs. Number of nodes (IEEE 802.11 rate 5 pps)	126
Figure 8.12: Routing load vs. Number of nodes (TDMA 5 pps)	126