

List of figures

Figure 1.1 Light propagation through an asymmetric and free-standing planar waveguide structure.	5
Figure 1.2 Structure of POF	6
Figure 1.3 Loss spectrum of PMMA fiber	12
Figure 1.4 Illuminations using POF	19
Figure 2.1 Energy level diagram of a typical organic dye molecule	33
Figure 2.2 Absorption spectra of Rh B dye (5×10^{-4} mol/dm ³) dissolved in various solvents.	35
Figure 2.3 Molecular formula and optimized structure of Rhodamine B with labeling of atoms in gaseous phase.....	36
Figure 2.4 Kohn-Sham Frontier molecular orbitals of Rhodamine B	37
Figure 2.5 Fluorescence spectra of Rh B dye dissolved in methanol at different concentrations. Inset shows red-shift of peak fluorescence with the concentration of Rh B.....	40
Figure 2.6 Fluorescence decay curve, instrument response (IR) curve, fitting line and fitting residue of Rh B in methanol. Excitation: 379 nm laser (0.1 mW, 69ps); emission 590 nm.	41
Figure 2.7 (a) Shows the schematic of experimental setup. (b) Lasing spectrum of Rh B solution in Butanol at a pump power of 15 mW and (c) shows the emission intensity and FWHM of emission band versus pump power.	43
Figure 2.8 The graph illustrates the lasing intensities of Rh B dye (5×10^{-4} mol/dm ³) dissolved in butanol at different pump powers. The spectrum moves towards shorter wavelengths with growing pump power.	45
Figure 2.9 Schematic of a quartz cuvette with its resonant condition.	46
Figure 2.10 Three measured laser spectra using Rh B dissolved (5×10^{-4} mol/dm ³) in ethanol, butanol and glycerol as the active gain medium at a pump power of 15 mW. The change of solvent introduces an over-all shift of the output spectra due to a shift of the gain-spectrum of the dissolved laser dye.	48
Figure 2.11 Resonant modulation of laser modes of Rh B dye dissolved in methanol at a pump power of 15 mW. Inset shows the enlarged view of the variation in the thickness of the two walls of the cuvette.....	50

Figure 2.12. Dependence of the emission intensity on stripe length at three different pump powers (3, 5, 20 mW) for dye dissolved in butanol. The solid lines are fits to the data using equation 2.7.....	52
Figure 3.1 Schematic and photograph of MMA distillation set up	61
Figure 3.2 Polymerisation of methyl methacrylate to get poly-methyl methacrylate.....	62
Figure 3.3 Photograph of oil bath.....	63
Figure 3.4 The steps involved in photo-copolymerization technique	66
Figure 3.5 The different steps involved in the interfacial gel polymerization technique.....	67
Figure 3.6 Schematic diagram and setup of heat drawing workstation.....	68
Figure 3.7 IR Lamp heating furnace.....	68
Figure 3.8 Fiber attenuation measurement using cutback method	70
Figure 3.9 Light propagation through drawn fiber	72
Figure 3.10 Experimental setup of SIF technique	73
Figure 3.11 Different types of dye doped PMMA preforms (a) SI, (b) hollow and (c) GI respectively.	74
Figure 3.12 Dye doped PMMA preform after the fiber is drawn and enlarged cross sectional view of Rh6G-hollow POF using a CCD camera	74
Figure 3.13 Refractive index of the different types of dye doped fibers.....	75
Figure 3.14 Fluorescent emission from Rh6G-hollow-POF at different pump power	76
Figure 3.15 Comparison of fluorescence emission from Rh6G doped hollow, GI and SI POFs at a pump power of 30 mW.....	77
Figure 3.16 FWHM of the spectral emission from Rh6G doped hollow, GI and SI POF as a function of pump power	78
Figure 3.17 Variation of emission peak and output intensity with length of Rh6G doped SI-POF (a), GI-POF (b) and Hollow POF (c) at a pump power of 30 mW.	79

Figure 3.18 Normalized output intensity as a function of number of pump pulses for Rh6G doped different type of POFs at a pump power of 30 mW. .	81
Figure 3.19 Normalized emission intensity for Rh6G-hollow fiber at different pump power versus the exposure time	82
Figure 4.1 Illustration of a (a) Fabry-Perot laser and (b) a ring laser respectively	91
Figure 4.2 Whispering gallery in St. Paul’s Cathedrel, London, UK.....	94
Figure 4.3 Acoustical reflection from the surface	95
Figure 4.4 (a) Four typical whispering gallery microcavity; microsphere, micro disk, microcylinder, and microtoroid. (b) Geometrical optics of the WGM resonance; (c) wave optics representation of a WGM.....	96
Figure 4.5 (a) Schematic of the cylindrical dielectric waveguide and cross section of the waveguide with inner radius b and outer radius a. Relative permittivity of each medium are labelled as ϵ_1 , ϵ_2 and ϵ_3	99
Figure 4.6 Simulation model of the WGM resonator with waveguide coupling.	101
Figure 4.7 (a) Visualization of the steady-state electric field pattern in the air-core microring resonator at the frequency of $f_r = 198.257$ THz ($m = 27$). (b) Power flow distribution. (c) Resonant frequency spectrum of the microresonator.	102
Figure 4.8 Schematic representation of micro disk cavity resonator model of dye doped hollow POF (DDHPOF).....	105
Figure 4.9 Schematic of experimental setup.	106
Figure 4.10 Emission spectra from 400 micron DDHPOF at different pump power.	107
Figure 4.11 The output laser power versus the pump power for different diameter DDHPOFs. The linear dependence and change in slope reveal laser action. The lasing threshold is at about 20 mW.	108
Figure 4.12 The emission spectra from a 400 micron diameter DDHPOF after bleaching of the dye.....	108
Figure 4.13 The spectra shows the typical WGM laser emission from different diameter DDHPOF as 310, 400 and 500 micron with pump power maintained at around $1.5 - 2 \times P_{th}$	109

Figure 4.14 Peak fluorescence versus diameter, D of the cylindrical microcavity laser.....	110
Figure 4.15 Relation between FSR and diameter	110
Figure 4.16 Emission spectrum from DDHPOF as a function of pump power by spot illumination technique and right inset shows the expanded modes at 26 mW.	113
Figure 4.17 Emission spectrum from DDHPOF as a function of pump power by stripe illumination technique and right inset shows the expanded modes at 26 mW.	115
Figure 4.18 Shift in peak wavelength as a function of pump power.	116
Figure 4.19 Line narrowing as a function of pump power (when the pump beam is focussed with convex and cylindrical lens	117
Figure 4.20 Integrated emission intensity from DDHPOF as a function of pump power for cylindrical and convex lens focussing	118
Figure 5.1 Typical output spectrum for a symmetric resonant (SRC) cylindrical microcavity having $D = 660 \mu\text{m}$ and $d = 290 \mu\text{m}$. Left inset: schematic diagram of different regions in an SRC cavity with WGM resonance. Right inset: shows the schematic of experimental setup.	129
Figure 5.2 (a) Simulation modal (b) Electric field distribution (c) Resonance spectrum and (d) Isotropic far-field emission at resonant frequency from SRC.	131
Figure 5.3 Shows generalized reflection law includes Goos-Hanchen (G-H) shift (ΔS) and an increase in the angle of the reflected ray from θ_r to ' $\theta + \Delta\theta$ ' (FF).	133
Figure 5.4 (a) Simulation modal (b) Electric field distribution (c) Resonance spectrum and (d) Anisotropic far-field emission at resonant frequency from ARC.	134
Figure 5.5 Emission spectra from an ARC at different pump power. Right inset shows the output intensity and FWHM of emission as a function of pump power (Laser threshold is indicated with arrow mark). Left inset shows the enlarged view of photograph of ARC taken in a CCD camera.	136
Figure 5.6 (a) Emission from ARC, when collecting fiber moves in Z-direction (b) Variation of Q factor of the highest intensity lasing mode with different	

propagation length. (c) Far-field angular distributions of emission intensities of all lasing modes from an ARC and SRC cavity.	139
Figure 5.7(a) Emission spectra from ARC, when the collecting fiber moves in X-direction (1 to 20 mm). (b) Three laser modes with almost equal intensities were sustained and stable after a propagation distance from 16 to 20 mm in X-direction.	140
Figure 5.8 Schematic of an asymmetric annular microcavity with radius R_1 . The radius of hole is R_2 , the distance to cavity surface is t	141
Figure 5.9 (a) Electric field distribution of HQM (b) far-field emission pattern on-resonance condition (c) Electric field distribution of LQM and (d) corresponding far-field emission pattern	142
Figure 5.10 Effect of hole position (t/R_1) on the far-field profile of an ARC	144
Figure 5.11 Typical laser emission spectrum of deformed RhB-doped hollow polymer optical fiber. The left inset shows the cross-sectional view of the deformed hollow polymer fiber. The right inset shows the far-field emission pattern.	145
Figure 6.1 Emission spectrum of dye coated on glass fiber with diameter $D = 420 \mu\text{m}$ and pump power of 24 mW ($P_{\text{th}} \times 8$). The inset depicts the measurement geometry	155
Figure 6.2. Typical emission spectra recorded. From the bottom to top, $P = P_{\text{th}} \times 1.33$, $P = P_{\text{th}} \times 2.67$, $P = P_{\text{th}} \times 5.67$ and $P = P_{\text{th}} \times 9.33$ respectively. Inset shows the output laser power (numerically integrated output intensity) versus the pump power.	155
Figure 6.3. Resonant modulation of the waveguided modes and whispering gallery modes.....	157
Figure 6.4. Schematic representation of the experimental setup. Inset shows the Ray-tracing description of light propagating in a planar waveguide.....	159
Figure 6.5. The absorption and photoluminescence spectra of Rh6G doped in a PMMA film. Inset, chemical structure of Rh6G	160
Figure 6.6. The emission spectra from the dye-doped polymer film measured in the direction parallel (A) and perpendicular (B) to the film surface at the same excitation intensity (20 mW); emission intensity B is magnified by 50. The inset illustrate the experimental setup	161

Figure 6.7. Output emission intensity integrated over all wavelengths as a function of pump power (filled square) and dependence of the FWHM on the pump power (open squares).....	163
Figure 6.8. The emission spectra from planar waveguide at various pump power. Inset : Blue-shift in peak wavelength as a function of pump power.	163
Figure 6.9. The output intensity (a) and FWHM (b) of the emission spectra from the planar waveguide as a function of viewing angle by keeping a constant pump power of 25 mW.....	165
Figure 6.10 Multimode laser emission from 50 μm thick rhodamine 6G doped PMMA films at a pump power of 22 mW. Left inset, schematic diagram of the setup for intensity distribution measurement. Right inset, intensity distribution of the output of a planar microcavity (data points were well-fitted with a Gaussian curve (before and after laser threshold)).....	167
Figure 7.1 Schematic of a thin ring-type microcavity with its refractive index profile.....	176
Figure 7.2 Cross-sectional view of different size micro-ring cavity using microscopic camera.	177
Figure 7.3 WGM lasing spectrum from a thick micro-ring cavity. Top inset shows the schematic of experimental setup and bottom inset shows the integrated emission intensity of the peaks as a function of pump pulse energy.	179
Figure 7.4 Modulated WGM lasing spectrum from sample 2 with increasing PPEs.....	181
Figure 7.5 (a) Strongly modulated lasing mode spectra from a sample 3 at different PPE. Almost single mode emission is observed at a PPE of 1000 μJ . (b) shows the magnified version of the highest intensity lasing line at 585.4 nm with Gaussian fit and (c) shows emission intensity of 585.4 nm mode and integrated emission intensity versus pump power.	183

List of tables

Table 1.1 Properties of PMMA	12
Table 2.1 Vertical excitation data of Rhodamine B in different solvent	38
Table 2.2 χ_1 and χ_2 dihedral angles (degree) of the Rh B dye in different solvents in the ground and excited state at the DFT/TD-DFT – B3LYP/6-31 G (d) and C-PCM solvation model.....	39
Table 2.3 Photophysical and chemical properties of Rh B dye in different solvents..	42
Table 2.4. Comparison of emission peak and number of longitudinal resonant modes for different solvents.	49
Table 3.1 Result obtained under various drawing conditions	69
Table 3.2 Summarize emission characteristics of Rh6G doped Hollow, GI and SI POFs.....	82
Table 4.1 The total number of modes, FWHM of modes, Observed and calculated FSR of WGMs for different diameter DDHPOFs.....	111
Table 7.1 Details of the sample, lasing threshold and modulation parameters of the different ring-thickness microcavities.	184