

List of Figures

Chapter 1	INTRODUCTION	Page No.
Figure 1.1	Electron–hole pair generation and emission of photon by semiconductor.	6
Figure 1.2	(a) Quantum dot structure. A nanometer scale semiconductor crystallite is embedded inside an insulating material and (b) Energy level diagram for semiconductor, quantum dot and atom. The energy levels of excited carriers (electrons and holes) become quantized due to finite nano dimension of the semiconductor.	7
Figure 1.3	Schematic representation of the changes of density of state with change in number of atoms in material (AO: atomic orbital)	9
Figure 1.4	Flow chart for growth process for Quantum dots in glass matrix.	16
Figure 1.5	Schematic drawing of the temperature dependence of the glass volume for the transition liquid-glass in comparison to the case of crystallization.	18
Figure 1.6	Schematic two dimensional illustration of atomic arrangement in (a) Crystalline silica and (b) Glassy or liquid silica.	20
Figure 1.7	Schematic two dimensional illustration of the structure of sodium silicate glass.	21
Chapter 2	THEORETICAL BACKGROUND AND EXPERIMENTAL TECHNIQUES	
Figure 2.1	Concentration profile around the nanocluster during the growth process. \bar{C} is the average concentration within the supersaturated solution and C_o is the concentration inside the nanocluster.	35

Figure 2.2	Electronic balance used to weigh chemical compounds.	38
Figure 2.3	(a) The ball milling machine and (b) Zirconium balls and bottle that were used for mixing.	39
Figure 2.4	(a) High temperature box furnace used for glass melting and (b) Programmable furnace used for annealing process.	39
Figure 2.5	Schematic representation of X-ray diffraction from crystal planes.	41
Figure 2.6	Geometric arrangement of X-ray Diffractometer.	43
Figure 2.7	Effect of crystallite size on diffraction pattern.	44
Figure 2.8	Photograph of X-ray diffraction system used in this study (RigakuMiniflex II).	46
Figure 2.9	(a)The schematic outline of a TEM and(b) TEM instrument used in this work (FEI Technai G ² T30).	48
Figure 2.10	Electron source of a TEM and imaging system.	49
Figure 2.11	Ray diagram of Transmission Electron Microscopy (TEM).	52
Figure 2.12	(a)Digital photograph of UV-Vis apparatus used for absorption study (Perkin Elmer Lambda-35 spectrophotometer) and (b)Schematic ray diagram of UV-Visible absorption spectrometer.	57
Figure 2.13	Schematic of PL from the standpoint of semiconductor or crystalline systems (left) and molecular systems (right).	59
Figure 2.14	(a)Digital photograph of Horiba Jobin Yvon Fluorolog 3 spectrofluorometer used in present study and (b) Setup of the PL spectrometer Jobin Yvon Fluorolog 3. The arrangement allows flexibility in geometry and excitation source. Due to the double monochromator concept no filters are required.	62

Figure 2.15	Schematic diagram of transition in molecule.	65
Figure 2.16	The Raman microscope (Model: Renishawin Via) used in present thesis.	67
Figure 2.17	Digital photograph of Scanning Electron Microscopy (SEM) and EDAX setup used in present work.	68
Figure 2.18	Schematic diagram of Scanning Electron Microscopy (SEM).	69
Figure 2.19	A schematic representation showing how X-rays are produced which are used by the EDAX to analyze samples.	70
Figure 2.20	Digital photograph of DSC instrument (TA Instruments SDT QSeries 600).	71
Chapter 3	GROWTH AND CHARACTERIZATION OF CdS QUANTUM DOTS	
Figure 3.1	Hexagonal crystal structure of CdS [40].	75
Figure 3.2	XRD pattern of four glass compositions without any heat treatment.	81
Figure 3.3	Schematic representation of XRD pattern of crystalline CdS. The inset shows the complete 2θ range of diffraction data according to reference 22.	82
Figure 3.4	Some selective XRD pattern of glass samples from glass composition 1 (GC1). Heat treatment time and temperature are shown in sample identification. The inset shows the XRD scan for one of the sample with higher intensity.	83
Figure 3.5	Some selective XRD pattern of glass samples from glass composition 2 (GC2). Heat treatment time and temperature are shown in sample identification. Diffraction peaks are indexed according to Figure 3.3.	84

Figure 3.6	Some selective XRD pattern of glass samples from glass composition 3 (GC3). Heat treatment time and temperature are shown in sample identification. Diffraction peaks are indexed according to Figure 3.3.	85
Figure 3.7	Some selective XRD pattern of glass samples from glass composition 4 (GC4). Heat treatment time and temperature are shown in sample identification. Diffraction peaks are indexed according to Figure 3.3.	86
Figure 3.8	Calculated temperature dependant glass viscosity from equation 3.1 for the region relevant to CdS quantum dot growth (heat treatment) for the four different glass compositions. The inset depicts the viscosity in temperature range 0 °C to 1000 °C for the four glass compositions.	88
Figure 3.9	CdS dot size as the function of growth time t at 600 °C in four batches of glass compositions. The solid lines are only guide to eye. The inset shows the linear relation (the least square fit shown by solid lines) between the size and $t^{1/3}$ indicating the growth by diffusion as expected from Equation 3.2.	90
Figure 3.10	Growth of CdS dot size with growth time at 700 °C in four glasses of different compositions. The solid lines are only guide to eye. The inset shows the linear relation (the least square fit shown by solid lines) between the size and $t^{1/3}$ as expected from Equation 3.2.	91
Figure 3.11	Dependence of CdS dot size growth on glass viscosity for different growth durations. The solid lines are only guide to eye. The inset depicts the linear relation (the least square fit shown by solid lines) between the dot size and $\eta^{-1/3}$ as expected from Equation 3.4.	93

Figure 3.12	Room temperature absorption spectra of various samples: (a) GC1-700 °C-2 hrs, (b) GC1-600 °C-6 hrs, (c) GC3-600 °C-6 hrs, (d) GC3-700 °C-2 hrs, (e) GC2-700 °C-2 hrs, (f) GC1-700 °C-12 hrs, (g) GC4-700 °C-24 hrs and (h) GC4-700 °C-48 hrs. The absorption spectra are vertically shifted for clarity.	94
Figure 3.13	Room temperature emission (photoluminescence) spectra of some selected samples as identified in the figure and the identification has the same meaning as mentioned in the Figure caption 3.12.	95
Figure 3.14	Plot of exciton peak (of Figure 3.12) energy versus $1/d^2$ demonstrating the quantum confinement of CdS dots in glass matrices. The solid line represents the least square fit (Equation 3.5) to the data.	96
Figure 3.15	Thermal analysis of glass sample: TGA (inset) and DTA shows the glass transition at 531 °C.	99
Figure 3.16	X- ray diffraction pattern of CdS doped glass samples annealed at 600 °C and 625 °C for different time durations. In the figure the pattern labeled by “melted” represents the glass sample melted at 1050 °C and rapidly quenched in air.	100
Figure 3.17	Transmission electron micrographs of glass sample (a) annealed at 600 °C for 4 hrs, (a1) corresponding selective area electron diffraction (SAED) pattern, (b) annealed at 625 °C for 5 hrs and (b1) corresponding SAED pattern. Contrast of white spots is increased for better visibility.	101
Figure 3.18	Representative optical absorption spectra measured at room temperature for CdS doped glass samples annealed at (a) 600 °C for 10 min, (b) 600 °C for 30 min, (c) 600 °C for 4 hrs, (d) 625 °C for 5 hrs (e) 625 °C for 8 hrs and (f) 625 °C for 10 hrs.	103

Figure 3.19	Plot of absorption edge as a function of $1/d^2$ demonstrating the quantum confinement of CdS dots in glass matrix.	104
Figure 3.20	Glass samples in white light and ultraviolet radiations. (a) glass sample melted at 1050 °C and rapidly quenched in air (transparent), (b) annealed at 600 °C for 10 min, (c) annealed at 625 °C for 10 hrs, (d) 625 °C for 8 hrs and (e) 600 °C for 4 hrs.	105
Figure 3.21	Room temperature photoluminescence spectra of CdS doped glass samples at the 350 nm excitation. The thermal treatment conditions are identical with the labels of absorption spectra shown in Figure 3.18.	106
Figure 3.22	A plot of PL peak energy versus full width at half maximum (FWHM) of the PL emission spectrum for various samples showed in Figures 3.18 and 3.21. The continuous curve is only a guide to eye showing the trend.	107
Chapter 4	GROWTH AND CHARACTERIZATION OF CdSe QUANTUM DOTS	
Figure 4.1	Hexagonal crystal structure of CdSe semiconductor [10].	113
Figure 4.2	(a) Set of some selective X-ray diffractograms of CdSe doped glass samples and (b) is the full scan XRD pattern of glass sample annealed at 650 °C for 12 hrs.	118
Figure 4.3	Glass sample with heat treatment at 650 °C for 8 hrs (a) TEM image of CdSe-QDs and (b) is corresponding Selected Area Electron Diffraction (SAED) pattern image. Indexing has been done accordingly CdSe - JCPDS file: 08-0459.	121
Figure 4.4	Glass sample with heat treatment at 700 °C for 4 hrs (a) TEM image of CdSe QDs and (b) is corresponding Selected Area Electron Diffraction (SAED) pattern image. Indexing has been done accordingly CdSe- JCPDS file: 08-0459.	123

Figure 4.5	Room temperature optical absorption spectra of various glass samples annealed at different time and temperature: (a) 600 °C 4 hrs, (b) 600 °C 6 hrs, (c) 650 °C 4 hrs, (d) 600 °C 12 hrs, (e) 650 °C 8 hrs, (f) 680 °C 12 hrs and (g) 700 °C 10 hrs.	124
Figure 4.6	Plot of first exciton peak energy versus $1/d^2$ demonstrating the quantum confinement of CdSe dots in glass matrices. The solid line represents the least square fit (Equation 4.1) to the data.	126
Figure 4.7	Calculated average dot size from first exciton absorption peak and experimentally observed quantum dot size by XRD and TEM. The Solid lines are just guide to eye.	128
Figure 4.8	Normalized photoluminescence spectra of some selected samples as identified in the figure and the identification has the same meaning as mentioned in the figure caption 4.5. Spectra were taken at room temperature.	129
Figure 4.9	Variation of FWHM of photoluminescence spectra with characteristic PL peak position.	130
Figure 4.10	Variation of FWHM of photoluminescence spectra with dot size.	131
Figure 4.11	Room temperature Raman spectra in the region for LO phonon for CdSe quantum dots in borosilicate glass matrix of different dot sizes. The inset shows the extended Raman spectrum for glass sample with dot size 8.1 nm to show 2LO peak at 415 cm^{-1} .	132
Figure 4.12	Plot of the experimental peak frequency of the LO phonon peak (left Y-axis) and FWHM of the LO phonon peak (right Y-axis) as a function of dot size. Solid lines are just guide to eye.	133

Chapter 5	GROWTH AND CHARACTERIZATION OF Sb_2S_3 QUANTUM DOTS	
Figure 5.1	SEM image of bleached transparent glass sample heat treated at 1000 °C for 30 minutes and the EDAX spectra of the highlighted area in the micrograph.	142
Figure 5.2	SEM image of bleached transparent glass sample heat treated at 1000 °C for 30 minutes, showing layered structure of antimony (Sb).	143
Figure 5.3	X-ray diffraction pattern of for bleached glass sample and the two peaks are identified and indexed using JCPDS No. 35-0732 for Sb and JCPDS No.72-1001 for S.	144
Figure 5.4	The most intense peak (used to determine the average dot size) of some selected XRD patterns of glass samples heat treated with different parameters (identified in the figure). The inset depicts the full XRD scan for glass sample annealed at 620 °C for 8 hrs	145
Figure 5.5	High resolution TEM image of glass sample annealed at (a) 550 °C for 4 hrs and (b) is the corresponding SAED image.	147
Figure 5.6	High resolution TEM image of glass sample annealed at (a) 600 °C for 4 hrs and (b) is the corresponding SAED image.	148
Figure 5.7	High resolution TEM image of glass sample annealed at (a) 620 °C for 8 hrs and (b) is the corresponding SAED image.	149
Figure 5.8	High resolution TEM image of glass sample annealed at (a) 650 °C for 6 hrs and (b) is the corresponding SAED image.	150
Figure 5.9	Room temperature Raman spectra of (a) reference glass sample and (b) for Sb_2S_3 doped glass sample.	151

- Figure 5.10** Room temperature absorption spectra of various Sb_2S_3 doped glass samples heat-treated at: (a) 550 °C for 1 hr, (b) 550 °C for 4 hrs, (c) 580 °C for 6 hrs, (d) 600 °C for 4 hrs, (e) 600 °C for 10 hrs, (f) 620 °C for 8 hrs and (g) 650 °C for 6 hrs. The inset shows the linear dependence of band gap E_g with $1/d^2$ where d is the average dot size. **153**
- Figure 5.11** Digital photograph of glass samples heat treated at various time and duration: (a) bleached transparent glass sample heat treated at 1000 °C for 30 minutes (b) 550 °C for 1 hr, (c) 550 °C for 4 hrs, (d) 580 °C for 6 hrs, (e) 600 °C for 4 hrs, (f) 600 °C for 10 hrs, (g) 620 °C for 8 hrs and (h) 650 °C for 6 hrs, (i) 650 °C for 10 hrs (j) without bleached 600 °C for 4 hrs and (k) without bleached 700 °C for 6 hrs. **155**