

LIST OF FIGURES

	Page	
1.1	Cartoon showing the difference between single crystal, polycrystalline and amorphous forms of the material along with their XRD signatures.	22
1.2	Pie-chart depicting applications of single crystals.	23
1.3	Photograph of scintillator crystals under UV illumination.	24
2.1	Free-energy curve for the surface free-energy, volume free-energy and total free-energy as a function of radius of nuclei.	42
2.2	Estimated shares of world crystal: methods of growth.	44
2.3	Photograph of the Crystal puller system [Cyberstar make Oxypuller] along with schematic of CZ puller.	47
2.4	Photograph of a Bridgman crystal growth system along with the schematic of the furnace.	49
2.5	Photograph of a vacuum hot press.	50
2.6	Bragg's law of x-ray diffraction and schematic of X-ray powder diffractometer.	51
2.7	The schematics of Laue back reflection method.	53
2.8	Schematic diagram of a double beam UV-VIS-NIR spectrophotometer.	53
2.9	The schematic diagram of fluorescence spectrometer FLP920.	56
2.10	A typical setup for recording thermally stimulated luminescence.	58
2.11	Schematic depiction of the scintillation process.	60
2.12	Schematic of photodiode based scintillator detector.	61
2.13	Partitioning of the unit cell into atomic spheres (A) and an interstitial region	67

(B).

3.1	Temperature profiles in the furnace (a) blank furnace, (b) furnace with silica crucible (controlling thermo-couple at the crucible bottom) and (c) furnace with crucible (controlling thermo-couple 3 cm above the crucible bottom). Furnace diagram is shown on the right side of the figure.	71
3.2	Photograph of silica glass crucibles (a) before and (b) after carbon coating.	72
3.3	Photograph of (a) crystal ingot and (b) polished cylinder.	73
3.4	Transmission (a) and fluorescence (b) spectra of 0.2 mole% Tl doped CsI single crystal. (sample thickness 20 mm).	73
3.5	(a) Rocking curve for (4 2 2) plane of 0.1 mole% Tl doped CsI and (b) 2θ position of same plane. (X-ray energy- 9750 eV).	74
3.6	Transmission spectra of Type-I (a) and Type-II (b) crystals after 10 days of daylight exposure (sample thickness - 20 mm).	75
3.7	Calculated induced absorption (\circ), individual fitted peaks and envelope fitted peak.	75
3.8	TSL glow curves of (a) Type-I and (b) Type-II crystals. (heating rate 0.5°C/s).	76
3.9	Afterglow (a) and thermally stimulated glow (b) spectrum of type-II crystal.	76
3.10	Scintillation performance of 0.2 mole% Tl doped CsI crystal (a) Calibration curve drawn from detector response to different radionuclide and (b) a typical gamma spectra of ^{137}Cs recorded using detector (30 mm diameter and 25 mm thickness).	76
3.11	Modified Bridgman furnace diagram (a) schematic of the crystal growth	80

system, (b) enlarge view of furnace along with the control and monitoring thermocouple positions (green coloured ones are the controlling and the red coloured are the monitoring thermocouples) and (c) photograph of the fabricated crystal growth system.

3.12	Radial and axial temperature gradients of the crystal growth furnace.	81
3.13	AutoCAD drawing of the crucible used in the crystal growth in the modified Bridgman furnace.	81
3.14	The schematic diagram of the complete growth process of the CsI:Tl single crystal in the modified Bridgman furnace. (1) Loading of the crucible and melting of the material, (2) Lowering of the crucible to lower zone and solidification, (3) Locking of the crucible in the furnace and rotation by 180 degree and (4) retrieval of the crystal.	82
3.15	Photograph of crystal ingot grown using the modified Bridgman technique and processed scintillator.	85
3.16	Absorption spectra of CsI crystal as a function of Tl concentration.	85
3.17	Electronic band structure of CsI calculated using Exciting code.	85
3.18	Radio-luminescence spectra of Tl doped CsI as a function of Tl concentration.	86
3.19	Typical gamma spectra of ^{137}Cs and ^{60}Co as recorded using a $18 \times 18 \times 18 \text{ mm}^3$ cube prepared from the CsI:Tl crystal and coupled to a PMT.	86
3.20	Non proportionality response of Tl doped CsI as a function of photon energy.	87
3.21	Typical gamma spectra of ^{137}Cs and ^{60}Co as recorded by CsI:Tl crystal ($45 \text{ mm } \phi \times 45 \text{ mm L}$) coupled to a PMT.	88

3.22	Typical gamma spectra of ^{137}Cs and ^{60}Co as recorded by $18 \times 18 \times 18 \text{ mm}^3$ CsI:Tl coupled to a P-I-N photodiode.	89
3.23	The decay profiles of (a) Undoped CsI for gamma and (b) CsI:Tl for gamma and alpha particle.	89
3.24	Photograph of as-grown Tl doped NaI crystal.	91
3.25	Typical gamma spectra of ^{137}Cs and ^{60}Co recorded using a NaI:Tl crystal scintillator ($45 \text{ mm } \phi \times 45 \text{ mm L}$) coupled to a PMT.	91
4.1	Photograph of a typical $\text{NaBi}(\text{WO}_4)_2$ single crystal ingot.	95
4.2	Schematic of Photo-conductivity setup.	96
4.3	Spectral dependence of transmission and reflectivity of as-grown $\text{NaBi}(\text{WO}_4)_2$ crystal.	96
4.4	Excitation, emission and temperature dependence of emission for $\text{NaBi}(\text{WO}_4)_2$ crystal (a) and (b) as-grown, (c) and (d) annealed in air, and (e) and (f) annealed in vacuum.	98
4.5	Effect of temperature on emission of as-grown $\text{NaBi}(\text{WO}_4)_2$ crystal.	100
4.6	Effect of after growth annealing on emission of as-grown $\text{NaBi}(\text{WO}_4)_2$ crystal.	100
4.7	Partial density of states of constituent atoms of $\text{NaBi}(\text{WO}_4)_2$ crystal.	101
4.8	Spectral dependence of excitation and photoconductivity of as-grown $\text{NaBi}(\text{WO}_4)_2$ crystal.	102
4.9	Effect of annealing on photoconductivity of $\text{NaBi}(\text{WO}_4)_2$ crystal.	102
4.10	Photographs of as-grown $\text{NaGd}(\text{WO}_4)_2$ crystal ingots.	105
4.11	Powder XRD pattern of un-doped $\text{NaGd}(\text{WO}_4)_2$ along with the calculated	106

	pattern and residual .	
4.12	Calculated unit cell structure of NaGd(WO ₄) ₂ .	106
4.13	NaGd(WO ₄) ₂ crystal samples oriented along c-axis and the Laue pattern.	107
4.14	(a) Plot of square-root of absorption as a function of photon energy. (b) Transmission spectra of NaGd(WO ₄) ₂ crystals.	108
4.15	Emission and excitation spectra of NaGd(WO ₄) ₂ crystal at room temperature.	109
4.16	(a) Calculated band structure of NaGd(WO ₄) ₂ . (b) Calculated density of state of each atom species in NaGd(WO ₄) ₂ .	109
4.17	Decay profile of NaGd(WO ₄) ₂ . (Crystal-I; excitation: 313 nm, emission: 500 nm).	110
4.18	Temperature map of luminescence intensity of crystal-I and II.	110
4.19	(a) Temperature map of excitation spectra of crystal-I.(with emission at 500 nm). (b) Temperature map of emission spectra of crystal-I.(with excitation at 270 nm).	111
4.20	Excitation spectra of Yb in NaGd(WO ₄) ₂ matrix.	111
4.21	Emission spectrum of Yb in NaGd(WO ₄) ₂ for excitation at 975 nm.	111
5.1	SEM image of (a) as-prepared nano particles and (b) optically transparent ceramic.	116
5.2	Raw data of SANS experiment carried out on CaF ₂ samples.	117
5.3	Processed SANS data.	117
5.4	Pore size distribution in CaF ₂ samples as calculated from SANS data.	118
5.5	XRD spectra of as grown nano particles and OTC of CaF ₂ :Mn.	119
5.6	Optical image of a 2mm thick sample of Mn doped CaF ₂ transparent ceramic.	119
5.7	Transmission spectrum of a 1 mm thick sample of Mn doped CaF ₂	120

	transparent ceramic.	
5.8	XPS spectra of Mn 2 <i>p</i> peak of CaF ₂ :Mn OTC.	120
5.9	Glow curve of CaF ₂ :Mn OTC after irradiation with a dose of 100 mGy. The inset shows the dose linearity of CaF ₂ :Mn OTC.	123
5.10	Emission spectrum of Ce ³⁺ and excitation spectrum of Mn ²⁺ in CaF ₂ :Mn,Ce OTC showing the over-lapping of Ce emission band with Mn absorption. Inset shows the optical photograph of a CaF ₂ :Mn,Ce OTC.	123
5.11	Glow curves of CaF ₂ :Mn and CaF ₂ :Mn,Ce OTC after irradiation with 0.66 Gy. Inset shows the dose linearity of CaF ₂ :Mn,Ce OTC.	124
5.12	Optical photograph of a 25 mm diameter and 3 mm thick transparent ceramic of CaF ₂ :Mn.	126
5.13	Tanabe Sugano diagram for d ⁵ electronic configuration and recorded excitation spectrum (on the right) of CaF ₂ :Mn transparent ceramic at room temperature.	126
5.14	(a) Excitation and emission spectra of CaF ₂ :Mn transparent ceramic at room temperature. (b) Room temperature emission peak of CaF ₂ :Mn transparent ceramic corresponding to excitation different at different wave-lengths.	128
5.15	Temperature map of the entire excitation spectra in the 300-500 nm range for emission at 500 nm of a CaF ₂ :Mn transparent ceramic.	129
5.16	Enlarged temperature map of the excitation spectra in the range 3.25-2.75 eV (380-450 nm) for emission at 500 nm of a CaF ₂ :Mn transparent ceramic.	129
5.17	(a) Intensity as a function of temperature for excitation at 335 nm, 395 nm and 445 nm. (b) Temperature dependence of constituent peaks of 395 nm	130

excitation band for a transparent ceramic of CaF₂:Mn.

- 5.18 Temperature map for the decay profile of CaF₂:Mn transparent ceramic 130
(excitation: 395 nm; emission: 500 nm).
- 5.19 Temperature behavior of the two decay constants τ_1 and τ_2 of CaF₂:Mn 130
transparent ceramic. The τ_{avg} is the average time constant of the two decay
components.
- 5.20 X-ray induced radio-luminescence spectrum of a CaF₂:Mn transparent 131
ceramic.

LIST OF TABLES

	Page
2.1 List of techniques of crystal growth from liquid phase.	45
3.1 The scintillation decay constant of undoped and Tl doped CsI.	90
4.1 Parameters used to grow NaBi(WO ₄) ₂ single crystals.	95
4.2 Calculated structural parameters of NaGd(WO ₄) ₂ .	106